

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. **WEIGHT PANDUIT** NOMINAL В С STATIC CABLE O.D. LOAD** PART in. in. lbs./(a) in. lbs./(g) 100 pcs. NUMBER* in./(mm) (mm) (mm) (mm) 0.120 0.77 0.12 0.23 0.14 0.21 A1C12-A (3.0)(19.6)(3.0)(5.8)(64) (95)0.250 0.25 0.32 0.91 0.38 0.14 A1C25-A A1C25-A (6.4)(23.1)(6.4)(9.7)(64) (145)ACTUAL SIZE 0.375 1.04 0.38 0.51 0.14 0.42 A1C38-A (9.7)(190) (9.5)(26.4)(64)(13.0)REF 0.50 0.500 1.17 .50 0.64 0.14 A1C50-A (12.7)(64) (227) (29.7)(12.7)(16.3)NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE BY PANDUIT WITH RESPECT TO ADHESIVE BOND PERFORMANCE. AMONG OTHER THINGS, THE CONDITIONS UNDER WHICH THESE 0.59 MOUNTS MAY BÉ APPLIED AND/OR THE SURFACE TO WHICH (15.0)THEY MAY BE APPLIED ARE BEYOND PANDUIT'S CONTROL. TO APPLY MOUNT 1) REMOVE PROTECTIVE LINER. B REF 2) PLACE IN DESIRED LOCATION. 3) APPLY PRESSURE TO MOUNT. NOTES: *1. SEE CURRENT PRICE SHEET FOR PART NUMBER — TEAR TAB SUFFIX DESIGNATION FOR PACKAGE SIZE. -0.63-(16.0)ADHESIVE TAPE--PRESSURE SENSITIVE FOAM .040 (1.02) THICK WITH RUBBER ADHESIVE AND PROTECTIVE LINER. **MOUNT IS DESIGNED TO SUPPORT LISTED MAXIMUM STATIC (DIMENSIONS IN PARENTHESES ARE IN METRIC.) LOAD ON A CLEAN, DRY, SMOOTH, GREASE-FREE SURFACE. CAD FILENAME/LAYERS GB0431BA_PB_A1CCLIPS_02 TINLEY PARK, ILLINOIS A1C-A ADHESIVE CLIP UNLESS OTHERWISE SPECIFIED, UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: ALL DIMENSIONS ARE GIVEN (.X) ±0.1(2.5) (.XXX) ± 0.020(.5) (.XX) ±0.05(1.3) ANGLES ± 5° ADDED REF TO DIM 2 6/15/01 LGG GB0431BA 2 IN INCHES, THIRD ANGLE PROJECTION. DRAWN BY SCALE MAT'L: NONE 2-16-94 SJSU REVERSE TEAR TAB GB0431BA 1 SJSU GRAY DATE DRAWING NO. DWG l11-5-93 | SJSU INITIAL RELEASE GB0431BA R 11-5-93 PVC Α GB0431BA CHK 'D DATE DESCRIPTION SUP RFV BY CHK ECN - R CUST SIZE