



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





A202 Line Splitter

Specifications

Operating Voltage: 130V AC maximum

Operating Amperage: 15A AC maximum

Male Recepticle: Plugs into standard 2 conductor with ground outlets

Female Recepticle: Accepts 2 conductor without ground and 2 conductor with ground cords.

Features

- Enables clamp on meter amperage tests to be performed on devices with power cords without altering the cord.
- Can be used on 2 conductor no ground and 2 conductor with ground cords.
- X1 and X10 turn test areas
- Use the X10 test hole to measure smaller amperage. For example, 0.5A will be amplified to 5A for easier measurement and display on a clamp on meter
- Test holes for measuring voltage using test lead tips.

Dimensions

Size: 6" x 2.1" x 1.0" (152mm x 53mm x 25mm)

Weight: 0.4lbs (181g)

Copyright © 2015 Test Products International, Inc.

Accepts 2 conductor without ground and 2 conductor with ground cords

Test holes for measuring voltage using test lead tips

X1 and X10 turn test areas

Plugs into standard 2 conductor with ground outlets

