



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## A2200-A

### Positioning Product

GPS Receiver Modules  
Telematics Platforms



## SiRFstarIV - GPS Module:

### The Big Performance, Small Footprint Solution

The A2200 GPS modules enable fastest acquisition and tracking with the latest SiRFstarIV technology. This small form-factor module fully addresses the demand for lowest power consumption with, amongst other features, SiRFaware™ technology. The removal of jammers does not only facilitate designs of new products, but guarantees operation even in hostile environments. High sensitivity during acquisition or while tracking allows for use in many different environments and under toughest operating conditions.

#### Features

- Complete GPS module
- Jamming detection and removal
- Direct passive antenna support
- Best acquisition sensitivity
- Lowest tracking power consumption
- SiRFaware™ for constant Hot Start

#### Benefits

- Easy integration Minimal BOM
- Accurate positioning
- Fastest design-in
- Ideally suited for all small battery powered GPS applications

# GPS Solutions for Many Applications

With the mission to support our customers in implementing GPS functionality into their systems, Maestro Wireless Solutions is offering a distinct product portfolio to address a wide area of applications. These range from traditional telematics solutions to latest highly integrated consumer devices, all of them having their special requirements towards a GPS module. Based on SiRFstarIII and now also SiRFstarIV chip sets, Maestro Wireless Solutions GPS module solutions address different specific needs and combine high performance, low power consumption, and simplified integration effort. Our modules comply with the RoHS standard and are 100% electrically and functionally tested prior to packaging, thereby assuring the guarantee of the highest quality products.



Ordering information:  
A2200-A  
EVA2200-A Evaluation Board

## Technical Details A2200-A

### PERFORMANCE

<b>Channels</b>	48
<b>Correlators</b>	~ 400,000
<b>Frequency</b>	LI - 1,575 MHz
<b>Sensitivity<sup>1</sup></b>	
Tracking	- 163 dBm
Navigation	- 160 dBm
Acquisition (cold start)	- 148 dBm
<b>Position Accuracy<sup>2)</sup> (horizontal)</b>	< 2.5 m CEP (autonomous) < 2.0 m CEP SBAS
<b>Time To First Fix</b>	
Hot Start <sup>2)</sup>	< 1 s
Warm Start <sup>2)</sup>	< 35 s
Cold Start <sup>2)</sup>	< 35 s
<b>Navigation</b>	
Update Rate	1 Hz / 5 Hz Supported

### COMMUNICATION

UART - NMEA (Default)	
NMEA message Switchable	GGA, RMC, GSA, GSV, VTG, GLL, ZDA
Baud rate Switchable	4,800 (default) 1,200 to 115.2k
Ports	Tx (NMEA output) Rx (NMEA input)
UART - SiRF Specific SSB/OSP	
SiRFbinary protocol	Protocol for SiRFstar product family up to SSIII
Open Socket Protocol	Protocol extension for SiRFstarIV
Baud rate Switchable	57.6k (default) 1,200 to 115.2k
Ports	Tx (Binary output) Rx (Binary input)
SPI - NMEA/SiRF Specific	
Clock	Up to 6.8 MHz
Ports	DO (NMEA / Binary output) DI (NMEA / Binary input) SPI CLK (clock - input) SPI CS (chip select - input)

### HIGHLIGHTS

<b>SiRFnav™</b>	High availability and coverage; improved TTFF in weak signal environments
<b>SiRFaware™</b>	Keeps module in a state of readiness for rapid navigation (hot start)
<b>Jammer remover technology</b>	Detects and removes up to 8 in-band jammers with minimal loss of sensitivity
<b>A-GPS</b>	Embedded Extended Ephemeris (SiRFInstantFix1) and Ephemeris Push support
<b>MEMS I2C interface</b>	Prepared to use additional sensor information for improved navigation

### POWER

<b>Supply voltage</b>	3.0 to 3.6 VDC
<b>Average Current Draw</b>	(typical)
Full power mode (Searching) Peak Current	69mA
Full power mode (Searching) Average Current	52 mA
Full power mode (Tracking) Average Current	41 mA
Micro Power Mode (SiRFaware™)	35 uA
Hibernate Status	25 uA
<b>Antenna supply via Vant</b>	
Voltage range	up to 5.0V
Max. allowed current <sup>3)</sup>	50 mA

### MECHANICAL

<b>Dimensions</b>	
L x W x H	14 x 10.2 x 2.5 mm <sup>3</sup>
L x W x H	0.55" x 0.4" x 0.1"
<b>Weight</b>	0.6 g / 0.02 oz.

### ENVIRONMENT

<b>Temperature</b>	
Operating	-40°C to +85°C
Storage	-40°C to +85°C
<b>Humidity</b>	Non condensing

1) With best matched antenna  
2) All SVs with -130dBm

3) External current limiter suggested

The information provided herein is believed to be reliable at press time. Maestro Wireless Solutions assumes no responsibility for inaccuracies or omission. Maestro Wireless Solutions assumes no responsibility for the use of this information, and all such information shall be entirely at the users own risk. Prices and specifications are subject to change without notice. Maestro Wireless Solutions does not authorize or warrant any of its products for use in life support devices and/or systems.

Maestro Wireless Solutions Ltd  
3603-9, 36/F  
118 Connaught Road West  
Hong Kong  
Tel: (852) 2869 0688  
Fax: (852) 2525 4701  
contact@maestro-wireless.com  
www.maestro-wireless.com