



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# Ultra-low Power Real Time Clock Module with I<sup>2</sup>C Bus



3.7 x 2.5 x 0.9 mm

AB-RTCMC-32.768kHz-IBO5-S3



RoHS/RoHS II compliant

Moisture Sensitivity Level: MSL=1

## FEATURES:

- Based on state-of-the-art RTC Technology by Micro Crystal AG
- Ultra-Low current consumption:
  - XTAL Mode 60nA typ. @3.0V
  - RC Mode 17nA typ. @3.0V
  - RC Autocalibrated Mode 22nA typ. @3.0V
- RTC module with built-in crystal oscillating at 32.768 kHz
- Operating voltage: 1.5 – 3.6V
- Operating temperature range: -40 to +85°C
- Factory calibrated Time accuracy ±2.0ppm typ. @ 25°C
- Automatic Battery Switchover
- Trickle Charger, Power Management & Power Switch Function
- Programmable CLKOUT frequencies
- I<sup>2</sup>C Bus Interface (fast mode 400kHz)
- Time keeping mode down to 1.5 V
- Programmable Alarm, Timer and INT
- Up to 512 Bytes of general purpose RAM
- Small and compact package size: 3.7 x 2.5 x 0.9 mm. RoHS-compliant and 100% lead free


## APPLICATIONS:

- Smart cards
- Wireless sensors and tags
- Medical/Healthcare electronics
- Sports and fitness electronics
- Smart Utility meters
- Data loggers
- Appliances
- Tracking systems
- Home security systems
- Industrial and Consumer electronics
- Communications equipment


## STANDARD SPECIFICATIONS:

### Absolute Maximum Ratings

Parameters		Min.	Typ.	Max.	Units	Notes
Power Supply Voltage (V <sub>DD</sub> )		-0.3		3.8	V	
Backup Supply voltage (V <sub>BACKUP</sub> )		-0.3		3.8	V	
Input Voltage (V <sub>I</sub> )	V <sub>DD</sub> Power state	-0.3		V <sub>DD</sub> + 0.3	V	
	V <sub>BACKUP</sub> Power State	-0.3		V <sub>BACUUP</sub> + 0.3	V	
Output Voltage (V <sub>O</sub> )	V <sub>DD</sub> Power state	-0.3		V <sub>DD</sub> + 0.3	V	
	V <sub>BACKUP</sub> Power State	-0.3		V <sub>BACUUP</sub> + 0.3	V	
Input Current (I <sub>I</sub> )		-10		10	mA	
Output Current (I <sub>O</sub> )		-20		20	mA	
PSW Output Continuous Current (I <sub>OPC</sub> )				50	mA	
PSW Output Pulsed Current (I <sub>OPP</sub> )				150	mA	1 second pulse
ESD Voltage (V <sub>ESD</sub> )	CDM			±500	V	Charged Device Model
	HBM			±4000	V	Human Body Model
Latch-up Current (I <sub>LU</sub> )				100	mA	
Operating Temperature Range (T <sub>OP</sub> )		-40		+85	°C	
Storage Temperature (T <sub>STG</sub> )		-55		+125	°C	Stored as bare product
Lead Temperature (T <sub>SLD</sub> )				+300	°C	Hand soldering for 10s
Reflow Soldering Temperature (T <sub>REF</sub> )				+260	°C	Reflow profile per JEDEC J-STD-020D




## Power Supply and Switchover Parameters



T<sub>A</sub> = -40 to +85°C, Typ. values at +25°C

Parameters	Type	Power State	Test Conditions	Min.	Typ.	Max.	Units
System Power Voltage (V <sub>DD</sub> )	Static	V <sub>DD</sub> Power	Clocks operating and RAM and registers retained	1.5		3.6	V
V <sub>DD</sub> I <sup>2</sup> C Interface Voltage (V <sub>DDIO</sub> )	Static	V <sub>DD</sub> Power	I <sup>2</sup> C operation	1.5		3.6	V
V <sub>DD</sub> Start-up Voltage (V <sub>DDST</sub> ) <sup>(1)</sup>	Rising	POR->V <sub>DD</sub> Power		1.6			V
V <sub>DD</sub> Reset Voltage (V <sub>DDRST</sub> )	Falling	V <sub>DD</sub> Power -> POR	V <sub>BACKUP</sub> < V <sub>BACKUP, MIN</sub> or no V <sub>BACKUP</sub>		1.3	1.5	V
V <sub>DD</sub> Rising Switchover Threshold Voltage (V <sub>DDSWR</sub> )	Rising	V <sub>BACKUP</sub> Power ->V <sub>DD</sub> Power	V <sub>BACKUP</sub> ≥ V <sub>BACKRST</sub>		1.6	1.7	V
V <sub>DD</sub> Falling Switchover Threshold Voltage (V <sub>DDSWF</sub> )	Falling	V <sub>DD</sub> Power -> V <sub>BACKUP</sub> Power	V <sub>BACKUP</sub> ≥ V <sub>BACKSW, MIN</sub>	1.2	1.5		V
V <sub>DD</sub> Switchover Threshold Hysteresis (V <sub>DDSWH</sub> ) <sup>(2)</sup>	Hyst.	V <sub>DD</sub> Power <-> V <sub>BACKUP</sub> Power			70		mV
V <sub>DD</sub> Falling Slew Rate to Switch to V <sub>BACKUP</sub> State (V <sub>DDFS</sub> ) <sup>(4)</sup>	Falling	V <sub>DD</sub> Power -> V <sub>BACKUP</sub> Power	V <sub>DD</sub> < V <sub>DDSW, MAX</sub>	0.7	1.4		V
Backup Voltage (V <sub>BACKUP</sub> )	Static	V <sub>BACKUP</sub> Power	Clocks operating and RAM and registers retained	1.4		3.6	V
Backup Switchover Voltage Range (V <sub>BACKSW</sub> ) <sup>(5)</sup>	Static	V <sub>DD</sub> Power -> V <sub>BACKUP</sub> Power		1.6		3.6	V
Falling Backup POR Voltage (V <sub>BACKRST</sub> ) <sup>(7)</sup>	Falling	V <sub>BACKUP</sub> Power -> POR	V <sub>DD</sub> < V <sub>DDSWF</sub>		1.1	1.4	V
V <sub>BACK</sub> Margin above V <sub>DD</sub> (V <sub>BMRG</sub> ) <sup>(3)</sup>	Static	V <sub>BACKUP</sub> Power		200			mV
V <sub>BACK</sub> Supply Series Resistance (R <sub>BACKESR</sub> ) <sup>(6)</sup>	Static	V <sub>BACKUP</sub> Power		1.0	1.5		kΩ

# Ultra-low Power Real Time Clock Module with I<sup>2</sup>C Bus



3.7 x 2.5 x 0.9 mm

AB-RTCMC-32.768kHz-IBO5-S3



RoHS/RoHS II compliant

- (1)  $V_{DD}$  must be above  $V_{DDST}$  to exit the POR state, independent of the  $V_{BACKUP}$  voltage.
- (2) Difference between  $V_{DDSWR}$  and  $V_{DDSWF}$ .
- (3)  $V_{BACKUP}$  must be higher than  $V_{DD}$  by at least this voltage to insure the AB-RTCMC-32.768kHz-IBO5-S3 remains in the  $V_{BACKUP}$  Power state.
- (4) Maximum  $V_{DD}$  falling slew rate to guarantee correct switchover to  $V_{BACKUP}$  Power state. There is no  $V_{DD}$  falling slew rate requirement if switching to the  $V_{BACKUP}$  power source is not required.
- (5)  $V_{BACKUP}$  voltage to guarantee correct transition to  $V_{BACKUP}$  Power state when  $V_{DD}$  falls.
- (6) Total series resistance of the power source attached to the  $V_{BACKUP}$  pin. The optimal value is 1.5 k $\Omega$ , which may require an external resistor.  $V_{BACKUP}$  power source ESR (Equivalent Series Resistance) + external resistor value = 1.5 k $\Omega$ .
- (7)  $V_{BACKRST}$  is also the static voltage required on  $V_{BACKUP}$  for register data retention.

## Operating Parameters

$T_A = -40$  to  $+85^\circ\text{C}$ , Typ. values at  $+25^\circ\text{C}$

Parameters	Test Conditions	$V_{DD}$	Min.	Typ.	Max.	Units
Positive-going Input Threshold Voltage ( $V_{T+}$ )		3.0V		1.5	2.0	V
		1.8V		1.1	1.25	
Negative-going Input Threshold Voltage ( $V_{T-}$ )		3.0V	0.8	0.9		V
		1.8V	0.5	0.6		
Input Leakage Current ( $I_{LEAK}$ )		3.0V		0.02	80	nA
Input Capacitance ( $C_I$ )				3		pF
PSW Output Resistance to $V_{DD}$ ( $R_{DSON}$ )	PSW enabled	1.7V		1.7	5.8	$\Omega$
		1.8V		1.6	5.4	
		3.0V		1.1	3.8	
		3.6V		1.05	3.7	
Output Leakage Current ( $I_{OLEAK}$ )		1.7V – 3.6V		0.02	80	nA

## Oscillator Parameters

$T_A = -40$  to  $+85^\circ\text{C}$  unless otherwise indicated.  $V_{DD} = 1.7$  to  $3.6\text{V}$ , Typ. values at  $+25^\circ\text{C}$  and  $3.0\text{V}$


Parameters	Test Conditions	Min.	Typ.	Max.	Units
Crystal Frequency ( $F_{XT}$ )			32.768		kHz
XT Oscillator Failure Detection Frequency ( $F_{OF}$ )			8		kHz
Calibrated RC Oscillator Frequency ( $F_{RCC}$ ) <sup>(1)</sup>	Factory calibrated at $+25^\circ\text{C}$ , $V_{DD} = 2.8\text{V}$		64		Hz
Uncalibrated RC Oscillator Frequency ( $F_{RCU}$ )	Calibration disabled (OFFSETR=0) – 128Hz level	89	122	200	Hz
Uncalibrated RC Oscillator Cycle-to-Cycle Jitter,  Median  ( $J_{RCCC}$ )	Calibration disabled (OFFSETR=0) – 128Hz level		2000		ppm
	Calibration disabled (OFFSETR=0) – 1Hz level		500		
RC Oscillator Cycle-to-Cycle Jitter, MIN, MAX ( $J_{RCCC}$ )	128Hz level at $+25^\circ\text{C}$	-1		1	%
	128Hz level -10 to $+70^\circ\text{C}$	-3.5		3.5	
	128Hz level -40 to $+85^\circ\text{C}$	-10		10	
XT Mode Digital Calibration Accuracy ( $A_{XT}$ ) <sup>(1)</sup>	Calibrated at an initial temperature and voltage. Factory calibrated at $+25^\circ\text{C}$ , $V_{DD} = 3.0\text{V}$	-2		+2	ppm

# Ultra-low Power Real Time Clock Module with I<sup>2</sup>C Bus

AB-RTCMC-32.768kHz-IBO5-S3



RoHS/RoHS II compliant



3.7 x 2.5 x 0.9 mm

(Continued)

$T_A = -40$  to  $+85^\circ\text{C}$  unless otherwise indicated.  $V_{DD} = 1.7$  to  $3.6\text{V}$ , Typ. values at  $+25^\circ\text{C}$  and  $3.0\text{V}$

Parameters	Test Conditions	Min.	Typ.	Max.	Units
Autocalibration Mode Timing Accuracy, 512 second period, $T_A = -10$ to $+60^\circ\text{C}$ ( $A_{AC}$ ) <sup>(1)</sup>	24 hour run time		35		ppm
	1 week run time		20		
	1 month run time		10		
	1 year run time		3		
Autocalibration Mode Operating Temperature ( $T_{AC}$ ) <sup>(2)</sup>		-10		+60	$^\circ\text{C}$

(1) Timing accuracy is specified at  $25^\circ\text{C}$  after digital calibration of the internal RC oscillator and digital calibration of the 32.768 kHz crystal. The 32.768 kHz tuning fork crystal has a negative temperature coefficient with a parabolic frequency deviation, which can result in a change of up to 150 ppm across the entire operating temperature range of  $-40^\circ\text{C}$  to  $85^\circ\text{C}$  in XT mode. Autocalibration mode timing accuracy is specified relative to XT mode timing accuracy from  $-10^\circ\text{C}$  to  $60^\circ\text{C}$ .

(2) Outside of this temperature range, the RC oscillator frequency change due to temperature may be outside of the allowable RC digital calibration range ( $\pm 12\%$ ) for autocalibration mode. When this happens, an autocalibration failure will occur and the ACF interrupt flag is set. The AB-RTCMC-32.768kHz-IBO5-S3 should be switched to use the XT oscillator as its clock source when this occurs. Please see the AUTOCALIBRATION FAILURE section in the application manual for more details.

## XT Frequency Characteristics

$T_A = -40$  to  $+85^\circ\text{C}$  unless otherwise indicated.  $V_{DD} = 1.7$  to  $3.6\text{V}$ , Typ. values at  $+25^\circ\text{C}$  and  $3.0\text{V}$ ,  $f_{OSC} = 32.768\text{kHz}$

Parameters	Test Conditions	Min.	Typ.	Max.	Units
Frequency Accuracy ( $\Delta F/F$ )	$T_A = +25^\circ\text{C}$ ; Calibration disabled (OFFSETX=0)		$\pm 100$ <sup>(1)</sup>		ppm
Frequency vs. Temperature Characteristics ( $\Delta F/F_0$ )	$T_{OPR} = -40$ to $+85^\circ\text{C}$	$-0.035^{\text{ppm}/^\circ\text{C}^2} * (T_{OPR} - T_0)^2 \pm 10\%$			ppm
Turnover Temperature ( $T_0$ )		+20	+25	+30	$^\circ\text{C}$
Aging First Year	$T_A = +25^\circ\text{C}$			$\pm 3$	ppm
Oscillator Start-up Voltage	$T_A = -40$ to $+85^\circ\text{C}$	1.6			V
Oscillator Start-up Time	$V_{DD} = 1.7\text{V} - 3.6\text{V}$		1.0		s
CLKOUT Duty Cycle	$F_{CLKOUT} = 32.768\text{kHz}$ ; $T_A = +25^\circ\text{C}$	50	60	70	%

(1) The XT mode digital calibration accuracy is  $\pm 2$  ppm, see OSCILLATOR PARAMETERS.

# Ultra-low Power Real Time Clock Module with I<sup>2</sup>C Bus

AB-RTCMC-32.768kHz-IBO5-S3




RoHS/RoHS II compliant



3.7 x 2.5 x 0.9 mm

XT Frequency vs. Temperature Characteristics



## V<sub>DD</sub> Supply Current

T<sub>A</sub> = -40 to +85°C. V<sub>BACKUP</sub> = 0 to 3.6V, Typ. values at +25°C, V<sub>DD</sub> power state


Parameters	Test Conditions	V <sub>DD</sub>	Min.	Typ.	Max.	Units
V <sub>DD</sub> Supply Current during I2C burst Read/Write (I <sub>VDD:I2C</sub> )	400kHz bus speed, 2.2k pull-up resistors on SCL/SDA <sup>(1)</sup>	3.0V		6	10	μA
		1.8V		1.5	3	
V <sub>DD</sub> Supply Current in XT Oscillator Mode (I <sub>VDD:XT</sub> )	Time keeping mode with XT oscillator running <sup>(2)</sup>	3.0V		60	330	nA
		1.8V		27	290	
V <sub>DD</sub> Supply Current in RC Oscillator Mode (I <sub>VDD:RC</sub> )	Time keeping mode with only the RC oscillator running (XT oscillator is off) <sup>(2)</sup>	3.0V		17	220	nA
		1.8V		14	170	
Average V <sub>DD</sub> Supply Current in Autocalibrated RC Oscillator Mode (I <sub>VDD:ACAL</sub> )	Time keeping mode with only the RC oscillator running and Autocalibration enabled. ACP=512 seconds <sup>(2)</sup>	3.0V		22	235	nA
		1.8V		18	190	
Additional V <sub>DD</sub> Supply Current with CLK/INT at 32.768kHz (I <sub>VDD:CK32</sub> )	Time keeping mode with XT oscillator running, 32.768kHz square wave on CLK/INT <sup>(3)</sup>	3.0V		0.71		μA
		1.8V		0.34		
Additional V <sub>DD</sub> Supply Current with CLK/INT at 64Hz (I <sub>VDD:CK64</sub> )	All time keeping mode, 64Hz square wave on CLK/INT <sup>(3)</sup>	3.0V		0.6		nA
		1.8V		0.3		

# Ultra-low Power Real Time Clock Module with I<sup>2</sup>C Bus

AB-RTCMC-32.768kHz-IBO5-S3



RoHS/RoHS II compliant



3.7 x 2.5 x 0.9 mm

- (1) Excluding external peripherals and pull-up resistor current. All other inputs (besides SDA and SCL) are at 0V or V<sub>DD</sub>.  
 Test conditions: Continuous burst read/write, 55h data pattern, 25 μs between each data byte, 20 pF load on each bus pin.
- (2) All inputs and outputs are at 0V or V<sub>DD</sub>.
- (3) All inputs and outputs except CLK / INT are at 0V or V<sub>DD</sub>. 15 pF load on CLK / INT, pull-up resistor current not included.

## V<sub>BACKUP</sub> Supply Current

T<sub>A</sub> = -40 to +85°C. Typ. values at +25°C, Max. values at +85°C. V<sub>BACKUP</sub> power state

Parameters	Test Conditions	V <sub>DD</sub>	V <sub>BACK</sub>	Min.	Typ.	Max.	Units
V <sub>BACKUP</sub> Supply Current in XT Oscillator Mode (I <sub>VBACK:XT</sub> )	Time keeping mode with XT oscillator running <sup>(1)</sup>	<V <sub>DDSWF</sub>	3.0V		63	330	nA
			1.8V		60	290	
V <sub>BACKUP</sub> Supply Current in RC Oscillator Mode (I <sub>VBACK:RC</sub> )	Time keeping mode with only the RC oscillator running (XT oscillator is off) <sup>(1)</sup>	<V <sub>DDSWF</sub>	3.0V		19	220	nA
			1.8V		16	170	
Average V <sub>BACKUP</sub> Supply Current in Autocalibrated RC Oscillator Mode (I <sub>VBACK:ACAL</sub> )	Time keeping mode with only the RC oscillator running and Autocalibration enabled. ACP=512 seconds <sup>(1)</sup>	<V <sub>DDSWF</sub>	3.0V		25	235	nA
			1.8V		21	190	
V <sub>BACKUP</sub> Supply Current in V <sub>DD</sub> powered mode (I <sub>VBACK:VDD</sub> )	V <sub>DD</sub> powered mode <sup>(1)</sup>	1.7-3.6V	3.0V	-5	0.6	20	nA
			1.8V	-10	0.5	16	


(1) Test conditions: All inputs and outputs are at 0V or V<sub>DD</sub>.

## BREF Electrical Characteristics

T<sub>A</sub> = -20 to +70°C. Typ. values at +25°C, V<sub>DD</sub> = 1.7 to 3.6V.

Parameters	BREF	Min.	Typ.	Max.	Units
V <sub>BACKUP</sub> Falling Threshold (V <sub>BRF</sub> )	0111	2.3	2.5	3.3	V
	1011	1.9	2.1	2.8	
	1101	1.6	1.8	2.5	
	1111		1.4		
V <sub>BACKUP</sub> Rising Threshold (V <sub>BRR</sub> )	0111	2.6	3.0	3.4	V
	1011	2.1	2.5	2.9	
	1101	1.9	2.2	2.7	
	1111		1.6		

# Ultra-low Power Real Time Clock Module with I<sup>2</sup>C Bus



3.7 x 2.5 x 0.9 mm

AB-RTCMC-32.768kHz-IBO5-S3



RoHS/RoHS II compliant

(Continued)


T<sub>A</sub> = -20 to +70°C. Typ. values at +25°C, V<sub>DD</sub> = 1.7 to 3.6V.

Parameters	BREF	Min.	Typ.	Max.	Units
V <sub>BACKUP</sub> Threshold Hysteresis (V <sub>BRH</sub> )	0111		0.5		V
	1011		0.4		
	1101		0.4		
	1111		0.2		
BREF/BPOL Change to BBOD Valid (t <sub>BREF</sub> )	All valid BREF values		1000		ms
V <sub>BACKUP</sub> Analog Comparator Recommended Operating Temperature Range (T <sub>BR</sub> )	All valid BREF Values	-20		+70	°C


## I<sup>2</sup>C AC Electrical Characteristics

T<sub>A</sub> = -40 to +85°C. Typ. values at +25°C

Parameters	V <sub>DD</sub>	Min.	Typ.	Max.	Units
SCL Input Clock Frequency (f <sub>SCL</sub> )	1.7 – 3.6V	10		400	kHz
Low Period of SCL Clock (t <sub>LOW</sub> )	1.7 – 3.6V	1.3			µs
High Period of SCL Clock (t <sub>HIGH</sub> )	1.7 – 3.6V	600			ns
Rise Time of SDA and SCL (t <sub>RISE</sub> )	1.7 – 3.6V			300	ns
Fall Time of SDA and SCL (t <sub>FALL</sub> )	1.7 – 3.6V			300	ns
START Condition Hold Time (t <sub>HD:STA</sub> )	1.7 – 3.6V	600			ns
START Condition Setup Time (t <sub>SU:STA</sub> )	1.7 – 3.6V	600			ns
SDA Setup Time (t <sub>SU:DAT</sub> )	1.7 – 3.6V	100			ns
SDA Hold Time (t <sub>HD:DAT</sub> )	1.7 – 3.6V	0			ns
STOP Condition Setup Time (t <sub>SU:STO</sub> )	1.7 – 3.6V	600			ns
Bus Free Time before a New Transmission (t <sub>BUF</sub> )	1.7 – 3.6V	1.3			µs







3.7 x 2.5 x 0.9 mm

AB-RTCMC-32.768kHz-IBO5-S3




RoHS/RoHS II compliant


## Power-on AC Electrical Characteristics

$T_A = -40$  to  $+85^\circ\text{C}$ .  $V_{\text{BACKUP}} < 1.2\text{V}$

Parameters	$V_{\text{DD}}$	$T_A$	Min.	Typ.	Max.	Units
Low Period of $V_{\text{DD}}$ to Ensure a Valid POR ( $t_{\text{LOW:VDD}}$ )	1.7 – 3.6V	+85°C		0.1		s
		+25°C		0.1		
		-20°C		1.5		
		-40°C		10		
$V_{\text{DD}}$ Low to $\overline{\text{CLK/INT}}$ Low ( $t_{\text{VL:CLK}}$ )	1.7 – 3.6V	+85°C		0.1		s
		+25°C		0.1		
		-20°C		1.5		
		-40°C		10		
$V_{\text{DD}}$ High to $\overline{\text{CLK/INT}}$ High ( $t_{\text{VH:CLK}}$ )	1.7 – 3.6V	+85°C		0.4		s
		+25°C		0.5		
		-20°C		3		
		-40°C		20		
$\overline{\text{CLK/INT}}$ High to XT Oscillator Start ( $t_{\text{XTST}}$ )	1.7 – 3.6V	+85°C		0.4		s
		+25°C		0.4		
		-20°C		0.5		
		-40°C		1.5		



# Ultra-low Power Real Time Clock Module with I<sup>2</sup>C Bus



3.7 x 2.5 x 0.9 mm

AB-RTCMC-32.768kHz-IBO5-S3




RoHS/RoHS II compliant

## RST AC Electrical Characteristics

$T_A = -40$  to  $+85^\circ\text{C}$ .  $V_{\text{BACKUP}} < 1.2\text{V}$

Parameters	$V_{\text{DD}}$	$T_A$	Min.	Typ.	Max.	Units
Low Period of $V_{\text{DD}}$ to Ensure a Valid POR ( $t_{\text{LOW:VDD}}$ )	1.7 – 3.6V	+85°C		0.1		s
		+25°C		0.1		
		-20°C		1.5		
		-40°C		10		
$V_{\text{DD}}$ Low to $\overline{\text{RST}}$ Low ( $t_{\text{VL:NRST}}$ )	1.7 – 3.6V	+85°C		0.1		s
		+25°C		0.1		
		-20°C		1.5		
		-40°C		10		
$V_{\text{DD}}$ High to $\overline{\text{RST}}$ High ( $t_{\text{VH:NRST}}$ )	1.7 – 3.6V	+85°C		0.5		s
		+25°C		0.5		
		-20°C		3.5		
		-40°C		25		




## PART IDENTIFICATION:

AB-RTCMC-32.768 kHz-IBO5-S3-



<b>Packaging</b>
Blank: Bulk
T: 1000pcs/reel

# Ultra-low Power Real Time Clock Module with I<sup>2</sup>C Bus




AB-RTCMC-32.768kHz-IBO5-S3




RoHS/RoHS II compliant

3.7 x 2.5 x 0.9 mm

## OUTLINE DIMENSION:




Recommended Land Pattern




Pin No.	Pin Name	Function
1	V <sub>DD</sub>	Power Supply Voltage
2	Cap_RC	Capacitor RC-Oscillator
3	CLK/INT	Clock Output/Interrupt
4	SCL	Serial Clock Input
5	SDA	Serial Data
6	V <sub>SS</sub>	Ground
7	V <sub>BACKUP</sub>	Backup Supply Voltage
8	PSW	Power Switch Output
9	WDI	Watchdog Input
10	RST	Reset Output

Dimensions: mm

## BLOCK DIAGRAM:



# Ultra-low Power Real Time Clock Module with I<sup>2</sup>C Bus



AB-RTCMC-32.768kHz-IBO5-S3




RoHS/RoHS II compliant

3.7 x 2.5 x 0.9 mm

## REFLOW PROFILE:


Maximum Reflow Conditions in accordance with IPC/JEDEC J-STD-020C "Pb-free"



Temperature	Conditions	Units
Average Ramp-up Rate ( $T_{Smax}$ to $T_p$ )	3°C/second max	°C/s
Ramp Down Rate ( $T_{cool}$ )	6°C/second max	°C/s
Time 25°C to Peak Temperature ( $T_{to-peak}$ )	8 minutes max	m
<b>Preheat</b>		
Temperature Min ( $T_{Smin}$ )	150	°C
Temperature Max ( $T_{Smax}$ )	200	°C
Time $T_{Smin}$ to $T_{Smax}$ ( $t_s$ )	60 ~ 180	sec
<b>Time Above Liquidus</b>		
Temperature Liquidus ( $T_L$ )	217	°C
Time above Liquidus ( $t_L$ )	60 ~ 150	sec
<b>Peak Temperature</b>		
Peak Temperature ( $T_p$ )	260	°C
Time within 5°C of Peak Temperature ( $t_p$ )	20 ~ 40	sec

## TAPE & REEL:

T = 1000pcs/reel



Dimensions: mm

**ATTENTION:** Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

ABRACON IS  
ISO 9001 : 2008  
CERTIFIED



**ABRACON** LLC

2 Faraday, Suite# B | Irvine | CA 92618 Revised: 11.16.15  
Ph. 949.546.8000 | Fax. 949.546.8001

Visit [www.abracon.com](http://www.abracon.com) for Terms and Conditions of Sale