imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



PHYSICAL INFRASTRUCTURE SYSTEMS

B. Copper Systems

С.

Tak-Ty® Hook & Loop Cable Tie Mounts

- For use with TTS Tak-Tape[™] and HLT/HLS Tak-Ty[®] Hook & Loop Cable Ties
- Unique cradle design provides maximum stability for cable bundle



Part Number	Material	Color	Mounting Method	Std. Pkg. Qty.	Std. Ctn. Qty.
ABMT-A-C*		Natural		100	1000
ABMT-A-C20*	Nylon 6.6	Black	Rubber	100	1000
ABMT-S6-C	No. Loss O. O.	Natural		100	1000
ABMT-S6-C20	Nylon 6.6	Black		100	1000
ABMT-S6-C60**	Flame Retardant	Black	#6 (M3) Screw	100	1000
ABMT-S6-C69**	Nylon 6.6	Natural		100	1000

• Dimensions: 1.10"L x 1.10"W x .34"H

(27.9mm x 27.9mm x 8.6mm)

· For indoor use only

*Maximum static load for adhesive backed mounts is .38 lbs. (174g).

**Flame retardant products are manufactured from a material that is rated UL 94V-0.

A 4-Way Adhesive Backed Cable Tie Mounts

- · Allow cable tie entry from all four sides
- Available in multiple sizes to match application load requirements
- Rubber-based adhesive provides a strong and reliable bond
- For indoor use only
- Produced 2-up and with tear tabs for fast and easy liner removal to speed installation



Part Number	Used With Cable Ties	Length		Width				Std. Pkg.	Std. Ctn.
		In.	mm	In.	mm	Material	Color	Qty.	Qty.
ABM1M-A-C	М	.50	12.7	.50	12.7	Nylon 6.6	White	100	500
ABMM-A-C	M, I	.75	19.1	.75	19.1	ABS	White	100	500
ABMM-A-C20	M, I	.75	19.1	.75	19.1		Black	100	500
ABM2S-A-C	M, I, S	1.00	25.4	1.00	25.4		White	100	500
ABM2S-A-C14	M, I, S	1.00	25.4	1.00	25.4		Gray	100	500
ABM2S-A-C15	M, I, S	1.00	25.4	1.00	25.4		lvory	100	500
ABM2S-A-C20	M, I, S	1.00	25.4	1.00	25.4		Black	100	500
ABM100-A-C	M, I, S	1.00	25.4	1.00	25.4	Nylon 6.6	White	100	1000
ABM100-A-C15	M, I, S	1.00	25.4	1.00	25.4		lvory	100	1000
ABM100-A-D20	M, I, S	1.00	25.4	1.00	25.4		Black	500	5000
ABM112-A-C	M, I, S	1.12	28.6	1.12	28.6		White	100	500
ABM112-A-D20	M, I, S	1.12	28.6	1.12	28.6		Black	500	5000
ABM3H-A-L	M, I, S, HS, LH, H, HLM	1.50	38.1	1.50	38.1		White	50	500
ABM3H-A-L20		1.50	38.1	1.50	38.1		Black	50	500
ABM4H-A-L		2.00	50.8	2.00	50.8		White	50	500

 $\begin{array}{l} \mbox{Cable Tie Cross Sections: } M = \mbox{Miniature, I} = \mbox{Intermediate, S} = \mbox{Standard, HS} = \mbox{Heavy-Standard, LH} = \mbox{Light-Heavy, H} = \mbox{Heavy, HLM} = \mbox{Miniature Tak-Ty}^{\otimes} \mbox{Hook \& Loop Cable Ties.} \end{array}$

Fiber Optic Systems

D. Power over Ethernet

E.

Zone Cabling

F. Wireless

G. Outlets

H. Media Distribution

l. Physical Infrastructure Management

J. Overhead & Underfloor Routing

> K. Surface Raceway

L. Cabinets, Racks & Cable Management

M. Grounding &

Bonding

N. Industrial

0. Labeling & Identification

P. Cable Management Accessories

> Q. Index