



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





## ACD-3300 IND CAT IV Industrial True RMS Clamp Meter

This CAT IV rated clamp is ideal for industrial applications and utilities that require an extra level of safety. Includes True RMS sensing for accuracy and dependability. Extra large jaw to accommodate wide diameter wires.

- True RMS
- Measures AC Current up to 1000 ACA, Voltage up to 750 VAC / 1000 VDC, Frequency, Resistance and Capacitance and Duty Cycle
- Temperature to 1832°F or 1000°C
- Peak Hold
- Audible continuity
- Auto and manual ranging
- Auto power off
- Data hold
- Backlight
- Diode Test
- Duty Cycle
- Accommodates conductors up to 2" (51mm) in diameter
- Safety CAT IV 600 V, CAT III 1000 V
- Test leads, battery (installed), Users Manual, Carrying Case and type-K thermocouple included with the product

### No hassle warranty

*No waiting.*

*No shipping charges.*



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)



## ACD-3300 IND CAT IV Industrial True RMS Clamp Meter

## Data Sheet

### Specifications (valid for 23 °C ± 5 °C, for less than 75% relative humidity).

<b>DC Volts</b>	<b>Ranges</b>	<b>Accuracy</b>	
	660.0 mV, 6.600 V, 66.00 V, 660.0 V, 1000 V	± (0.5% rdg + 2 dgts)	
<b>Input impedance</b>	660 mV: >100 MΩ; 6.6 V:10 MΩ; 66 V to 1000 V: 9.1 MΩ		
<b>Overload protection</b>	1000 VDC or 750 VAC rms		
<b>AC Volts True RMS</b>	<b>Ranges</b>	<b>Frequency</b>	<b>Accuracy</b>
	660.0 mV	50 to 100 Hz	± (1.5% rdg + 8 dgts)
	6.600V, 66.00V	50 to 500 Hz	± (1.5% rdg + 8 dgts)
	660.0V, 750V	50 to 500 Hz	± (1.5% rdg + 8 dgts)
	Frequency*	50 to 1 kHz	± (0.1% rdg + 5 dgts)
	* Frequency: 10% to 100% of voltage range		
<b>Peak Hold</b>	<b>Ranges</b>	<b>Frequency</b>	<b>Accuracy</b>
	66.00V, 660.0V, 750V	50 to 500 Hz	± (3.0% rdg + 300 dgts)
<b>AC coupled TRMS</b>	5% to 100% of range		
<b>Crest factor</b>	≤ 3		
<b>Input impedance</b>	660 mV: >100 MΩ; 6.6 V:10 MΩ; 66 V to 750 V: 9.1 MΩ		
<b>Overload protection</b>	1000 VDC or 750 VAC rms		
<b>AC Current True RMS</b>	<b>Ranges</b>	<b>Frequency</b>	<b>Accuracy</b>
	66.00A	50 to 60 Hz	± (2.0% rdg + 10 dgts)
	66.00A	61 to 400 Hz	± (3.0% rdg + 10 dgts)
	660.0A	50 to 60 Hz	± (2.0% rdg + 10 dgts)
	660.0A	61 to 400 Hz	± (3.0% rdg + 10 dgts)
	1000 A	50 to 60 Hz	± (2.5% rdg + 10 dgts)
	1000 A	61 to 400 Hz	± (3.5% rdg + 10 dgts)
	Frequency*	50 to 1kHz	± (0.1% rdg + 5 dgts)
<b>Peak Hold</b>	<b>Ranges</b>	<b>Frequency</b>	<b>Accuracy</b>
	66.00A, 660.0A, 1000A	50 to 400 Hz	± (3.0% rdg + 200 dgts)
	* Frequency: 10% to 100% of current range		
<b>AC coupled TRMS</b>	5% to 100% of range		
<b>Crest factor</b>	≤ 3		
<b>Overload protection</b>	1000A AC		
<b>Resistance</b>	<b>Range</b>	<b>Accuracy</b>	
	660.0Ω, 6.600kΩ, 66.00kΩ, 660.0kΩ	± (1.0% rdg + 5 dgts)	
	6.600MΩ	± (2.0% rdg + 5 dgts)	
	66.00MΩ	± (3.5% rdg + 5 dgts)	
<b>Open circuit volts</b>	-0.8 Vdc typical , (-1.2 Vdc on 660 Ω range)		
<b>Overload protection</b>	1000 VDC or 750 VAC rms		
<b>Capacitance</b>	<b>Range</b>	<b>Accuracy</b>	
	6.600nF, 66.00nF	±(3.0% rdg + 20 dgts)	
	660.0nF, 6.600μF, 66.00μF,660.0μF	±(3.0% rdg + 10 dgts)	
	6.6 mF	±(5.0% rdg + 10 dgts)	
<b>Overload protection</b>	1000 VDC or 750 VAC rms		

## ACD-3300 IND CAT IV Industrial True RMS Clamp Meter

## Data Sheet

### Specifications (continued)

Temperature	Range	Accuracy
	0.0°C to 400.0°C	± (1.0% + 1°C)
	-35.0°C to 0.0°C, 400°C to 1000°C	± (2.0% + 3°C)
	32.0°F to 750.0°F	± (1.0% + 2°F)
	-30.0°F to 32.0°F, 750°F to 1832°F	± (2.0% + 6°F)
<b>Sensor type</b>	K-type thermocouple	
<b>Overload protection</b>	30 V Max	

### Diode Test

<b>Test current</b>	1.0 mA (approximate)
<b>Accuracy</b>	± (1.5% rdg + 5 dgts)
<b>Open circuit volts</b>	3.2 Vdc typical
<b>Audible indication</b>	< 0.25 V
<b>Overload protection</b>	1000 VDC or 750 VAC rms

### Continuity

<b>Ranges</b>	660.0 Ω
<b>Audible indication</b>	< 30 Ω
<b>Response time</b>	500 ms
<b>Overload protection</b>	1000 VDC or 750 VAC rms

Frequency (Auto ranging)	Range	Accuracy
	66.00 Hz, 660.0 Hz, 6.600k Hz, 66.00 kHz, 660.0 kHz, 1.000 MHz	± (0.1% rdg + 3 dgts)
<b>Sensitivity</b>	10 Hz to 1 MHz: > 3.5 V rms	
<b>Minimum pulse Width</b>	>1 us	


### % Duty Cycle

<b>Range</b>	5.0 % to 95.0 %
<b>Resolution:</b>	0.1 %
<b>Minimum Pulse Width</b>	>10 us
<b>Frequency range</b>	40 Hz to 20 kHz
<b>Accuracy ( 5V logic )</b>	± (2% rdg + 10 dgts)
<b>Overload protection</b>	1000 VDC or 750 VAC rms

## ACD-3300 IND CAT IV Industrial True RMS Clamp Meter

## Data Sheet

### Technical Data – General Information

Display	3¾ digit liquid crystal display (LCD) (6600 count) with a 66-segment analog bar-graph
Polarity	Automatic, positive implied, negative polarity indication
Over range	(OL) or (-OL) is displayed
Zero	Automatic
Low battery indication	"  " is displayed when the battery voltage drops below the operating level
Auto power off	Approx. 30 minutes
Backlight	Backlight auto-off approx. 60 sec.
Measurement rate	2.8 times per second, nominal
Analog bar-graph	28 times per second
Operating environment	0°C to 50°C (32°F to 122°F) at < 70% R.H.
Storage temperature	-20°C to 60°C (-4°F to 140°F) at < 80% R.H. with battery removed from meter
Temperature Coefficient	0.1 × (specified accuracy) per °C. (0°C to 18°C, 28°C to 50°C)
Environmental	2000m (6561.7 Feet), Indoor use
Jaw opening capability	57 mm (2.0 in) conductor
Power	Single standard 9-volt battery, NEDA 1604, JIS 006P, IEC 6F22
Battery life	typically 75 hours with carbon-zinc; 150 hour with alkaline
Dimensions	283 x 105 x 50 mm (11 x 4 x 2.1 in.)
Weight	500 gm ( 1.10 lb.)
Safety	LVD Meets EN61010-1:2001 and EN61010-2-032:2002, CAT III 1000V, CAT IV 600V, class II and pollution degree 2

### CE EMC

EN 61326-1:2006 This product complies with requirements of the following European Community Directives: 2004/108/EC (Electromagnetic Compatibility) and 2006/95/EC (Low Voltage) as amended by 93/68/EEC (CE Marking). However, electrical noise or intense electromagnetic fields in the vicinity of the equipment may disturb the measurement circuit. Measuring instruments will also respond to unwanted signals that may be present within the measurement circuit. Users should exercise care and take appropriate precautions to avoid misleading results when making measurements in the presence of electronic interference.



### Optional Accessories

TL-1500 Test leads with set of alligator clips

**Amprobe® Test Tools**  
 website: [www.Amprobe.com](http://www.Amprobe.com)  
 email: [info@amprobe.com](mailto:info@amprobe.com)  
 Everett, WA 98203  
 Tel: 877-AMPROBE

**Amprobe® Test Tools Europe**  
 Amprobe Test Tools Europe  
 Beha-Amprobe GmbH  
 In den Engematten 14  
 79286 Glottertal, Germany  
 Tel.: +49 (0) 7684 8009 - 0

©2009 Amprobe Test Tools. All rights reserved.  
 03/2009 3465178 Rev A