



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



ACL 350 Digital Static Locator














Easy to Use:

Discharge static from your body by touching a grounded metal object. Press the "ZERO" button twice. From a distance, point the electrode in the direction of the target and move toward it, observing the value on the LCD window. Press and hold the "PWR ON/HOLD" button and note reading from 1/10" to 8.5", making sure to properly multiply reading according to chart in the user manual. See manual for details.

Product #350 includes carrying case, 9-volt battery, and NIST-traceable calibration certificate.

Measure electrostatic charges with precision!

The ACL 350 is the ideal electrostatic locator meter for applications in which a precise measurement is required. The 3.5 digit LCD displays both negative and positive polarities. By spacing the meter from 1/10" to 8.5", a range of 0-80,000 volts can be measured. Utilizing the "HOLD" function allows the user time to record the precise voltage. Easy to use and lightweight, this battery-powered meter can be quickly re-zeroed, allowing for repetitive measurements. The ACL 350 can be used for determining the source of electrostatic charges in ESD-controlled environments or in other areas where static is of concern. It is perfect in electronic component production and assembly areas, textiles, packaging, engineering labs, and printing.

-  **3½ digit LCD**
-  **Accuracy: ± 10%**
-  **Range: 0 ± 80,000 volts**
-  **Low battery indication**
-  **Powered by 9-volt battery**
-  **Quick zero function**
-  **1" spacer**
-  **Hold function**
-  **Automatic shut off after 90 seconds**
-  **Weight: 5 ounces**
-  **Size: 4.2" x 2.4" x 0.9"**