



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



AD-FMCADC2-EBZ FMC Board

The [AD-FMCADC2-EBZ](#) is a high speed data acquisition board featuring [AD9625](#) single channel ADC at 2500 MSPS, in a FMC form factor which supports the JESD204B high speed serial interface. This board meets most of the FMC specifications in terms of mechanical size, mounting hole locations, and more. For that information, please refer to the FMC specification.


Although this board does meet most of the FMC specifications, it is not meant as a [commercial off the shelf](#) (COTS) board. If you want a commercial, ready to integrate product, please refer to one of the many FMC manufacturers.

This board is targeted to use the ADI reference designs that work with Xilinx development systems. ADI provides complete source (HDL and software) to re-create those projects (minus the IP provided by the FPGA vendors, which we use), but may not provide enough info to port this to your custom platform.

Contains

The card contains:

- [AD9625](#) 12-bit ADC with sampling speeds of up to 2500 MSPS, with a [JESD204B](#) digital interface.
- [ADP7104](#) is a 20V, 500mA, low noise, CMOS LDO
- [ADP1753A](#) is a low dropout linear regulators that operate from 1.6 V to 3.6 V and provide up to 800mA of output current.
- [ADP2119](#) is a 2A, 1.2MHz, synchronous step-down DC-to-DC regulator
- [ADP1741](#) is a 2A, low Vin, low dropout, CMOS linear regulator
- [ADR280](#) is a ultralow power high PSRR voltage reference.



FPGA Code

[ZC706 VC707 VC707 Dual AD9625 Board](#)

Eye Scan

Eye scan for this board can be found at [jesd_eye_scan](#).

Linux

- [JESD Linux Driver](#)
- [AD9625 Linux driver](#)
- [ZC706 Linux image](#)

Specifications

The AD-FMCADC2-EBZ board's primary purpose is to quickly and easily connect to an FMC carrier platform and start collecting data using the AD9625. The board is designed to be easy to use. Out of the box the board will self power and self clock when connected to an FMC carrier. The only other required equipment is your chosen signal source to provide an input signal to "Ain".

This rapid prototyping board also has 4 vertically mounted SMA connectors. These are labeled SYSREF IN and SYSREF OUT. These are to enable synchronization of multiple AD-FMCADC2-EBZ boards together using characteristics of the JESD204B high speed serial interface between the AD9625 and FPGA.

Clocking

The AD-FMCADC2-EBZ provides multiple options for clocking the AD9625. The default configuration of the board clocks the ADC using an on-board 2.5 GHz, low noise, crystal oscillator. This oscillator is then routed through a wide band transformer producing the differential clock for the ADC.

Alternatively, the oscillator can be disconnected and an external clock source connected by only changing two components on the board. A single ended clock connected to the CLK+ input would then be routed through the transformer in the same way.

Finally, the option exists to connect a differential clock to the board using both the CLK+ and CLK- inputs. Then referencing the schematic make the component changes to directly route the differential input bypassing the transformer.

Front End

The AD-FMCADC2-EBZ uses a passive front end designed for very wide bandwidth. A single ended input needs to be provided to "Ain". A 500 kHz to 6 GHz broadband balun then converts the input signal to differential.

Layout

Downloads

- [02-036007-01-c-1.pdf](#)
- [ad-fmccadc2-ebz_gerbers.zip](#)
- [05_036007_c_bom_wiki.xlsx](#)



© Analog Devices, Inc. All rights reserved. Trademarks and registered trademarks are the property of their respective owners.



www.analog.com