imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Data Sheet

FEATURES

Ultralow power

400 μ A power supply current (4 mW on ±5 V_S) Specified for single supply operation High speed 270 MHz, -3 dB bandwidth (G = +1) 170 MHz, -3 dB bandwidth (G = +2) 280 V/ μ s slew rate (G = +2) 28 ns settling time to 0.1%, 2 V step (G = +2) Low distortion/noise -63 dBc at 1 MHz, V₀ = 2 V p-p -50 dBc at 10 MHz, V₀ = 2 V p-p 4.0 nV/ \sqrt{Hz} input voltage noise at 10 MHz Good video specifications (R_L = 1 k Ω , G = +2) Gain flatness 0.1 dB to 30 MHz 0.11% differential gain error 0.4° differential phase error

APPLICATIONS

Rev. B

Signal conditioning A/D buffer Power sensitive, high speed systems Battery powered equipment Loop/remote power systems Communication or video test systems Portable medical instruments

GENERAL DESCRIPTION

The AD8005 is an ultralow power, high speed amplifier with a wide signal bandwidth of 170 MHz and slew rate of 280 V/ μ s. This performance is achieved while consuming only 400 μ A of quiescent supply current. These features increase the operating time of high speed battery powered systems without reducing dynamic performance.

The current feedback design results in gain flatness of 0.1 dB to 30 MHz while offering differential gain and phase errors of 0.11% and 0.4°. Harmonic distortion is low over a wide bandwidth with THDs of -63 dBc at 1 MHz and -50 dBc at 10 MHz. Ideal features for a signal conditioning amplifier or buffer to a high speed A-to-D converter in portable video, medical or communication systems.

The AD8005 is characterized for +5 V and ±5 V supplies and operates over the industrial temperature range of -40°C to +85°C. The amplifier is supplied in 8-lead PDIP, 8-lead SOIC_N, and 5-lead SOT-23 packages.

270 MHz, 400 µA Current Feedback Amplifier

AD8005

FUNCTIONAL BLOCK DIAGRAMS



Figure 4. Distortion vs. Frequency; $V_S = \pm 5 V$

Document Feedback

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A. Tel: 781.329.4700 ©1996–2014 Analog Devices, Inc. All rights reserved. Technical Support www.analog.com

AD8005* PRODUCT PAGE QUICK LINKS

Last Content Update: 02/23/2017

COMPARABLE PARTS 🖵

View a parametric search of comparable parts.

EVALUATION KITS

• Universal Evaluation Board for Single High Speed Operational Amplifiers

DOCUMENTATION

Application Notes

- AN-253: Find Op Amp Noise with Spreadsheet
- AN-257: Careful Design Tames High Speed Op Amps
- AN-356: User's Guide to Applying and Measuring Operational Amplifier Specifications
- AN-649: Using the Analog Devices Active Filter Design Tool
- AN-692: Universal Precision Op Amp Evaluation Board

Data Sheet

 AD8005: 270 MHz, 400 μA Current Feedback Amplifier Data Sheet

User Guides

- UG-755: 8-Lead SOIC Amplifier Evaluation Board User Guide
- UG-838: Evaluation Board for Single, High Speed Op Amps Offered in 5-Lead SOT-23 and 6-Lead SOT-23 Packages

TOOLS AND SIMULATIONS

AD8005 SPICE Macro-Model

REFERENCE MATERIALS

Product Selection Guide

• High Speed Amplifiers Selection Table

Tutorials

- MT-034: Current Feedback (CFB) Op Amps
- MT-051: Current Feedback Op Amp Noise Considerations
- MT-057: High Speed Current Feedback Op Amps
- MT-059: Compensating for the Effects of Input Capacitance on VFB and CFB Op Amps Used in Current-to-Voltage Converters

DESIGN RESOURCES

- AD8005 Material Declaration
- PCN-PDN Information
- Quality And Reliability
- Symbols and Footprints

DISCUSSIONS

View all AD8005 EngineerZone Discussions.

SAMPLE AND BUY

Visit the product page to see pricing options.

TECHNICAL SUPPORT

Submit a technical question or find your regional support number.

DOCUMENT FEEDBACK

Submit feedback for this data sheet.

TABLE OF CONTENTS

Features	1
Applications	1
General Description	1
Functional Block Diagrams	1
Revision History	2
Specifications	3
±5 V Supplies	3
+5 V Supply	4
Absolute Maximum Ratings	5
Thermal Resistance	5
Maximum Power Dissipation	5

REVISION HISTORY

3/14—Rev. A to Rev. B

Updated Format	Universal
Deleted Operating Temperature Range Parameter, Tab	le 1 3
Changes to Table 3	5
Change to Figure 11	6
Changes to Ordering Guide	13
0/00 D 0 to D 4	

8/99—Rev. 0 to Rev. A

ESD Caution	5
Typical Performance Characteristics	6
Applications	10
Driving Capacitive Loads	10
Single-Supply Level Shifter	10
Single-Ended-to-Differential Conversion	10
Layout Considerations	11
Increasing Feedback Resistors	11
Outline Dimensions	12
Ordering Guide	13

SPECIFICATIONS

±5 V SUPPLIES

At T_{A} = +25°C, V_{S} = ±5 V, R_{L} = 1 kΩ, unless otherwise noted.

Table 1.					
Parameter	Conditions	Min	Тур	Мах	Units
DYNAMIC PERFORMANCE	$R_F = 3.01 \text{ k}\Omega$ for N-8 Package or				
	$R_F = 2.49 \text{ k}\Omega$ for R-8 Package or				
	$R_F = 2.10 \text{ k}\Omega$ for RJ-5 Package				
–3 dB Small Signal Bandwidth	$G = +1, V_0 = 0.2 V p - p$	225	270		MHz
-	$G = +2, V_0 = 0.2 V p-p$	140	170		MHz
Bandwidth for 0.1 dB Flatness	$G = +2, V_0 = 0.2 V p p$	10	30		MHz
Large Signal Bandwidth	$G = +10, V_0 = 4 V p - p, R_F = 499 \Omega$		40		MHz
Slew Rate (Rising Edge)	$G = +2$, $V_0 = 4$ V Step		280		V/µs
	$G = -1$, $V_O = 4 V$ Step, $R_F = 1.5 k\Omega$		1500		V/µs
Settling Time to 0.1%	$G = +2$, $V_0 = 2$ V Step		28		ns
DISTORTION/NOISE PERFORMANCE	$R_F = 3.01 \text{ k}\Omega$ for N-8 Package or				
	$R_F = 2.49 \text{ k}\Omega$ for R-8 Package or				
	$R_F = 2.10 \text{ k}\Omega$ for RJ-5 Package				
Total Harmonic Distortion	$f_c = 1 \text{ MHz}, V_o = 2 \text{ V p-p}, G = +2$		-63		dBc
	$f_c = 10 \text{ MHz}, V_0 = 2 \text{ V p-p}, G = +2$		-50		dBc
Differential Gain	NTSC, $G = +2$		0.11		%
Differential Phase	NTSC, $G = +2$		0.4		Degrees
Input Voltage Noise	f = 10 MHz		4.0		nV/√Hz
Input Current Noise	$f = 10 \text{ MHz}, +I_{IN}$		1.1		pA/√Hz
	-l _{IN}		9.1		pA/√Hz
DC PERFORMANCE					
Input Offset Voltage			5	30	±mV
	T _{MIN} to T _{MAX}			50	±mV
Offset Drift			40		μV/°C
+Input Bias Current			0.5	1	±μΑ
	T _{MIN} to T _{MAX}			2	±μΑ
-Input Bias Current			5	10	±μΑ
	T _{MIN} to T _{MAX}			12	±μΑ
Input Bias Current Drift (±)			6		nA/°C
Open-Loop Transimpedance		400	1000		kΩ
INPUT CHARACTERISTICS					
Input Resistance	+Input		90		MΩ
	–Input		260		Ω
Input Capacitance	+Input		1.6		pF
Input Common-Mode Voltage Range			3.8		±V
Common-Mode Rejection Ratio	$V_{CM} = \pm 2.5 V$	46	54		dB
OUTPUT CHARACTERISTICS					
Output Voltage Swing	Positive	+3.7	+3.90		V
	Negative		-3.90	-3.7	V
Output Current	$R_L = 50 \Omega$		10		mA
Short Circuit Current			60		mA
POWER SUPPLY					
Quiescent Current			400	475	μΑ
	T _{MIN} to T _{MAX}			560	μΑ
Power Supply Rejection Ratio	$V_s = \pm 4 V \text{ to } \pm 6 V$	56	66		dB

+5 V SUPPLY

At $T_A = +25^{\circ}$ C, $V_S = +5$ V, $R_L = 1$ k Ω to 2.5 V, unless otherwise noted.

Table 2.

Parameter	Conditions	Min	Тур	Мах	Units
DYNAMIC PERFORMANCE	$R_F = 3.01 \text{ k}\Omega$ for N-8 Package or				
	$R_F = 2.49 \text{ k}\Omega$ for R-8 Package or				
	$R_F = 2.10 \text{ k}\Omega$ for RJ-5 Package				
–3 dB Small Signal Bandwidth	$G = +1, V_0 = 0.2 V p-p$	190	225		MHz
	$G = +2, V_0 = 0.2 V p-p$	110	130		MHz
Bandwidth for 0.1 dB Flatness	$G = +2, V_0 = 0.2 V p-p$	10	30		MHz
Large Signal Bandwidth	$G = +10$, $V_0 = 4 V p-p$, $R_F = 499 \Omega$		45		MHz
Slew Rate (Rising Edge)	$G = +2, V_0 = 4 V Step$		260		V/µs
	$G = -1$, $V_0 = 4$ V Step, $R_F = 1.5$ k Ω		775		V/µs
Settling Time to 0.1%	$G = +2, V_0 = 2 V Step$		30		ns
DISTORTION/NOISE PERFORMANCE	$R_F = 3.01 \text{ k}\Omega$ for N-8 Package or				
	$R_F = 2.49 \text{ k}\Omega$ for R-8 Package or				
	$R_F = 2.10 \text{ k}\Omega$ for RJ-5 Package				
Total Harmonic Distortion	$f_{c} = 1 \text{ MHz}, V_{0} = 2 \text{ V p-p}, G = +2$		-60		dBc
	$f_{c} = 10 \text{ MHz}, V_{0} = 2 \text{ V p-p}, G = +2$		-50		dBc
Differential Gain	NTSC, $G = +2$		0.14		%
Differential Phase	NTSC. $G = +2$		0.70		Degrees
Input Voltage Noise	f = 10 MHz		4.0		nV/√Hz
Input Current Noise	$f = 10 \text{ MHz} + I_{IN}$		1.1		pA/ ₁ /Hz
	-l _{IN}		9.1		pA/√Hz
DC PERFORMANCE	-114				In 1 1 1
Input Offset Voltage			5	35	+mV
input onset tokage			5	50	+mV
Offset Drift			40	50	v
+Input Bias Current			0.5	1	μυ, c +uA
			0.5	2	_μ/ +μΑ
–Input Bias Current			5	10	±μΛ +μΑ
input blus current			5	11	±μΛ +μΔ
Input Bias Current Drift (+)			8	••	±μ/Υ nA/°C
Open-Loop Transimpedance		50	500		kO
		50	500		142
	+loput		120		мо
input resistance			300		0
Input Capacitance			16		nF
Input Capacitance	Thiput		1.0 1.5 to 3.5		рі V
Common-Mode Pointinge Nange	$V_{cv} = 1.5 V_{to} 3.5 V_{cv}$	19	54		V dB
		40	J4		uв
		1 1 to 2 0	0.05 to 1.05		V
Output voltage Swing	R - 50 O	1.1 10 5.9	10		V mA
Short Circuit Current	$R_L = 50.02$		10		mA m A
			30		MA
			250	425	
Quiescent Current	- · -		350	425	μΑ
		50		4/0	μΑ
Power Supply Rejection Ratio	$V_{\rm S} = +4 V \text{ to } +6 V$	56	66	<i>c</i> -	dR
OPERATING TEMPERATURE RANGE		-40		+85	с

ABSOLUTE MAXIMUM RATINGS

Table 3.

Parameter	Rating
Supply Voltage	12.6 V
Internal Power Dissipation ¹	
PDIP Package (N-8)	1.3 Watts
SOIC_N (R-8)	0.75 Watts
SOT-23 Package (RJ-5)	0.5 Watts
Input Voltage (Common Mode)	$\pm V_{s} \pm 1 V$
Differential Input Voltage	±3.5 V
Output Short Circuit Duration	Observe Power Derating Curves
Storage Temperature Range	–65°C to +125°C
Operating Temperature Range	–40°C to +85°C
Lead Temperature Range (Soldering 10 sec)	+300°C

¹ See Table 4.

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

THERMAL RESISTANCE

 θ_{JA} is specified for device in free air.

Table 4. Thermal Resistance

Package Type	θ _{JA}	Unit
8-Lead PDIP Package	90	°C/W
8-Lead SOIC_N Package	155	°C/W
5-Lead SOT-23 Package	240	°C/W

MAXIMUM POWER DISSIPATION

The maximum power that can be safely dissipated by the AD8005 is limited by the associated rise in junction temperature. The maximum safe junction temperature for plastic encapsulated devices is determined by the glass transition temperature of the plastic, approximately +150°C. Exceeding this limit temporarily causes a shift in parametric performance due to a change in the stresses exerted on the die by the package. Exceeding a junction temperature of +175°C for an extended period can result in device failure.

While the AD8005 is internally short circuit protected, this is not sufficient to guarantee that the maximum junction temperature (+150°C) is not exceeded under all conditions. To ensure proper operation, it is necessary to observe the maximum power derating curves shown in Figure 5.



ESD CAUTION



ESD (electrostatic discharge) sensitive device. Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

TYPICAL PERFORMANCE CHARACTERISTICS



Figure 6. Frequency Response; G = +1, +2, +10; $V_S = \pm 5 V$



Figure 8. Large Signal Frequency Response; G = +2, $R_L = 1 k\Omega$



Figure 9. Frequency Response; G = -1, -10; $V_S = \pm 5 V$







Figure 11. Output Swing vs. Frequency; $V_s = \pm 5 V$

Data Sheet

AD8005





Data Sheet

AD8005

-Vs

12146-027



12146-028

Rev. B | Page 9 of 16

APPLICATIONS DRIVING CAPACITIVE LOADS

Capacitive loads interact with the output impedance of an op amp to create an extra delay in the feedback path. This reduces circuit stability and can cause unwanted ringing and oscillation. A given value of capacitance causes much less ringing when the amplifier is used with a higher noise gain.

The capacitive load drive of the AD8005 can be increased by adding a low valued resistor in series with the capacitive load. Introducing a series resistor tends to isolate the capacitive load from the feedback loop, thereby diminishing its influence. Figure 31 shows the effects of a series resistor on capacitive drive for varying voltage gains. As the closed-loop gain is increased, the larger phase margin allows for larger capacitive loads with less overshoot. Adding a series resistor at lower closed-loop gains accomplishes the same effect. For large capacitive loads, the frequency response of the amplifier is dominated by the roll-off of the series resistor and capacitive load.



SINGLE-SUPPLY LEVEL SHIFTER

In addition to providing buffering, many systems require that an op amp provide level shifting. A common example is the level shifting required to move a bipolar signal into the unipolar range of many modern analog-to-digital converters (ADCs). In general, single supply ADCs have input ranges that are referenced neither to ground nor supply. Instead the reference level is some point in between, usually halfway between ground and supply (+2.5 V for a single supply 5 V ADC). Because high-speed ADCs typically have input voltage ranges of 1 V to 2 V, the op amp driving it must be single supply but not necessarily rail-to-rail.



Figure 32. Bipolar to Unipolar Shift Lever

Figure 32 shows a level shifter circuit that can move a bipolar signal into a unipolar range. A positive reference voltage, derived from the +5 V supply, sets a bias level of +1.25 V at the noninverting terminal of the op amp. In ac applications, the accuracy of this voltage level is not important; however, noise is a serious consideration. A 0.1 mF capacitor provides useful decoupling of this noise.

The bias level on the noninverting terminal sets the input commonmode voltage to +1.25 V. Because the output is always positive, the op amp can be powered with a single +5 V power supply.

The overall gain function is given by the equation:

$$V_{OUT} = -\left(\frac{R2}{R1}\right)V_{IN} + \left(\frac{R4}{R3 + R4}\right)\left(1 + \frac{R2}{R1}\right)V_{REF}$$

In the above example, the equation simplifies to

 $V_{OUT} = -V_{IN} + 2.5 V$

SINGLE-ENDED-TO-DIFFERENTIAL CONVERSION

Many single supply ADCs have differential inputs. In such cases, the ideal common-mode operating point is usually halfway between supply and ground. Figure 33 shows how to convert a single-ended bipolar signal into a differential signal with a common-mode level of 2.5 V.



Figure 33. Single-Ended-to-Differential Converter

Amp 1 has its +input driven with the ac-coupled input signal while the +input of Amp 2 is connected to a bias level of +2.5 V. Thus the –input of Amp 2 is driven to virtual +2.5 V by its output. Therefore, Amp 1 is configured for a noninverting gain of five, $(1 + R_{\rm Fl}/R_{\rm G})$, because $R_{\rm G}$ is connected to the virtual +2.5 V of the –input of Amp 2.

When the +input of Amp 1 is driven with a signal, the same signal appears at the –input of Amp 1. This signal serves as an input to Amp 2 configured for a gain of -5, $(-R_{F2}/R_G)$. Thus the two outputs move in opposite directions with the same gain and create a balanced differential signal.

This circuit can be simplified to create a bipolar in/bipolar out single-ended to differential converter. Obviously, a single supply is no longer adequate and the $-V_s$ pins must now be powered with -5 V. The +input to Amp 2 is tied to ground. The ac coupling on the +input of Amp 1 is removed and the signal can be fed directly into Amp 1.

LAYOUT CONSIDERATIONS

In order to achieve the specified high-speed performance of the AD8005, the user must be attentive to board layout and component selection. Proper R_F design techniques and selection of components with low parasitics are necessary.

The printed circuit board (PCB) must have a ground plane that covers all unused portions of the component side of the board. This provides a low impedance path for signals flowing to ground. Remove the ground plane from the area under and around the chip (leave about 2 mm between the pin contacts and the ground plane). This helps to reduce stray capacitance. If both signal tracks and the ground plane are on the same side of the PCB, also leave a 2 mm gap between ground plane and track.





Figure 34. Inverting and Nonconverting Configurations

Chip capacitors have low parasitic resistance and inductance and are suitable for supply bypassing (see Figure 34). Make sure that

AD8005

one end of the capacitor is within 1/8 inch of each power pin with the other end connected to the ground plane. An additional large (0.47 μF – 10 μF) tantalum electrolytic capacitor must also be connected in parallel. This capacitor supplies current for fast, large signal changes at the output. It must not necessarily be as close to the power pin as the smaller capacitor.

Locate the feedback resistor close to the inverting input pin in order to keep the stray capacitance at this node to a minimum. Capacitance variations of less than 1.5 pF at the inverting input significantly affect high-speed performance.

Use stripline design techniques for long signal traces (that is, greater than about 1 inch). Striplines must have a characteristic impedance of either 50 Ω or 75 Ω . For the stripline to be effective, correct termination at both ends of the line is necessary.

Table 5. Typical	Bandwidth vs.	Gain Setting	Resistors
------------------	---------------	--------------	-----------

Gain	R _F	R _G	R _T	Small Signal –3 dB BW (MHz), Vs = ±5 V
-1	1.49 kΩ	1.49 kΩ	52.3	120 MHz
-10	1 kΩ	100 Ω	100 Ω	60 MHz
+1	2.49 kΩ	∞	49.9 Ω	270 MHz
+2	2.49 kΩ	2.49 kΩ	49.9 Ω	170 MHz
+10	499 Ω	56.2 Ω	49.9 Ω	40 MHz

INCREASING FEEDBACK RESISTORS

Unlike conventional voltage feedback op amps, the choice of feedback resistor has a direct impact on the closed-loop bandwidth and stability of a current feedback op amp circuit. Reducing the resistance below the recommended value makes the amplifier more unstable. Increasing the size of the feedback resistor reduces the closed-loop bandwidth.



Figure 35. Saving Power by Increasing Feedback Resistor Network

In power-critical applications where some bandwidth can be sacrificed, increasing the size of the feedback resistor yields significant power savings. A good example of this is the gain of +10 case. Operating from a bipolar supply (\pm 5 V), the quiescent current is 475 μ A (excluding the feedback network). The recommended feedback and gain resistors are 499 Ω and 56.2 Ω respectively. In order to drive an rms output voltage of 2 V, the output must deliver a current of 3.6 mA to the feedback network. Increasing the size of the resistor network by a factor of 10, as shown in Figure 35, reduces this current to 360 μ A; however, the closed loop bandwidth decreases to 20 MHz.

070606-A

012407-A

OUTLINE DIMENSIONS



Figure 36. 8-Lead Plastic Dual In-Line Package [PDIP] Narrow Body (N-8) Dimensions shown in inches and (millimeters)



CONTROLLING DIMENSIONS ARE IN MILLIMETERS; INCH DIMENSIONS (IN PARENTHESES) ARE ROUNDED-OFF MILLIMETER EQUIVALENTS FOR REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.

Figure 37. 8-Lead Standard Small Outline Package [SOIC_N] Narrow Body (R-8)

Dimensions shown in millimeters and (inches)



Figure 38. 5-Lead Small Outline Transistor Package [SOT-23] (RJ-5) Dimensions shown in millimeters

ORDERING GUIDE

Model ¹	Temperature Range	Package Description	Package Option	Branding Code
AD8005ANZ	-40°C to +85°C	8-Lead Plastic Dual In-Line Package [PDIP]	N-8	
AD8005ARZ	-40°C to +85°C	8-Lead Standard Small Outline Package [SOIC_N]	R-8	
AD8005ARZ-REEL	-40°C to +85°C	8-Lead Standard Small Outline Package [SOIC_N]	R-8	
AD8005ARZ-REEL7	-40°C to +85°C	8-Lead Standard Small Outline Package [SOIC_N]	R-8	
AD8005ARTZ-R2	-40°C to +85°C	5-Lead Small Outline Transistor Package [SOT-23]	RJ-5	H05
AD8005ARTZ-REEL7	-40°C to +85°C	5-Lead Small Outline Transistor Package [SOT-23]	RJ-5	H05
AD8005AR-EBZ		Evaluation Board		
AD8005ART-EBZ		Evaluation Board		

 1 Z = RoHS Compliant Part.

NOTES

NOTES

NOTES



www.analog.com

©1996–2014 Analog Devices, Inc. All rights reserved. Trademarks and registered trademarks are the property of their respective owners. D12146-0-3/14(B)

Rev. B | Page 16 of 16