



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



ADAM-6150

ADAM-6151/6156

15-ch Isolated Digital I/O Real-time Ethernet Module

16-ch Isolated Digital Input/ Digital Output Real-time Ethernet Module



ADAM-6150

FCC CE RoHS COMPLIANT 2002/95/EC

Specifications

Digital Input

- Channels 8
- Dry Contact Logic level 0: open
Logic level 1: close to DGND
- Wet Contact Logic level 0: 0 ~ 3 V_{DC} or 0 ~ -3 V_{DC}
Logic level 1: 10 ~ 30 V_{DC} or -10 ~ -30 V_{DC}
(Dry/Wet Contact decided by switch)
- Input Impedance 5.2 kΩ (Wet Contact)
- Transition Time From logic level 0 to 1: 0.2 ms
From logic level 1 to 0: 0.2 ms

Digital Output

- Channels 7
- Output Voltage Range 8 ~ 35 V_{DC}
- Normal Output Current 100 mA (per channel)

Ordering Information

- ADAM-6150EI 15-ch Isolated DI/O EtherNet/IP Module



ADAM-6151/6156

FCC CE RoHS COMPLIANT 2002/95/EC

Specifications

Digital Input (ADAM-6151)

- Channels 16
- Dry Contact Logic level 0: open
Logic level 1: close to DGND
- Wet Contact Logic level 0: 0 ~ 3 V_{DC} or 0 ~ -3 V_{DC}
Logic level 1: 10 ~ 30 V_{DC} or -10 ~ -30 V_{DC}
(Dry/Wet Contact decided by switch)
- Input Impedance 5.2 kΩ (Wet Contact)
- Transition Time From logic level 0 to 1: 0.2 ms
From logic level 1 to 0: 0.2 ms

Digital Output (ADAM-6156)

- Channels 16
- Output Voltage Range 8 ~ 35 V_{DC}
- Normal Output Current 100 mA (per channel)

Ordering Information

- ADAM-6151EI 16-ch Isolated DI EtherNet/IP Module
- ADAM-6156EI 16-ch Isolated DO EtherNet/IP Module

Common Specifications

General

- LAN 10/100Base-T(X)
- Power Consumption ADAM-6150: 3 W @ 24 V_{DC}
ADAM-6151: 2.7 W @ 24 V_{DC}
ADAM-6156: 3.2 W @ 24 V_{DC}
- Connectors 2 x RJ-45 LAN, (Daisy Chain)
Plug-in screw terminal block (I/O and power)
- Watchdog System (1.6 second)
- Power Input 10 ~ 30 V_{DC}

Protection

- Over Voltage Protection ±35 V_{DC}
- Isolation Protection 2,500 V_{DC}
- Power Reversal Protection

Environment

- Operating Temperature -10 ~ 70°C (14 ~ 158°F)
- Storage Temperature -20 ~ 80°C (-4 ~ 176°F)
- Operating Humidity 20 ~ 95% RH (non-condensing)
- Storage Humidity 0 ~ 95% RH (non-condensing)
0 ~ 95% RH (non-condensing)