



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



COMPLEMENTARY OUTPUT HALL EFFECT LATCH**AH276****General Description**

The AH276 is an integrated Hall sensor with output driver designed for electronic commutation of brushless DC motor applications. The device includes an on-chip Hall sensor for magnetic sensing, an amplifier that amplifies the Hall voltage, a Schmitt trigger to provide switching hysteresis for noise rejection, a temperature compensation circuit to compensate the temperature drift of Hall sensitivity and two complementary open-collector drivers for sinking large load current. It also includes an internal band-gap regulator which is used to provide bias voltage for internal circuits.

Placing the device in a variable magnetic field, if the magnetic flux density is larger than threshold B_{OP} , the pin DO will be turned low (on) and pin DOB will be turned high (off). This output state is held until the magnetic flux density reverses and falls below B_{RP} , then causes DO to be turned high (off) and DOB turned low (on).

AH276 is available in TO-94 (SIP-4L) package.

Features

- On-Chip Hall Sensor
- 3.5V to 16V Supply Voltage
- 350mA (avg) Output Sink Current
- Reversed Supply Voltage Protection
- Build in Over Temperature Protection Function
- -20°C to 85°C Operating Temperature
- Low Profile TO-94 (SIP-4L) Package
- ESD Rating: 300V (Machine Model)

Applications

- Dual-Coil Brushless DC Motor
- Dual-Coil Brushless DC Fan
- Revolution Counting
- Speed Measurement




Figure 1. Package Type of AH276

COMPLEMENTARY OUTPUT HALL EFFECT LATCH

AH276

Pin Configuration

Z4 Package
(TO-94)




Figure 2. Pin Configuration of AH276 (Front View)

Pin Description

| Pin Number | Pin Name | Function |
|------------|-----------------|----------------|
| 1 | V _{CC} | Supply voltage |
| 2 | DO | Output 1 |
| 3 | DOB | Output 2 |
| 4 | GND | Ground |

COMPLEMENTARY OUTPUT HALL EFFECT LATCH

AH276

Functional Block Diagram





Figure 3. Functional Block Diagram of AH276

Ordering Information



| Package | Temperature Range | Part Number | | Marking ID | | Packing Type |
|---------|-------------------|-------------|-------------|------------|------------|--------------|
| | | Lead Free | Green | Lead Free | Green | |
| TO-94 | -20 to 85 °C | AH276Z4-AE1 | AH276Z4-AG1 | AH276Z4-E1 | AH276Z4-G1 | Bulk |
| | | AH276Z4-BE1 | AH276Z4-BG1 | AH276Z4-E1 | AH276Z4-G1 | Bulk |
| | | AH276Z4-CE1 | AH276Z4-CG1 | AH276Z4-E1 | AH276Z4-G1 | Bulk |

BCD Semiconductor's Pb-free products, as designated with "E1" suffix in the part number, are RoHS compliant. Products with "G1" suffix are available in green package.

**COMPLEMENTARY OUTPUT HALL EFFECT LATCH****AH276****Absolute Maximum Ratings (Note 1)** $(T_A=25^{\circ}\text{C})$

| Parameter | Symbol | Value | Unit |
|----------------------------|---------------------|---------------|------------------------------------|
| Supply Voltage | V_{CC} | 20 | V |
| Reverse Protection Voltage | V_{RCC} | -20 | V |
| Magnetic Flux Density | B | Unlimited | Gauss |
| Output Current | Continuous | 350 | mA |
| | Hold | 550 | mA |
| | Peak (start up) | 750 | mA |
| Power Dissipation | P_D | 550 | mW |
| Thermal Resistance | Die to atmosphere | θ_{JA} | 227 $^{\circ}\text{C}/\text{W}$ |
| | Die to package case | θ_{JC} | 49 $^{\circ}\text{C}/\text{W}$ |
| Storage Temperature | T_{STG} | -50 to 150 | $^{\circ}\text{C}$ |
| ESD (Machine Model) | | 300 | V |
| ESD (Human Body Model) | | 2500 | V |

Note 1: Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "Recommended Operating Conditions" is not implied. "Absolute Maximum Ratings" for extended period may affect device reliability.

Recommended Operating Conditions $(T_A=25^{\circ}\text{C})$

| Parameter | Symbol | Min | Max | Unit |
|---------------------|----------|-----|-----|--------------------|
| Supply Voltage | V_{CC} | 3.5 | 16 | V |
| Ambient Temperature | T_A | -20 | 85 | $^{\circ}\text{C}$ |



COMPLEMENTARY OUTPUT HALL EFFECT LATCH

AH276

Electrical Characteristics


($T_A=25^{\circ}\text{C}$, $V_{CC}=14\text{V}$, unless otherwise specified)

| Parameter | Symbol | Test Condition | Min | Typ | Max | Unit |
|--------------------------------|--------------------|---|-----|------|-----|--------------------|
| Output Saturation Voltage | V_{SAT} | $V_{CC}=3.5\text{V}$, $I_O=100\text{mA}$ | | 0.3 | | V |
| | | $I_O=350\text{mA}$ | | 0.35 | 0.6 | V |
| Output Leakage Current | I_{OL} | $V_{CE}=16\text{V}$ | | 0.1 | 10 | μA |
| Supply Current | I_{CC} | $V_{CC}=16\text{V}$, Output Open | | 12 | 16 | mA |
| Output Rise Time | t_r | $R_L=820\Omega$, $C_L=20\text{pF}$ | | 3.0 | 10 | μs |
| Output Fall Time | t_f | $R_L=820\Omega$, $C_L=20\text{pF}$ | | 0.3 | 1.5 | μs |
| Switch Time Differential | Δt | $R_L=820\Omega$, $C_L=20\text{pF}$ | | 3.0 | 10 | μs |
| Output Zener Breakdown Voltage | V_Z | | | 55 | | V |
| Thermal Protection Temperature | TSD | | | 178 | | $^{\circ}\text{C}$ |
| Thermal Protection Hysteresis | ΔTSD | | | 40 | | $^{\circ}\text{C}$ |

Magnetic Characteristics

($T_A=25^{\circ}\text{C}$)

| Parameter | Symbol | Grade | Min | Typ | Max | Unit |
|-----------------|-----------|-------|------|-----|-----|-------|
| Operating Point | B_{OP} | A | 10 | | 50 | Gauss |
| | | B | 5 | | 70 | Gauss |
| | | C | | | 100 | Gauss |
| Releasing Point | B_{RP} | A | -50 | | -10 | Gauss |
| | | B | -70 | | -5 | Gauss |
| | | C | -100 | | | Gauss |
| Hysteresis | B_{HYS} | | | 75 | | Gauss |



COMPLEMENTARY OUTPUT HALL EFFECT LATCH

AH276

Magnetic Characteristics (Continued)




Figure 4. Basic Test Circuit




Figure 5. V_{DO} vs. Magnetic Flux Density




Figure 6. V_{DOB} vs. Magnetic Flux Density



COMPLEMENTARY OUTPUT HALL EFFECT LATCH

AH276

Typical Performance Characteristics




Figure 7. I_{CC} vs. V_{CC}




Figure 8. $B_{OP}/B_{RP}/B_{HYS}$ vs. V_{CC}




Figure 9. $B_{OP}/B_{RP}/B_{HYS}$ vs. Ambient Temperature




Figure 10. P_D vs. Ambient Temperature

COMPLEMENTARY OUTPUT HALL EFFECT LATCH

AH276

Typical Performance Characteristics (Continued)




Figure 11. I_{CC} vs. Ambient Temperature




Figure 12. V_{SAT} vs. Ambient Temperature

Typical Applications




Figure 12. Typical Application Circuit




COMPLEMENTARY OUTPUT HALL EFFECT LATCH

AH276

Mechanical Dimensions

TO-94

Unit: mm(inch)





BCD Semiconductor Manufacturing Limited

<http://www.bcdsemi.com>

IMPORTANT NOTICE

BCD Semiconductor Manufacturing Limited reserves the right to make changes without further notice to any products or specifications herein. BCD Semiconductor Manufacturing Limited does not assume any responsibility for use of any its products for any particular purpose, nor does BCD Semiconductor Manufacturing Limited assume any liability arising out of the application or use of any its products or circuits. BCD Semiconductor Manufacturing Limited does not convey any license under its patent rights or other rights nor the rights of others.

MAIN SITE

- Headquarters

BCD Semiconductor Manufacturing Limited

No. 1600, Zi Xing Road, Shanghai Zizhu Science-based Industrial Park, 200241, China
Tel: +86-21-24162266, Fax: +86-21-24162277

- Wafer Fab

Shanghai SIM-BCD Semiconductor Manufacturing Co., Ltd.

800 Yi Shan Road, Shanghai 200233, China
Tel: +86-21-6485 1491, Fax: +86-21-5450 0008

REGIONAL SALES OFFICE

Shenzhen Office

Shanghai SIM-BCD Semiconductor Manufacturing Co., Ltd., Shenzhen Office

Unit A Room 1203, Skyworth Bldg., Gaoxin Ave. 1.S., Nanshan District, Shenzhen, China
Tel: +86-755-8826 7951
Fax: +86-755-8826 7865

Taiwan Office

BCD Semiconductor (Taiwan) Company Limited

4F, 298-1, Rui Guang Road, Nei-Hu District, Taipei, Taiwan
Tel: +886-2-2656 2808
Fax: +886-2-2656 2806

USA Office

BCD Semiconductor Corp.

30920 Huntwood Ave. Hayward, CA 94544, USA
Tel : +1-510-324-2988
Fax: +1-510-324-2788