

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









PolySwitch® PTC Devices

Overcurrent Protection Device

PRODUCT: AHS300

DOCUMENT: SCD27199

REV LETTER: E

REV DATE: JULY 26, 2016


PAGE NO.: 1 OF 2

Specification Status: Released


Maximum Electrical Rating


Operating Voltage / Interrupt Current $16V_{DC}$ / 70A

Marking:









Notes:

- All metal surfaces are tin plated.
- 2. Drawing not to scale.

TABLE I. DIMENSIONS:

_															
	A		В		С		D		E		F		G		Н
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
mm:	8.0	9.4		3.0	6.0	6.71	0.56	0.71	0.56	0.71	3.68	3.94	0.66	1.37	0.43
in*:	(0.315)	(0.370)		(0.118)	(0.24)	(0.264)	(0.022)	(0.028)	(0.022)	(0.028)	(0.145)	(0.155)	(0.026)	(0.054)	(0.017)

TABLE II. PERFORMANCE RATINGS:

	CU	RRENT	RATING	iS**		TIME TO TRIP**		TANCE UES	TRIPPED-STATE POWER	
		-		_					DISSIPATION**	
AM	AMPS		AMPS		PS	SECONDS AT	OHMS		WATTS AT	
AT 0°C		AT 20°C		AT 60°C		20°C, 15.0A	AT 20°C		20°C	
HOLD	TRIP	HOLD	TRIP	HOLD	TRIP	MAX	MIN	MAX*	MAX	
3.7	7.4	3	6	2.1	4.2	8	0.024	0.083	3	

^{*} Maximum resistance is measured 1 hour after reflow.

Reference Documents: PS300, PS400

Precedence: This specification takes precedence over documents referenced herein.

Effectivity: Reference documents shall be the issue in effect on the date of invitation for bid.

CAUTION: Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.

Materials Information

Directive 2002/95/EC

ROHS Compliant

ELV Compliant

Pb-Free

Halogen Free*

Directive 2000/53/EC Compliant





^{**} Values specified were determined using PCB's with 0.140" x 2.0 ounce copper traces.

^{*} Halogen Free refers to: Br≤900ppm, Cl≤900ppm, Br+Cl≤1500ppm.



PolySwitch® PTC Devices

Overcurrent Protection Device

PRODUCT: AHS300

DOCUMENT: SCD27199 REV LETTER: E

REV DATE: JULY 26, 2016 PAGE NO.: 2 OF 2

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and shall not be used for, any purpose (including, without limitation, military, aerospace, medical, lifesaving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse documentation. The sale and use of Littelfuse products is subject to Littelfuse Terms and Conditions of Sale, unless otherwise agreed by Littelfuse.