



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Air LED

## AIL024541

Old item no.: 16717BK



## Air LED T60 BI 106 932 CLA NA

Air LED is a self-balancing task light with a spring-balanced arm for maximum reach and flexibility. It has perfect balance and smooth movement that make it feel feather light – in spite of its steel construction. Edge clamp mount. Color: black.



#### Lightsource

|   |                  |
|---|------------------|
| Number of lamps                         | 1                |
| Lamp power (W)                          | 6                |
| Lightsource                             | LED              |
| CRI and/or Color Temperature            | CRI 90, 3200K    |
| Lumen/Watt                              | 38               |
| Lumen Out                               | 300              |
| LLMF LED 50000h Ta25                    | 0.70             |
| MacAdam step                            | 3,5              |
| Average useful life (IEC 62717)<br>Ta25 | 50000h<br>L70B50 |

#### Technical data

|                                  |    |
|----------------------------------|----|
| Maximum ambient temperature (°C) | 25 |
| IP classification                | 20 |

#### Body

|               |       |
|---------------|-------|
| Body material | Steel |
| Body color    | Black |

#### Ballast

|                 |  |
|-----------------|--|
| Type of Ballast | AC/DC = alternating current/<br>direct current |
|-----------------|--|

#### Electrical data

|                        |     |
|------------------------|-----|
| Maximum voltage (V)    | 240 |
| Maximum frequency (Hz) | 60  |
| Minimum frequency (Hz) | 50  |
| Voltage from (V)       | 100 |
| Total consumption (W)  | 8   |

#### Dimensions

|                  |     |
|------------------|-----|
| Net weight (kg)  | 0,9 |
| Arm length (in.) | 24  |

#### Termination

|       |     |
|-------|-----|
| Optic | ASY |
|-------|-----|

#### Optic

|                            |       |
|----------------------------|-------|
| Light distribution Up/Down | 0/100 |
|----------------------------|-------|

Air LED  
AIL024541



Air LED T60 BI 106 932 CLA NA

Air LED is a self-balancing task light with a spring-balanced arm for maximum reach and flexibility. It has perfect balance and smooth movement that make it feel feather light – in spite of its steel construction. Edge clamp mount. Color: black.



## Drawings

