



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





AK-SecureSocketSwitch



Remote controllable IP socket for networks

The **AK-SecureSocketSwitch** is a switchable IP socket, which is used to switch on or off any power consumers as well as to monitor and measure the current power consumption. Due to the integrated micro switch you do not need any additional power supply cable, since the **AK-SecureSocketSwitch** possesses two integrated network connections. The high-performance and safety relay which is equipped with silver tin oxide contacts (AgSnO₂), is offering you a high switching capacity, a high durability as well as a reliable and trouble-free operation. The network connection is performed by default via a 1024Bit-SSL encryption and can additionally be secured or expanded by server and client certificates. The consumption data are logged for up to 30 days and can be displayed on the WEB monitor. Lots of additionally programmable software functions allow you to control, reduce and optimise your power consumption in a targeted and efficient way. Using our M2M solution, the **AK-SecureSocketSwitch** is easily and simply available via the Internet at any time. Without apps and without tools.

The web monitor can be simply and easily accessed without any additional application via the network, the internet or a mobile terminal such as a mobile phone. It shows all relevant data in realtime and you immediately get an overview of the consumption or power of the connected electrical consumer.



Options:

The existing WEB interface can be exchanged, adapted or changed according to the customers' specifics. To do so, a Flash-File system is available which can be accessed simply and easily after releasing a FTP connection.

After having released an additional TCP-IP network port you can also directly access the **AK-SecurePowerSwitch** via the network and directly control or prompt with simple ASCII commands such as `<PW0>`, `<PW1>` or `<PW?>` .

Technical data

- **Dimensions:**
135 x 55 x 40 mm (LxWxH)
- **Housing**
Impact-proof ABS plastic
- **Weight**
200 grams
- **Temperature range:**
-40°C .. + 70°C
- **Standards**
CE / WEEE / RoHS-II
EN 55022 Class B
EN 55024 Class A
- **Protection class**
IP30
- **Power supply:**
110-230V 50/60Hz
about 1.2 watts
- **Switching capacity**
110-230V 50/60Hz
10A or 2300 watts
- **Connections**
1 x CEE 7/4 connector plug (type F)
1 x CEE 7/4 power input (type F)
2 x RJ45 (micro switch)
- **Ethernet (M-DIX)**
10 Half Duplex
10 Full Duplex
100 Half Duplex
100 Full Duplex
AutoSensing
- **Relay**
Contact material = AgSnO₂
Max. continuous current = 16A
Max. switch-on current = 25A
Nominal voltage = 250V
Max. switching voltage = 400V
Max. switching capacity AC1 = 4.000VA
Max. switching capacity AC15 = 750VA

Supported protocols IP-Dual-Stack

- IPv4
- TCP
- UDP
- FTP
- FTSP
- TFTP
- ICMP
- ARP
- SNMP
- LPR
- DHCP
- BOOTP
- DNS
- TELNET
- HTML
- HTTP
- HTTPS
- DYNDNS
- SMTP
- POP3
- SYSLOG
- AK-M2M
- IPv6
- NDP
- ICMPv6
- DHCPv6
- TCPv6
- UDPv6
- Netbios-NS
- LLMNR
- ZeroConfig
-APIPA
-AutoIP
- IP-Multicast
- IEEE802.1x
- SSL 3.0
- TLS 1.0
- TLS1.1
- TLS1.2

Management

1. Telnet
2. Browser

Views

Front view

Side view



Software Functions

- Controlling the IP socket via the Internet.
- Suppressing devices through an interruption in the power supply.
- Time controlled switching of power consumers.
- Switching of power consumers depending on the consumption.
- Automatic switching the power consumers on or off.
- Controlling the IP socket through the network with ASCII commands.
- XML data exchange.
- Examining the inactivity of network devices.
- Optical display of the current consumption.