



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



AMT-1023C-DH25

23" LED Touch Monitor



Features

- Ten point multi-touch
- High speed USB3.0 hub
- LED backlight
- 1920 x 1080 resolution
- Wide viewing angles
- Windows 8 compatibility
- HDMI/DVI/VGA interface



Introduction

AMT-1023C-DH25, 23 inch-wide touch screen, provides a smooth and intuitive touch experience with 1920 x 1080 pixel high definition images and 178°(H)/178°(V) viewing angles.

It supports HDMI, DVI, and VGA interface to be fully compatible with a wide variety of systems.

Specifications

Display	Model	AMT-1023C-DH25
	Size	23" LED
	Resolution	1920 x 1080
	View Angel	178°/178° (H) 178°/178° (V)
	Brightness	250 (cd/m ²)
	Color Support	16.7M
	Contrast Ratio	1000:1
	Response Time	5 [msec]
	Backlight Life	30,000 (hrs)
Environment	Operating Temperature	0~40°C
	Storage Temperature	-20°C~ 60°C
	Humidity	Operating: 10 ~ 85% Non Operating: 5~85%
	Vibration	Vibration Frequency: 5~200Hz, Acceleration: 1.0g Test Duration: 60 minutes per axis
System	I/O	VGA x1; DVI x1; HDMI x1; UpstreamUSB3.0 x1; Downstream USB3.0 x4
	OSD	Menu Functions: Luminance, Image Setup, Color Temp, OSD Setup
	Power	58 W
	EMC Compliance	CE & FCC

AMT-1023C-DH25

23" LED Touch Monitor

Drawing

