



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



DATA SHEET

WIRELESS COMPONENTS

FR4 Chip Antenna
ANT1204F007R0870A
UHF (870MHz)
1204 Series



Preliminary



FEATURES

- Compact size
- Omni-directional Radiation
- Tape & reel automatic mounting
- Reflow process compatible
- RoHS compliant

APPLICATIONS

- Smart meter
- Industrial remote control

ORDERING INFORMATION

All part numbers are identified by the series, packing type, material, size, antenna type, working frequency and packing quantity.

PART NUMBER

ANT 1204 F 007 R 0870 A
(1) (2) (3) (4) (5) (6)

(1) PRODUCT

ANT = Antenna

(2) SIZE

1204=12 × 4 mm

(3) ANTENNA TYPE

L, F, A=Chip antenna

(4) SERIAL NO.

007

(5) PACKING STYLE

R = Tape and Reel

(6) WORKING FREQUENCY

0870 = UHF 870MHz

PHYCOMP CTC

CAN4311059070871K

I2NC

431105907087

SPECIFICATION

Table 1

DESCRIPTION	VALUE
Centre Frequency	870MHz
Bandwidth	30 MHz (Typ.)
Return Loss	10 dB min
Polarization	Linear
Azimuth Beamwidth	Omni-directional
Peak Gain	1.67 dBi (Typ.)
Impedance	50Ω
Operating Temperature	- 40~85 °C
Maximum Power	1 W
Termination	Cu / Au (Environmentally-Friendly Leadless)
Resistance to Soldering Heats	260°C / 10 sec

NOTE

The specification is defined on Yageo evaluation board

DIMENSION

Table 2 Machinical Dimension

	DIMENSION
L (mm)	12.20±0.20
W (mm)	4.00±0.20
T (mm)	1.60±0.20

OUTLINES




Fig. 1 Antenna outlines

Table 3 Termination configuration

TERMINAL NAME	Function
S1	Feeding Point
S2	Soldering Point

REFERENCE DESIGN OF EVALUATION BOARD




Fig. 2 Outlook and dimension of evaluation board






Fig. 3 Details of soldering Pad

ELECTRICAL PERFORMANCE



REVISION HISTORY

REVISION	DATE	CHANGE NOTIFICATION	DESCRIPTION
Preliminary	Sept. 11, 2013		- New data sheet antenna, 870MHz application, 1204 series