



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Apacer

The Most **Reliable**
Storage For Industries



Industrial microSD H1-M



Industrial microSD H1-M

Overview

Apacer Industrial microSD H1-M series conforming to SD3.0 specification are designed with high performance, good reliability, wide compatibility, and through UHS-I, supporting speed class up to U3. The microSD 3.0 card is capable of delivering better performance and P/E cycles by the latest firmware architecture including a powerful built-in Error Correction, Read Retry, Wear Leveling & Bad Block Management algorithms.



Feature

- Compliant with SD 3.0 Specification
- S.M.A.R.T supported
- Wear-Leveling and Block Management
- Support SD mode and SPI mode
- Low Power Consumption
- Auto Read Refresh
- Power Failure Management

Specifications

Model	Industrial microSD H1-M
Interface	SD3.0
Form Factor	microSD
NAND Flash Type	MLC
Capacity	4G~128G
Sustained Read Performance (MB/sec)	Up to 75
Sustained Write Performance (MB/sec)	Up to 65
ECC Engine	Built-in 42-bit per 1K bytes BCH ECC
Standard Operating Temperature (°C)	-25 ~ + 85
Extended Operating Temperature (°C)	-40 ~ + 85
Storage Temperature (°C)	-40 ~ + 85
Shock	(Operating)1,500G, 0.5ms
Vibration	20Hz~80Hz/1.52mm (frequency/displacement) 80Hz~2,000Hz/20G (frequency/accelerate)
Operating Voltage	3.3 V ± 5%
Power Consumption	Operating: 155 Ma & Standby: 445 µA
Dimension (L x W x H)	15x11x1 (mm)
MTBF (hours)	>3,000,000

For more information, contact your Apacer representative

Global Presence

Taiwan (Headquarters)
Apacer Technology Inc.
Tel: +886-2-2267-8000
Fax: +886-2-2267-2261

Europe
Apacer Technology B.V.
Tel: +31-40-267-0000
Fax: +31-40-290-0686

U.S.A.
Apacer Memory America, Inc.
Tel: +1-408-518-8699
Fax: 1-510-249-9551

China
Apacer Electronic(Shanghai)
Co., Ltd.
Tel: +86-21-6228-9939

Japan
Apacer Technology Corp.
Tel: +81-3-5419-2668
Fax: +81-3-5419-0018

India
Apacer Technologies Pvt. Ltd.
Tel: +91-80-41529061~3
Fax: +91-80-41700215