



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com


Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China






Space-saving SOP4-pin high capacity type with built-in input resistor

PhotoMOS®
GU SOP 1 Form A High Capacity
Voltage-sensitive (AQY212FG2S)



mm inch



RoHS compliant

The voltage-sensitive type, which eliminates the need to mount an external input resistor, is now available in a small package (recommended input voltage is 5 V). Man-hours spent mounting external input resistors are cut and board designing is simplified.


2. Saves space on PC board

Since the small package size remains the same while including a built-in input resistor, space on the PC board is saved. This makes it easier to incorporate space savings when designing miniature devices.

3. Continuous load current of 1.25A
 This miniature SOP type controls 1.25A/60V load.

TYPICAL APPLICATIONS

- 1. Measuring and testing equipment**
 Semiconductor testing equipment, Probe cards, Datalogger, Board tester and other testing equipment.
- 2. Telecommunication, Broadcasting, and Medical equipment**



<Artistic impression of PC board space savings due to built-in resistor>

*Above is in case of SSOP.

FEATURES

1. Built-in input resistor means less man-hours when mounting

TYPES

	Output rating*1		Package	Part No.*2			Packing quantity	
	Load voltage	Load current		Tube packing style	Tape and reel packing style		Tube	Tape and reel
					Picked from the 1/2-pin side	Picked from the 3/4-pin side		
AC/DC dual use	60V	1.25A	SOP4-pin	AQY212FG2S	AQY212FG2SX	AQY212FG2SZ	1 tube contains: 100 pcs. 1 batch contains: 2,000 pcs.	1,000 pcs.

Notes: *1 Indicate the peak AC and DC values.

*2 For space reasons, only "212FG2" is marked on the product. The three initial letters of the part number "AQY", the package (SOP) indicator "S", and the packing style indicator "X" or "Z" have been omitted.

RATING

1. Absolute maximum ratings (Condition: ambient temperature 25°C 77°F)


Item	Symbol	AQY212FG2S	Remarks	
Input	Input voltage	V _{IN}	6V	
	Input reverse voltage	V _{RIN}	5V	
	Power dissipation	P _{in}	65mW	
Output	Load voltage (peak AC)	V _L	60V	
	Load current	I _L	1.25A	
	Peak load current	I _{peak}	3A	Peak AC, DC
	Power dissipation	P _{out}	400mW	100ms (1shot), V _L =DC
Total power dissipation	P _T	450mW		
I/O isolation voltage	V _{iso}	500V AC		
Operating temperature	T _{opr}	-40°C to +85°C -40°F to +185°F	Non-condensing at low temperatures	
Storage temperature	T _{stg}	-40°C to +100°C -40°F to +212°F		

GU SOP 1 Form A High Capacity Voltage-sensitive (AQY212FG2S)

2. Electrical characteristics (Condition: ambient temperature 25°C 77°F)

Item			Symbol	AQY212FG2S	Condition	
Input	Operate voltage	Typ.	V _{Fon}	1.4V	I _L = 100mA	
		Max.		4V		
	Turn off voltage	Min.	V _{Foff}	0.8V		
		Typ.		1.4V		
	Input current	Typ.	I _{IN}	8.5mA		V _{IN} = 5V
Output	On resistance	Typ.	R _{on}	0.2Ω	V _{IN} = 5V, I _L = Max. Within 1 s on time	
		Max.		0.5Ω		
	Output capacitance	Typ.	C _{out}	—		V _{IN} = 0V, V _B = 0V, f = 1MHz
		Max.		—		
	Off state leakage current	Typ.	I _{Leak}	—		
Max.		1μA				
Transfer characteristics	Turn on time*	Typ.	T _{on}	0.7ms	V _{IN} = 5V, I _L = 100mA, V _L = 10V	
		Max.		5ms		
	Turn off time*	Typ.	T _{off}	0.1ms		
		Max.		0.5ms		
	I/O capacitance	Typ.	C _{iso}	0.8pF		f = 1MHz, V _B = 0V
		Max.		1.5pF		f = 1MHz, V _B = 0V
	Initial I/O isolation resistance	Min.	R _{iso}	1,000MΩ		500V DC
Maximum operating frequency	Max.	—	5 cps	V _{IN} = 5V, duty = 50% V _I × I _L = 75V·A		

*Turn on/Turn off time



RECOMMENDED OPERATING CONDITIONS

Please obey the following conditions to ensure proper device operation and resetting.

Item	Symbol	Minimum	Typical	Maximum	Unit
Input voltage	V _{IN}	4.5	5	5.5	V


■ These products are not designed for automotive use.

If you are considering to use these products for automotive applications, please contact your local Panasonic Corporation technical representative.

REFERENCE DATA


1. Load current vs. ambient temperature characteristics

Allowable ambient temperature: -40°C to +85°C
-40°F to +185°F




2. On resistance vs. ambient temperature characteristics

Measured portion: between terminals 3 and 4
Input voltage: 5V; Load voltage: Max. (DC);
Continuous load current: Max. (DC)




3. Turn on time vs. ambient temperature characteristics

Input voltage: 5V; Load voltage: 10V (DC);
Continuous load current: 100mA (DC)




4. Turn off time vs. ambient temperature characteristics

Input voltage: 5V; Load voltage: 10V (DC);
Continuous load current: 100mA (DC)




5. Turn on voltage vs. ambient temperature characteristics

Load voltage: 10V (DC);
Continuous load current: 100mA (DC)




6. Turn off voltage vs. ambient temperature characteristics

Load voltage: 10V (DC);
Continuous load current: 100mA (DC)




7. Input current vs. ambient temperature characteristics

Input voltage: 5V




8. Current vs. voltage characteristics of output at MOS portion

Measured portion: between terminals 3 and 4
Ambient temperature: 25°C 77°F




9. Input current vs. input voltage characteristics

Ambient temperature: 25°C 77°F
(Recommended input voltage: 5±0.5V)




10. Off state leakage current vs. load voltage characteristics

Measured portion: between terminals 3 and 4
Ambient temperature: 25°C 77°F




11. Turn on time vs. input voltage characteristics

Measured portion: between terminals 3 and 4
Load voltage: 10V (DC); Continuous load current: 100mA (DC); Ambient temperature: 25°C 77°F




12. Turn off time vs. input voltage characteristics

Measured portion: between terminals 3 and 4
Load voltage: 10V (DC); Continuous load current: 100mA (DC); Ambient temperature: 25°C 77°F



13. Output capacitance vs. applied voltage characteristics

Measured portion: between terminals 3 and 4
Frequency: 1 MHz, 30m Vrms;
Ambient temperature: 25°C 77°F



14. Max. operating speed vs. load voltage-load current characteristics

Input voltage: 5V
Ambient temperature: 25°C 77°F

