

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







| | 1 | 2 | | 3 | | 4 | | | 5 | | | 6 | | 7 | |
|---|---|--|-----|----------------|---|----------------------|------|------------------|---|-----|---|-------|---|---|---|
| А | Materials: DESCRIPTION INSULATION JACKET Material HDPE PVC Material HDPE PVC Conductor: | | | | | | | | | | | | | | А |
| В | Strength Unaged ≥1.69 ≥1.05 24AWG*4P | | | | | | | | | | | В | | | |
| С | 3. Flexibility Test 4. Flame Retardant Test PASS FT2 ECN No: ECN STATE: - HDPE - Min. Average Thickness: 0.18MM - Diameter: 0.92±0.05MM • Jacket: | | | | | | | | | | | | С | | |
| D | - PVC, CM | | | | | | | | | | | | D | | |
| Е | Jacket – | DC Conductor Resistance @20°C: ≤93.25Ω/KM 24ΔWG | | | | | | | | | Е | | | | |
| F | Green, White/Green Brown, White/Brown Orange, Wnite/Orange Insulation Resistance @20°C: ≥100MΩ-I | | | | | | | | | -КМ | F | | | | |
| G | | 1:1 CE 0.40 0.25 | | | | Approved Title Cat5e | | Title Cat5e, UTF | P-P305T TP, Twisted Pair, AWG24/1, solid, 305 meters | | G | | | | |
| Н | Ro | | ±3° | Modification [| | | Name | | ASSIVIAIVI | | | rev00 | н | | |
| | 1 2 | | | | 3 | 4 | 4 | | | 5 | | 6 7 | | 7 | |