

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China












		REVISIONS			
REV	ECO	DESCRIPTION	DATE	BY	APPR
A1	-	RELEASE DRAWING	03MAY18	RIMON	TOMMY









PLUG, 18 PIN, ATV SERIES, REDUCED DIAMETER WIRE SEAL

ATV06-18SX-RR01


## NOTES: UNLESS OTHERWISE SPECIFIED

- 1. SEE SHEET 2 FOR KEY ARRANGEMENTS AND COLORS.
- 2. MATERIAL:

HOUSING: THERMOPLASTIC

SEAL: SILICONE RUBBER, COLOR: YELLOW

- 3. MODIFICATIONS: REDUCED DIAMETER WIRE SEAL
- 4. SPECIFICATIONS:
  - 4.1 CURRENT RATING: 13 AMPS
  - 4.2 OPERATING TEMPERATURE: -55°C TO +125°C.
  - 4.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
  - 4.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
  - 4.5 MOISTURE RESISTANCE: IP67 ( MATED CONDITION )
  - 4.6 MATING CYCLE DURABILITY: 100 CYCLES
  - 4.7 RoHS COMPLIANT
- 5. MATING PART: ATV02-18PX\* RECEPTACLE & ATV04-18PX\* RECEPTACLE (X = A,B,C,D KEYS; \* = MODIFICATIONS AND COLORS)
- 6. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.





|--|


CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL
SIZE	O.D.	O.D.	WIRE RANGE
16	1.12 mm (.044 in)	2.31 mm (.090 in)	

	SEE S	SHEET 2	:					
	PART N	NUMBER			DESCRIPTION			ITEM
QUANTITY			MA	TERI/	٩LS	3 LI	ST	
	WISE SPECIFIED	SIG	NATURE	S DATE		Λ	mphonol	
1) All dimensions are in metric(mm). 2) Tolerances are as follows:  1 PL DEC ±0.30 2 PL DEC ±0.15 3) Note reference =   X		DRAWN:	RIMON.MA	08JAN18	•		imprierioi	
		CHECKED:	ORION.LI	08JAN18			_	
		ENGINEER:			44724 Morley Drive Clinton Township, MI 48036			
MATERIAL SPECIFICATIONS:		APPROVAL:	TOMMY.XIE	08JAN18				
		CUSTOMER:					LUG, 18 PIN, ATV SERIES	
			NG IS SUPPLIE		REDUCED DIAMETER WIRE S		UCED DIAMETER WIRE SEAL	
PROCESS SPECIFICATIONS:  NEXT ASSY:		SPECIFICATI SHOWN HER THE AMPHEN OF REPRODU	ONS AND PERI EON ARE THE	FORMANCE DATA PROPERTY OF TION. NO RIGHTS MPLIED. ALL	B	C-	ATV06-18SX-RR01	A1
			RING VARIATIO		SCALE: N	ONE	SHEET 1 OF	2


REVISIONS						
REV	REV ECO DESCRIPTION		DATE	BY	APPR	
A1	-	RELEASE DRAWING	03MAY18	RIMON	TOMMY	








KEY-B CONFIGURATION				
COLOR	PART NUMBER			
BLACK	ATV06-18SB-RR01			



KEY-C CONFIGURATION				
COLOR	PART NUMBER			
GREEN	ATV06-18SC-RR01			



KEY-D CONFIGURATION

PART NUMBER

ATV06-18SD-RR01

	SEE S	SHEET 2	!						
	PART NUMBER					DE	SCRIPTION		ITEM
QUANTITY MATERIA				٩LS	S LI	ST			
UNLESS OTHERWISE SPECIFIED  1) All dimensions are in metric(mm).		SIG	NATURE:	Ampheno		$\overline{a}$	$\overline{}$		
2) Tolerances are		DRAWN:	RIMON.MA	03JAN18			ппрпеп	$\mathbf{O}$	
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	3 ± 1/64 CHECKED: ORIONLI 03JAN18 Sine Systems - www.amphenol-sine.com		_					
3) Note reference = X		ENGINEER:					44724 Morley Drive Clinton Township, MI 48036		
MATERIAL SPECIFICATIONS:		APPROVAL:	TOMMY.XIE	03JAN18					
		CUSTOMER:					LUG, 18 PIN, ATV SER		
			NG IS SUPPLIED			RED	UCED DIAMETER WIRE	E SEAL	
PROCESS SPECIFICATIONS:		SPECIFICATI SHOWN HER THE AMPHEI OF REPROD	ONS AND PERF EON ARE THE I	FORMANCE DATA PROPERTY OF TION. NO RIGHTS IPLIED. ALL	B	C-	ATV06-18SX-RF	R01	A1
NEXT ASSY:		MANUFACTU	ANUFACTURING VARIATIONS.		SCALE: N	ONE	SHEET	2 or	2

COLOR

**BROWN** 

ATV06-18SX-RR01 | REV: A1 | SH: 2 | OF: 2

TITLE: PLUG, 18 PIN, ATV SERIES, REDUCED DIAMETER WIRE SEAL DWG NO: