



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!









## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



1	2	3	4	5	6	7	A																																								
A	<p style="text-align: center;"><b>NOTES:</b></p> <ol style="list-style-type: none"> <li>1. Material: <ol style="list-style-type: none"> <li>1.1 Housing: PBT+30%GF UL94V-0, Color Blue</li> <li>1.2 Shell: Brass</li> <li>1.3 Contact :Copper Alloy</li> </ol> </li> <li>2. FINISH: <ol style="list-style-type: none"> <li>2.1 Contact Area: Selective 15u"Au Solder Area: Tin Plated Under: Ni Plated</li> </ol> </li> <li>3. MECHANICAL: <ol style="list-style-type: none"> <li>3.1 Mating Force:3.57kgf Max.</li> <li>3.2 Unmating Force:1.02kgf Min</li> <li>3.3 Durability:1500 cycles Min</li> </ol> </li> <li>4. ELECTRICAL: <ol style="list-style-type: none"> <li>4.1 Current Rating:1.0A</li> <li>4.2 Dielectric Strength:100V AC FOR 1 MINUTE</li> <li>4.3 Contact Resistance:30mΩ Max</li> <li>4.4 Insulation Resistance:100 MΩ Min</li> <li>5. Operating temperature: -55°C TO +85°C</li> <li>6. PACKING: Tray</li> </ol> </li> </ol>						A																																								
B	  						B																																								
C	   <p style="text-align: center;">RECOMMENDED P.C.B LAYOUT (TOLERANCE:±0.05)</p>						C																																								
D	<p>Customer-No.</p>						D																																								
E	<p>ASSMANN WSW-No. <b>AU-Y1007-3-R</b></p>						E																																								
F	<p>Drawing-No. ASS 5779 CO</p>						F																																								
G	<p>Replace</p>						G																																								
H	<p>rev00</p>						H																																								
<p><b>RoHS compliant</b></p>																																															
1	2	3	4	5	6	7	H																																								
<table border="1"> <tr> <th>Scale</th> <td>Free</td> </tr> <tr> <th>TOLERANCE</th> <td></td> </tr> <tr> <td>.X</td> <td>±0.30</td> </tr> <tr> <td>.XX</td> <td>±0.20</td> </tr> <tr> <td>.XXX</td> <td>±0.10</td> </tr> <tr> <th>DIM</th> <td>TOL</td> </tr> <tr> <td>X. °</td> <td>±5°</td> </tr> <tr> <th>Angle</th> <td>TOL</td> </tr> <tr> <th>UNIT</th> <td>mm</td> </tr> </table>		Scale	Free	TOLERANCE		.X	±0.30	.XX	±0.20	.XXX	±0.10	DIM	TOL	X. °	±5°	Angle	TOL	UNIT	mm	<table border="1"> <tr> <th>Free</th> <td></td> </tr> </table>	Free		<table border="1"> <tr> <th>Id.</th> <td>Ⓢ</td> </tr> <tr> <th>Drawn</th> <td>Winnie</td> </tr> <tr> <th>Modification</th> <td></td> </tr> <tr> <th>Date</th> <td>07.06.2013</td> </tr> <tr> <th>Name</th> <td>Winnie</td> </tr> </table>	Id.	Ⓢ	Drawn	Winnie	Modification		Date	07.06.2013	Name	Winnie	<table border="1"> <tr> <th>Date</th> <td>07.06.2013</td> </tr> <tr> <th>Name</th> <td>Winnie</td> </tr> <tr> <th>Approved</th> <td>07.06.2013</td> </tr> <tr> <th>Name</th> <td>Winnie</td> </tr> </table>	Date	07.06.2013	Name	Winnie	Approved	07.06.2013	Name	Winnie	<table border="1"> <tr> <th>ASSMANN</th> <td>WWSW/</td> </tr> <tr> <th>components</th> <td></td> </tr> </table>	ASSMANN	WWSW/	components	
Scale	Free																																														
TOLERANCE																																															
.X	±0.30																																														
.XX	±0.20																																														
.XXX	±0.10																																														
DIM	TOL																																														
X. °	±5°																																														
Angle	TOL																																														
UNIT	mm																																														
Free																																															
Id.	Ⓢ																																														
Drawn	Winnie																																														
Modification																																															
Date	07.06.2013																																														
Name	Winnie																																														
Date	07.06.2013																																														
Name	Winnie																																														
Approved	07.06.2013																																														
Name	Winnie																																														
ASSMANN	WWSW/																																														
components																																															