

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







## SMD Glass Sealing Crystals 8.0 x 4.5 x 1.5 mm AX Series


## **Features**


- · Reliable glass sealed ceramic package.
- · Wide operating temperature range.
- · Superior and reliable performance in harsh environment.
- · Application : TPMS, ECM, ABS and sensor modules.
- · Contains Pb in sealing glass exempted by RoHS directive.

Electrical Specifications	
Item / Type	AX
Frequency Range	8 ~ 40 MHz
Overtone	Fundamental
Frequency Tolerance (at 25 °C)	± 30 ppm
Frequency Stability	$\pm$ 50 ppm Max. (-40 $\sim$ +85 $^{\circ}$ C)
Operating Temperature Range	- 40 ~ +150 ℃
Drive Level	10 μW (typical) ; 500 μW (Max.)
Load Capacitance	8 pF, or specify
Storage Temperature Range	- 40 ~ +150 °C


Equivalent Series Resistance(ESR)		
Fundamental		
8 ~ 10 MHz	120 Ω Max.	
10 ~ 12 MHz	100 Ω Max.	
12 ~ 40 MHz	80 Ω Max.	

## **Dimensions**





**Top View Crystal Connection** 



Top View Suggested Layout

Units: mm