



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## AX104615 Faceplates and Panels - KeyConnect Multi-User Adapter 12-Port



For more Information  
please call

1-800-Belden1



### General Description:

KeyConnect Multi-User Outlet Adapter 12-Ports

### Usage (Overall)

<b>Suitable Applications:</b>	- Used with Multi-User Outlet Box to accept KeyConnect modules that are suitable for use with Belden IBDN Systems 10GX, 4800,3600, 2400 and 1200.
<b>Related Parts:</b>	- Compatible with 10GX, CAT6+ and CAT5E KeyConnect Modular Jacks and Multimedia Modules

### Physical Characteristics (Connectivity)

#### Capacity

<b>Max. Capacity:</b>	12 KeyConnect Modules
-----------------------	-----------------------

#### Access

<b>Front Connection:</b>	Flush
--------------------------	-------

#### Dimensions

Dimensions:

Height (mm)	Width (mm)
43.942	228.092

#### Materials

Materials:

Description	Material
Multi Media KeyConnect Adapter	Metal

#### Color

<b>Color:</b>	Black
---------------	-------

#### Weight

<b>Weight:</b>	0.176 kg
----------------	----------

#### Packaging

<b>Packaging:</b>	Individually packaged in a plastic bag
-------------------	--

### Mechanical Characteristics (Connectivity)

<b>Footprint/Type:</b>	KeyConnect
<b>Storage Temperature Range:</b>	-40°C To +70°C
<b>Installation Temperature Range:</b>	-10°C To +60°C
<b>Operating Temperature Range:</b>	-10°C To +60°C

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

<b>EU Directive 2002/95/EC (RoHS):</b>	Yes
<b>EU RoHS Compliance Date (mm/dd/yyyy):</b>	07/01/2006
<b>MIL Order #39 (China RoHS):</b>	Yes

#### Suitability

<b>Suitability - Indoor:</b>	Yes
------------------------------	-----

### Transmission Characteristics (Connectivity)

### Notes (Overall)

**Notes:** For proper installation refer to the installation guide included with the product or visit our web site at <http://www.belden.com>

### Product Family

Part Numbers:

Description	Belden Part Number
MDVO Adapter Strip, 12-port, Empty, Black	AX100223
CAT5E HD-BIX Connector Module Strip, Universal Wiring 12-port. T568A/B	AX100224

## METRIC MEASUREMENT VERSION

### AX104615 Faceplates and Panels - KeyConnect Multi-User Adapter 12-Port

CAT5E HD-110 Connector Module Strip, Universal Wiring 12-port, T568B/A	AX100494
KeyConnect Adapter Strip, 12-port, Empty, black	AX104615

#### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX104615	1 EA	0.389 LB			KEYCONNECT ADAPTER STRIP,

Revision Number: 0    Revision Date: 11-11-2011

© 2017 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.