



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## 2-Port Compact USB KVM Switch with Audio and Cable

MODEL NUMBER: **B004-VUA2-K-R**



### Description

The B004-VUA2-K-R is a 2-port Compact USB KVM Switch with optional audio and microphone switching function. It allows you to access, control, boot and reboot two USB-enabled computers from a single console (keyboard, monitor and mouse). The independent audio/mic switching function allows an uninterrupted audio experience - you can continue listening to audio even when you switch to the other computer.

It includes innovative, easy-to-use KVM Switcher Software for Windows and Macintosh platforms. A small client application facilitates your KVM switching operations such as computer selection, hot key sequence programming, auto-scanning, auto-scan delay time programming, independent or simultaneous audio/computer switching and more. Compatible with all major operating systems.

### Features

- Fast, easy switching via keyboard hot keys, push buttons or software
- Plug-and-play setup - no software required
- Hot-swap capability allows easy addition or removal of computers without powering down the switch or other computers
- Speaker and microphone connections allow sharing of audio components between systems (standard 3.5 mm audio connections)
- Independent audio switching allows you to listen to audio from one computer while switching to the other computer
- Supports video resolutions up to 2048 x 1536 (standard 15-pin VGA connectors)
- Supports Microsoft® IntelliMouse® and the scrolling wheel on most mice]
- Compact design saves desk space
- Does not require an AC adapter

### Highlights

- Fast, easy switching via keyboard hot keys, push buttons or software (not required)
- PC and Mac compatible
- Allows sharing of audio components between systems; listen to music from one computer while switching to the other computer
- Compact design saves desk space
- No AC adapter required
- (x2) 6ft USB KVM Cable kits and (x2) 6ft 3.5mm Audio Cable kits included
- Compatible with all major operating systems

### System Requirements

- Console: VGA, SVGA or Multisync Monitor, USB Keyboard and USB Mouse
- Computers: VGA, SVGA or Multisync Monitor Port and USB Port
- Audio (Optional): Speakers with standard 3.5 mm Connectors and a computer with 3.5mm ports
- Compatible with all major operating systems

### Package Includes

- Compact 2-port USB KVM Switch with Audio
- (2) 6ft USB KVM Cable Kits and (2) 6ft 3.5mm Audio Cable Kits
- CD-ROM with KVM Switcher





- Compatible with all major operating systems
- Includes two, 6ft Cable Kits

- Software
- Owner's Manual with Warranty Information

## Specifications

| OVERVIEW                          |  |
|-----------------------------------|--|
| UPC Code                          | 037332140043                               |
| Users                             | 1  |
| Console                           | No   |
| Max CPU                           | 2  |
| Technology                        | USB (all versions); VGA/SVGA; Stereo Audio |
| INPUT                             |  |
| Bus Powered                       | Yes  |
| USER INTERFACE, ALERTS & CONTROLS |  |
| LED Indicators                    | Green (Selected PC)                        |
| PHYSICAL                          |  |
| Shipping Dimensions (hwd / in.)   | 3.00 x 7.90 x 7.80                         |
| Shipping Dimensions (hwd / cm)    | 7.62 x 20.07 x 19.81                       |
| Shipping Weight (lbs.)            | 1.80                                       |
| Shipping Weight (kg)              | 0.82                                       |
| Unit Packaging Type               | Box  |
| Unit Dimensions (hwd / in.)       | 1.3 x 4 x 2.6                              |
| Unit Weight (lbs.)                | 0.22                                       |
| Unit Weight (kg)                  | 0.10                                       |
| Material of Construction          | ABS  |
| Color                             | Black                                      |
| ENVIRONMENTAL                     |  |
| Operating Temperature Range       | 32 to 104 F (0 to 40 C)                    |
| Storage Temperature Range         | -4 to 140 F (-20 to 60 C)                  |
| Relative Humidity                 | 0%-90% RH, Non-Condensing                  |
| BTUs                              | 1.7 BTU/Hr                                 |



|                                       |                                |
|---------------------------------------|--------------------------------|
| Power Consumption (Watts)             | 0.5                            |
| <b>COMMUNICATIONS</b>                 |                                |
| IP Remote Access                      | No                             |
| <b>CONNECTIONS</b>                    |                                |
| Ports                                 | 2                              |
| PC/Server Connections                 | USB; VGA                       |
| Side A - Connector 1                  | (2) HD15 (FEMALE)              |
| Side B - Connector 1                  | HD15 (FEMALE)                  |
| Side B - Connector 2                  | (2) USB A (FEMALE)             |
| Side B - Connector 3                  | (2) 3.5MM (FEMALE)             |
| Computer Keyboard and Mouse Interface | PS/2                           |
| Computer Monitor Interface            | VGA                            |
| Console Keyboard and Mouse Interface  | USB                            |
| Console Monitor Interface             | VGA                            |
| Connector Plating                     | Nickel                         |
| <b>FEATURES &amp; SPECIFICATIONS</b>  |                                |
| Port Selection                        | Pushbutton; Hotkey; Software   |
| Max Supported Video Resolution        | 2048 x 1536 @60Hz              |
| USB Specification                     | USB 1.1 (up to 12 Mbps)        |
| Audio Specification                   | Stereo Audio                   |
| <b>CERTIFICATIONS</b>                 |                                |
| Certifications                        | Tested to CE, FCC, RoHS, REACH |
| <b>WARRANTY</b>                       |                                |
| Product Warranty Period (Worldwide)   | 3-year limited warranty        |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>