



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



TAA-Compliant NetDirector 16-Port Cat5 KVM Switch 1U Rack-Mount

MODEL NUMBER: **B064-016**



Description

Tripp Lite's 16-Port NetDirector 1U Rackmount Cat5 KVM Switch, is the next generation of our cost-effective, feature rich, KVM switches. It's sleek, 1U design and compact size, features RJ45 connection ports that utilize inexpensive Cat5 patch cables, reducing the amount of cable clutter normally found with traditional KVM cabling. Easily switch between CPU's with Push Buttons, Hot-Key commands, or built-in On Screen Display (OSD) menu function. Daisy-chaining allows connection to up to 512 computers. Compatible with PS/2 and USB computers, VGA, SVGA, or XGA monitors, as well as the following OS platforms: DOS, Windows (all versions), LINUX, UNIX, HP UX, and SUN. Supports both PS/2 and USB Mouse and Keyboards into the switch. Constructed of heavy-duty steel housing. Server Interface Units required at the server side to convert patch cables back to VGA and USB and/or PS/2 connections.

Features

- Directly connect up to 16 computers; or, expand the number of connected computers to up to 512 by daisy-chaining up to 31 additional levels of B064-016 KVM Switches
- Control multiple computers from a single keyboard, monitor and mouse. Both USB and PS/2 keyboards and mice are supported
- RJ45 connectors and Cat5e/6 cable allow for a more efficient installation
- 1U Rackmountable...Rackmount hardware Included
- Quickly access connected computers via On Screen Display (OSD), Push-button or Hotkey commands
- Firmware upgradeable using the included RJ11 to DB9 firmware upgrade cable
- Multi-language support; OSD can be displayed in English, German, Japanese, Traditional Chinese or Simplified Chinese
- Compatible with Windows, Mac, Linux, UNIX, Novell, Sun and DOS operating systems. Supports video resolutions up to 1600 x 1200 (60Hz) at 131 ft. (40 m.), or up to 1280 x 1024 (75Hz) at 164 ft. (50 m.)

Highlights

- 16 RJ45 Ports utilize inexpensive Cat5 patch cables
- Expandable - control up to 512 servers from a single station
- USB and PS/2 keyboards and mice are supported
- Quickly access connected computers via On Screen Display (OSD), Push-button or Hotkey commands
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

System Requirements

Compatible with Windows, Mac, Linux, UNIX, Novell, Sun and DOS operating systems

KVM INPUT

- A monitor with a VGA (HD15) input that is capable of supporting the highest video resolution that you will be using on the connected computers
- A USB or PS/2 mouse
- A USB or PS/2 keyboard

CONNECTED COMPUTERS

- A VGA (HD15) input
- A USB A Female port, or two PS/2 keyboard/mouse ports

Package Includes

- B064-016 KVM Switch
- Rackmount Hardware
- RJ11 to DB9 Firmware Upgrade



- Two-level password security; add up to 1 Administrator and 10 User accounts
- Use Server Interface Units B055-001-PS2 or B055-001-
- 100-240V, 50/60Hz, 1A
- Power Consumption: 120V (6.7W), 230V (7.3W)
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- Constructed of heavy-duty steel housing

Cable

- C13 to 5-15P Power Cord
- Grounding Wire
- Foot Pads
- Owner's Manual CD

Specifications

OVERVIEW	
UPC Code	037332159199
Users	1
Max CPU	512
PHYSICAL	
Shipping Dimensions (hwd / in.)	9.000 x 4.600 x 21.500
Shipping Dimensions (hwd / cm)	22.86 x 11.68 x 54.61
Shipping Weight (lbs.)	8.1000
Shipping Weight (kg)	3.67
Unit Dimensions (hwd / in.)	1.7 x 17 x 6
Unit Dimensions (hwd / cm)	4.32 x 43.18 x 15.24
Unit Weight (lbs.)	6.1
Unit Weight (kg)	2.77
Color	Black
ENVIRONMENTAL	
Storage Temperature Range	-20 to 60 C (-4 to 140 F)
Operating Temperature	0 to 40 C (32 to 104 F)
COMMUNICATIONS	
Port Control	Push Buttons, Hotkeys, OSD
IP Remote Access	No
CONNECTIONS	
Ports	16
PC/Server Connections	VGA; USB; PS/2
Local Console Ports - Port 3	2 x USB A Female



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

FEATURES & SPECIFICATIONS	
Autoscan (Y,N)	Y
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>