



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## 16-Port Serial Console/Terminal Server

MODEL NUMBER: **B096-016**



### Description

Tripp Lite's B096-016 is the most advanced console / terminal server platform available today. In a secure 1U rackmountable appliance, it offers an in-band and out-of-band management solution for serial console ports, servers, virtual servers, service processors, UPS & PDU's, environmental monitoring and more. This 16 port serial console / terminal server enables system administrators to securely access and control their data centers and networks from anywhere in the world. Supports 3G cellular out-of-band access. The USB port on the console server is compatible with both Multitech MT9234MU-CDC-XR and US RoboticsUSR5637 USB modems. This enterprise level unit is equipped with a built in modem, dual Ethernet, dual AC power, 16GB Internal USB flash and runs on Linux for scalability and reduced downtime.

The B096-016 offers advanced software features that surpass the requirements of even the most demanding applications. These features include Network UPS Tools for UPS monitoring, PowerMan for integrated PDU and RPC functions with in session hotkey support, Pattern match alerting, Open access to the Linux shell for scripting, heartbeat monitoring with automatic failover, Cisco pinouts and much more. Available in 16 and 48 port models, the B096 family of Console Servers are the perfect fit for in or out of band access to vital IT assets.

Made in the USA. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

### Features

- Built in modem for out-of-band dial-in access
- Configured to use standard Cat5e/6 patch cable when connecting to Cisco devices
- Tripp Lite's console servers all use an embedded FIPS 140-2 OpenSSL cryptographic module that has been validated to meet the FIPS 140-2 standards and has received Certificate #1051.
- When using SSH, HTTPS or SDT Connector to connect to any service on the console server while running in FIPS mode, they will be utilizing the embedded FIPS compliant module. In order to connect using any of the protocols, you must use a cryptographic algorithm that is FIPS approved or it will fail.
- Supports 3G cellular out-of-band access. The USB port on the console server is compatible with both Multitech MT9234MU-CDC-XR and US Robotics USR5637 USB modems.
- 16GB local FTP/TFTP storage for device configuration files
- IPsec VPN support

### Highlights

- Dual Ethernet, Dual Power Supply, and Built-in Modem
- Secure In-band and Out-of-band access for a Host of Equipment
- Supports 3G cellular out-of-band access
- Features 16GB Internal USB Flash
- 1U rackmountable
- Configured to use standard Cat5e/6 patch cable when connecting to Cisco devices
- Validated to meet FIPS 140-2 standards
- Manage all equipment in the rack: Servers, UPS, Routers, Switches, Firewalls, etc
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- Made in the USA

### Package Includes

- B096-016, 16-Port Serial Console / Terminal Server
- Rackmount hardware
- 2 x 6ft, Cat5e Patch cables
- 1 x DB9F - RJ45 Crossover Adapter
- 1 x DB9F - RJ45 Straight-Through Adapter
- 2 x 6ft, 5-15P to C13 Power cable
- CD with Manual
- Quick Start Guides





- Secure Shell (SSH V2)
- TACACS+ , RADIUS, LDAP, and Kerberos authentication
- PAP/CHAP authentication (dial up)
- Local authentication
- System event syslog
- SSH port and IP forwarding support
- IP packet filtering
- Break over SSH support
- Port triggers with SMNP and email alerts
- Offline data logging (Syslog, NFS, CIFS)
- Online data buffering and logging
- Multiple users per port (with port sniffing)
- Telnet/SSH/Raw TCP connect
- RFC 2217 - Port Redirection
- Integrated AJAX serial console and system terminal via web interface
- Native IPMI 1.5 and 2.0 (RMCP/RMCP+) support for BMC and service processor access and control
- Service processor access (IPMI, ILO, LOM and more)
- Access to KVM built in to service processors (DRAC, RSA)
- Limit user access by LAN device and SDT service for that device
- Port triggers with SMNP and email alerts for all tunnel traffic
- Each gateway can port forward to an unlimited number of locally networked hosts (computers, routers)
- Embedded DHCP server for management LAN devices
- Network UPS Tools for UPS Monitoring and Management
- PowerMan for PDU and RPC Management
- Command Line interface (Linux Shell)
- NAGIOS distributed monitoring
- Out-of-band (dial-up modem access) included - V.92 Serial Data/Fax Embedded Modem 3.3V Model, 14.4K Fax
- Linux with source code access
- Constructed of heavy-duty steel housing
- 1U rackmount

## Specifications

OVERVIEW	
UPC Code	037332148902
Multi-User	Yes
Technology	Modem; Serial (RS232)



<b>INPUT</b>	
Nominal Input Voltage(s) Supported	100V AC; 110V AC; 115V AC; 120V AC; 127V AC; 140V AC; 200V AC; 208V AC; 220V AC; 230V AC; 240V AC
Maximum Input Amps	0.8
Input Connection Type	2 x IEC-320-C14, Auto-Switching 100-240VAC
Input Frequency	50/60Hz
Input Current	120V (0.11A) / 230V (0.06A)
<b>PHYSICAL</b>	
Shipping Dimensions (hwd / in.)	3.40 x 19.30 x 16.10
Shipping Dimensions (hwd / cm)	8.64 x 49.02 x 40.89
Shipping Weight (lbs.)	11.00
Shipping Weight (kg)	4.99
Unit Dimensions (hwd / in.)	1.75 x 17.40 x 12.50
Unit Dimensions (hwd / cm)	4.445 x 44.2 x 31.75
Unit Weight (lbs.)	8.20
Unit Weight (kg)	3.72
Color	Black
<b>ENVIRONMENTAL</b>	
Storage Temperature Range	Non operating storage temperature: -30C to +60C (-20F to +140F)
Relative Humidity	Humidity: 5% to 90%
Operating Temperature	Ambient operating temperature: 5C to 50C (41F to 122F)
BTUs	120V: 52 BTU per hour
Power Consumption (Watts)	120V: 15 Watts
<b>COMMUNICATIONS</b>	
IP Remote Access	Yes
<b>CONNECTIONS</b>	
Ports	16
<b>CERTIFICATIONS</b>	
Approvals	FCC Part 15 A, UL 1950, CE (EN55022 A, EN55024, EN60950), TUV, C-Tick
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	4-year limited warranty



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>