



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



HDMI over Cat5/Cat6 Extender Kit, Power over Cable, 1080p @ 60 Hz, TAA

MODEL NUMBER: **B126-1P1M-U-POC**



Transmitter and receiver extend an HDMI signal via Cat5e/6/6a cable to a projector, monitor or TV up to 100 ft. away. Recommended for digital signs, classrooms, churches, offices and retail settings.

Description

The B126-1P1M-U-POC HDMI over Cat5/Cat6 Extender Kit includes a transmitter and a low-profile receiver that work in tandem to extend an HDMI audio/video signal to a projector, monitor or television. The kit is recommended for digital signs, trade shows, classrooms, churches, offices, retail settings and other applications where the source is located farther than conventional cables allow.

HDMI cable (see Tripp Lite's P568-Series) connects the audio/video source, such as a Blu-ray™ player, and optional local display to the transmitter's HDMI ports. Cat5e/6/6a cable connects the transmitter to the receiver's RJ45 port (for best results, use 24 AWG solid-wire Cat6 cable, such as Tripp Lite's N202-Series). The receiver plugs directly into the display's HDMI input port. Built-in PoC technology powers the receiver over Cat5e/6/6a cable, so no external power supply on the display side is needed.

The B126-1P1M-U-POC can extend a high-definition 1080p (at 60 Hz) signal up to 50 feet and a 1080i signal up to 100 feet. In addition to crystal-clear video, the B126-1P1M-U-POC delivers full, rich audio up to 7.1-channel surround sound (multi-channel or PCM) and supports 3D and HDCP standards. Easy to set up with no software or drivers to install. Complies with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

Extends a High-Definition HDMI Audio/Video Signal

- Transmitter extends HDMI A/V signal to low-profile receiver
- Recommended for digital signs, trade shows, classrooms, churches, offices, retail settings and other HDMI A/V applications

Highlights

- Built-in Power over Cable (PoC) technology powers the receiver
- Supports high-definition video resolutions up to 1080p (@ 60 Hz)
- Supports 7.1-channel surround sound audio
- HDCP and 3D compliant
- Plug-and-play operation with no software or drivers required

System Requirements

- Source with HDMI and USB ports (if source has no USB port, a USB wall charger can be used)
- Display with HDMI port

Package Includes

- Transmitter unit
- Receiver unit
- USB Micro-B cable, 1 ft.
- USB Micro-B cable, 3 ft.
- Owner's manual



- Extends a 1080p (@ 60 Hz) signal up to 50 ft. from source
- Extends a 1080i signal up to 100 ft. from source
- Supports 7.1-channel surround sound (multi-channel or PCM) audio
- HDCP and 3D compliant

Easy to Set Up and Use

- Built-in Power over Cable (PoC) technology powers the receiver
- Transmitter and receiver connect with Cat5e/6/6a cable (for best results, use Tripp Lite's N202-Series)
- Transmitter connects to source and optional local display using HDMI cable, such as Tripp Lite's P568-Series
- LEDs indicate when units are receiving power or an HDMI signal
- Plug-and-play operation with no software or drivers required

TAA-Compliant

- Complies with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
UPC Code	037332201003
Technology	HDMI (All types)
PHYSICAL	
Shipping Dimensions (hwd / in.)	1.730 x 7.870 x 5.590
Shipping Dimensions (hwd / cm)	4.39 x 19.99 x 14.20
Shipping Weight (lbs.)	0.4400
Shipping Weight (kg)	0.20
Color	Black
CONNECTIONS	
Ports	2
Side A - Connector 1	HDMI (MALE)
Side B - Connector 1	HDMI (MALE)
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>