



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Never stop thinking

[Home](#) > [Microcontrollers](#) > [Development Tools, Software and Training](#) > [TriCore® Development Tools and Software](#) > [StarterKits and Evaluation Boards](#) > **SK TC116x-Series Starter Kit**

SK TC116x-Series Starter Kit

MCU Derivates:

- SAF-TC1161-128F66HL
- SAF-TC1162-128F66HL
- SAF-TC1163-128F80HL
- SAF-TC1164-128F80HL
- SAF-TC1165-192F80HL
- SAF-TC1166-192F80HL

CPU Clock: 66/80 MHz

On-Chip Memory:

- 1.0/1.5 MByte embedded program flash with ECC,
- 16/32 KByte data flash for scalable EEPROM emulation,
- 32/40/56 KByte on-chip SRAM,
- 8 KByte instruction cache.
- 8/16 Kbyte code scratchpad memory

Interfaces

- DB9 for RS232-0,
- BERG10 for RS232-1,
- two BERG10 for CAN-0/1 with Transceiver,
- BERG16 for OCDS1,
- SAMTEC QSH-030-01-F-D-A for OCDS2,
- DB25 On Board Wiggler for OCDS1,
- three four 80-pin connectors (male) with all I/O signals,
- three four 80-pin connectors (female) with all I/O signals.

Includings:

- TC116x User manual (pdf),
- TriCore Architecture manual (pdf),
- TriBoard manual (pdf),
- Tools: Compiler, Debugger, Operating System from Infineon Tool Partners(Evaluation versions)
- Cable,
- 1 Extension Board,
- Power plug

Order Nr.: B158-H8690-X-0-7600