

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







### Common Mode Chokes For ADSL and VDSL





RoHS peak reflow solder temperature rating 245°C

RoHS peak wave solder temperature rating 260°C


For use in XDSL interfaces

Effective reduction of C.M. noise caused by AM broadcast or ham radio

Isolation 1500V line to line

Electrical Specifications @ 25°C – Operating Temperature –40°C to +85°C						
	<b>C.M. Attentuation</b> (dB TYP)					
RoHS Compliant Part No.	@ 500kHz	@ 1kHz	@ 10kHz	<b>Isolation Voltage</b> (Vrms)	Mounting	
B4001NL	45	49	35	1500	THT	
B4003NL	45	49	35	1500	SMT	
BX4053NL	45	49	35	150	SM	

Notes: Surge Voltage Capability - Metallic: 800Vpeak 10/560sec. Long.: 2400Vpeak 10/700sec. BX4053NL is a dual choke. Please add the suffix "T" for Tape & Reel orders (i.e. B4003NL becomes B4003NLT).




pulseelectronics.com


# Common Mode Chokes For ADSL and VDSL

#### Mechanicals (continued)

#### **Schematics**

#### **B4003NL**







Weight	1.0grams
Tape & Reel	425/reel
Tube	50/tube

## **Dimensions:** $\frac{\text{Inches}}{\text{mm}}$

Unless otherwise specified, all tolerances are  $\pm \frac{.010}{0.25}$ 

#### **BX4053NL**





Weight	2.1grams
Tape & Reel	400/reel
Tube	50/tube

**Dimensions:**  $\frac{\text{Inches}}{\text{mm}}$ 

Unless otherwise specified, all tolerances are  $\pm \frac{.010}{0.25}$ 

#### For More Information

Pulse Worldwide Headquarters 12220 World Trade Drive San Diego, CA 92128 U.S.A.

Tel: 858 674 8100 Tel: 49 7032 78060 Fax: 858 674 8262 Fax: 49 7032 7806 135

berg

Germany

## Pulse EuropePulse China HeadquartersEinsteinstrasse 1B402, Shenzhen Academy ofD-71083 Herren-Aerospace Technol-

Aerospace Technology Bldg.
10th Kejinan Road
High-Tech Zone
Nanshan District
Shenzen, PR China
518057
Tel: 86 755 33966678

Fax: 86 755 33966700

#### **Pulse North China** Room 2704/2705

Super Ocean Finance Ctr. 2067 Yan An Road West Shanghai 200336 China Tel: 86 21 62787060 Fax: 86 2162786973

#### **Pulse South Asia**

135 Joo Seng Road #03-02 PM Industrial Bldg. Singapore 368363

Tel: 65 6287 8998 Fax: 65 6287 8998

#### **Pulse North Asia**

3F, No. 198 Zhongyuan Road Zhongli City Taoyuan County 320 Taiwan R. O. C. Tel: 886 3 4356768 Fax: 886 3 4356823 (Pulse) Fax: 886 3 4356820 (FRE)

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2012. Pulse Electronics, Inc. All rights reserved.

