



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





**EPCOS**

Sample Kit 2009



# Ring Core Chokes for Power Lines

Series B82721

[www.epcos.com](http://www.epcos.com)


## Series B82721

$L_R$	mH	<b>39</b>	<b>27</b>	<b>27</b>	<b>10</b>	<b>6.8</b>	<b>3.3</b>	<b>1</b>	<b>0.7</b>	<b>0.4</b>	<b>0.2</b>
$I_R$	A	0.4	0.5	0.4	0.7	1.2	1.5	2.0	4.0	3.6	6.0
$L_{\text{stray, typ}}$	$\mu\text{H}$	450	290	300	110	80	37	13	7	6	2.5
$R_{\text{typ}}$	$\text{m}\Omega$	2000	1100	1700	550	280	180	80	30	35	15
$T_R$	$^{\circ}\text{C}$	40	60	40	60	40	40	40	40	40	40
UL/VEDE		yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Ordering code	B82721	A/K2401N020	K2501N022	A/K2401N021	A/K2701N020	A/K2122N020	A/K2152N001	A/K2202N001	A/K2402N020	A/K2362N001	K2602N020


- Rated current:  $I_R$  at 50 Hz and  $T_R$
- Rated voltage: 250 V AC (50/60 Hz)
- Higher inductance or intermediate values possible upon request
- Approx. 1% stray inductance for symmetrical interference suppression
- Higher rated current  $I_R$  available with series B82722 ... B82726
- Vertical version with lead spacing 5 x 10 mm available (B82721J\*)

## Dimensional drawings and pin configurations


### Vertical version (B82721J)



### Vertical version (B82721K)




### Horizontal version (B82721A)



Tolerances to ISO 2768-C unless otherwise noted. Dimensions in mm.

## Current derating $I_{op}/I_R$ versus temperature T



## Impedance $|Z|$ versus frequency f

