



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com




Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



EPCOS Sample Kit 2015

SMT Current Sense Transformers




EE 5.0 Core Series – B82801B




Current Sense Transformers - EE 5.0 Core (SMT)

Turns ratio	Np : Ns	1 : 20	1 : 30	1 : 40	1 : 50	1 : 60
L _{min}	μH	80	180	320	500	720
Voltage-time product	V*μs	10.0	15.0	20.0	25.0	30.0
Ordering code	B82801	B0803A020	B0184A030	B0324A040	B0504A050	B0724A060
Turns ratio	Np : Ns	1 : 70	1 : 100	1 : 125	1 : 200	
L _{min}	μH	980	2000	3000	8000	
Voltage-time product	V*μs	35.0	50.0	62.5	100.0	
Ordering code	B82801	B0984A070	B0205A100	B0305A125	B0925A200	

- All values measured at +25 °C ambient temperature
- Frequency range: 50 kHz ... 1 MHz
- Sensed current: The max. primary current of 20 A causes approx. +40 °C temperature rise
- Operating temperature range: -40 °C ... +125 °C
- Tape and reel packing: 16 mm blister tape, 330 mm reel
- Packing units: 900 pcs./reel; 7200 pcs./carton




Recommended PCB layout




IND1143-FE


1:20




1:30




1:40




1:50




1:60




1:70




1:100



1:125



1:200



Important information: It is incumbent on the customer to check and decide whether a product is suitable for use in a particular application. Our products are described in detail in our data sheets. Our *Important notes* and the product-specific *Cautions and warnings* must be observed. All relevant information is available through our sales offices.