

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









| - 1 | 2 | 100 405 | NEGATIVE CONTACT TOO CTAINIEGO CTEEL MICHELE DETD | 1 4 | | | | | | |
|------------------------------------|---|-----------|--|-----------------|------------------------|-----------|----------------|----------|------------------|--|
| | | ABG-195 | NEGATIVE CONTACT, 302 STAINLESS STEEL, NICKLE PLTD. | 1 | decimal | | | Scale | Drawn By B.S. | |
| | 3 | ABG-196-1 | RIGHT NEG./POS. CONTACT, 302 STAINLESS STEEL, NICKLE PLTD. | 1 | | | | | | |
| İ | 4 | ABG-201 | ASSY. NEG./POS. CONTACT, 302 STAINLESS STEEL, NICKLE PLTD. | 1 | ±.5 (.020) | | | | Approved By T.B. | |
| f | 5 | ABG-198 | BLACK POLYPROPYLENE HOLDER, UL94-HB | 1 | Fractional | Title | | | | |
| SPECIFICATION: | | | | \pm .8 (.030) | THREE "AA" CELL SPRING | | | S HOLDER | | |
| - 1 | 1. HOUSING: BLACK POLYPROPYLENE, PP-1040 FLAMMABILITY RATING: -UL94-HB, UL FILE NO. E216959 | | | | ` , | | | | | |
| | | | | | Angular | Date | Drawing Number | | | |
| TEMPERATURE RANGE: -10°C to +100°C | | | | ± 3° | 10/28/06 | BA3AAPC | | | | |
| L | | | | | | 10/.50/00 | | | | |