

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China











Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

BAS516

Features

- Lead Free Finish/Rohs Compliant ("P"Suffix designates RoHS Compliant. See ordering information)
- Ultra-Small Surface Mount Package
- High Switching Speed
- For General Purpose Switching Applications
- Marking: 61
- Halogen free available upon request by adding suffix "-HF"
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1


Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C

Electrical Characteristics @ 25°C Unless Otherwise Specified

DC Reverse Voltage	V_{R}	75V	
Forward Current	I _F	250mA	
Repetitive Forward	I_{FRM}	500mA	
Current			
Maximum		715mV	$I_F = 1mA$
Instantaneous	V_{F}	855mV	$I_F = 10mA;$
Forward Voltage		1000mV	$I_F = 50 \text{mA}$
		1250mV	$I_F = 150 \text{mA}$
Maximum DC		0.03μΑ	V _R =25Volts
Reverse Current At	I _R	•	
Rated DC Blocking		1μA	V _R =75Volts
Voltage			
Typical Diode	C_D	1pF	Measured at
Capacitance			1.0MHz, V _R =0V
Junction temperature	Tj	150℃	
Reverse Recovery	T_{rr}	4nS	$I_F=I_R=10$ mAdc,
Time			$V_R = 0V$
			R _L =100Ω

Switching Diode



DIMENSIONS						
	INCHES		ММ			
DIM	MIN	MAX	MIN	MAX	NOTE	
Α	.059	.067	1.50	1.70		
В	.043	.051	1.10	1.30		
С	.030	.033	0.75	0.85		
D	.001	.003	0.01	0.07		
Е	.010	.014	0.25	0.35		
F	.003	.006	0.08	0.15		
G	.020	.028	0.50	0.70		
Н	.020	.031	0.51	0.77		
Suggested Solder Pad Layout						
1.1mm —						



BAS516








Fig.2 Maximum permissible continuous forward current as a function of soldering point temperature.



- (1) $T_i = 150$ °C; typical values.
- (2) $T_i = 25$ °C; typical values.
- (3) $T_i = 25 \,^{\circ}\text{C}$; maximum values.

Fig.3 Forward current as a function of forward voltage.



Based on square wave currents; $T_i = 25$ °C prior to surge.

Fig.4 Maximum permissible non-repetitive peak forward current as a function of pulse duration.



Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel: 8Kpcs/Reel

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.