# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



### Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









#### No hassle warranty

No waiting.

No shipping charges.

Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace

NO HASSL

(note: \$500 MSLP limit)

it, on the spot.

## **BAT-500** Battery Capacity Tester

Quick and accurate battery testing without taking the batteries off line. Comparator function with pass/fail indication speeds testing of batteries up to 500Ah. Typical applications include but are not limited to power back-up and UPS systems.

- Tests battery capacity to calculate its true life
- Works with most batteries, compact storage batteries, alkaline and lead-acid up to 500Ah
- Resistance measurement up to 40 ohms, and voltage up to 40V
- Tests are performed without shutting down a battery
- Simultaneously measure battery resistance and voltage
- Comparator function to quickly access conditions as Pass, Warning, or Fail
- 99 memory locations to store results with read function
- Compact and lightweight
- RS232 PC Interface to download testing results to a PC for trending/life cycle analysis





#### **BAT-500 Battery Capacity Tester**

#### Data Sheet

#### **Specifications**

Specifications	
Battery Types Tested	Compact storage batteries, Alkaline, Nickel-Metal Hydride (NiMH), Nickel-Cadmium (NiCd),
	Lithium-ion (Li-ion) and lead-acid batteries
Battery Capacity	0 to 500AH
Impedance Measurement Range	40mΩ, 400mΩ, 4Ω, 40Ω
Resolution	10μ $\Omega$ , 100μ $\Omega$ , 1m $\Omega$ , 10m $\Omega$
Accuracy	±(1%reading ±10digits)
Open Circuit Voltage	3.5Vpp max
Measurement Current	25mA approx., 2.5mA approx., 250μA approx., 25μA approx
Measuring current Frequency	1KHz ±10%
Voltage Measurement Range	4V, 40V
Resolution	1mV, 10mV
Accuracy	±(0.1% rdg ±6 digits)
Data Memory	500 data sets
Continuous Data Memory	9600 data sets (only use PC download)
Comparator	
Setting	Resistance upper and lower limits and voltage throughold point
Number Of Comparator Settings	99 sets of values
Operating Environment	0°C to 40°C (32°F to 104°F) , 80%RH or less, non-condensing
Maximum Input Voltage	50 VDC
Power Supply or AC Adapter	Six size AA 1.5V
Battery Life	7 hours approx
Weight	Approx. 500g (1.1 lb) including batteries
Dimensions Approx	250(L) × 100(W) × 45(H)mm (9.8 x 39.4 x 1.8 in)
Accessories	Instruction manual, Batteries, Test probe, Software, RS232 cable

#### Amprobe® Test Tools

website: www.Amprobe.com email: info@amprobe.com Everett, WA 98203 Tel: 877-AMPROBE

#### **Amprobe® Test Tools Europe**

In den Engematten 14 79286 Glottertal, Germany Tel.: +49 (0) 7684 8009 - 0

©2009 Amprobe Test Tools. All rights reserved. 7/2009 3520379 Rev A