



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



USB to RS-485 Mini-Converters

485USB9F-2W & 485USB9F-4W

B+B SMARTWORX

Powered by

ADVANTECH

www.advantech-bb.com



PRODUCT FEATURES

- Connect RS-485 devices to your USB port
- Perfect for field service applications
- Small – fits easily into any laptop bag
- USB port powered
- USB 2.0 (12 Mbps) compatible
- RS-485 data rates up to 921.6 kbps
- Supports Windows XP, 7 (32/64 bit), 8 (32/64 bit), 8.1 (32/64 bit), 10 (32/64bit)

Universal Serial Bus (USB) has become the connectivity workhorse of today's PCs, replacing the familiar serial port. However, many commercial and industrial devices still use the RS-485 interface. To connect these devices to modern PCs, you need a simple and reliable conversion solution. The 485USB9F-2W and 485USB9F-4W offer this solution in a space saving, USB port powered package.

Simply install the drivers and plug the converter into an available USB port on your computer or USB hub. The device will show up as an additional COM port in the Windows Device Manager which is fully compatible with your Windows applications. Choose the 485USB9F-2W for RS-485 2-wire applications or the 485USB9F-4W for RS-485 4-wire applications. Locked serial number versions are also available. A one meter USB cable is included.

ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION
485USB9F-2W	USB to RS-485 2-Wire Converter
485USB9F-4W	USB to RS-485 4-Wire Converter
485USB9F-2W-LS	USB to RS-485 2-Wire Converter (Locked Serial Number)
485USB9F-4W-LS	USB to RS-485 4-Wire Converter (Locked Serial Number)

ACCESSORIES

USBAMB-3F - 3 ft. USB Cable (one included)



IN THE FIELD

Monitoring Laboratory Equipment

Industry: Industrial Automation
Product: USB Miniature Converter

Locked Serial Numbers Explained

We configure our single-port USB to serial converters in two ways. In standard format, each product has a unique serial number. "Locked serial" format uses the same serial number that is associated with a model type.

If your converter will always be used with the same computer, the standard serialized model is all you need. If the converter is shared among several computers, like field service laptops, the locked serial number model lets you plug and play without having to worry about matching the two.

DESCRIPTION	SERIALIZED	LOCKED SERIAL NUMBER
Every unit is assigned a unique COM port	✓	-
Same type model numbers shares the same COM port	-	✓
Ideal applications	Fixed Locations	Field Service

When ordering Locked Serial Number versions, add a "-LS" to the item number. Serialized and Locked Serial Number versions available for the same price.

All product specifications are subject to change without notice.
485USB9F-2Wx_485USB9F-4Wx_1017ds

USB to RS-485 Mini-Converters

485USB9F-2W & 485USB9F-4W




SPECIFICATIONS

SERIAL TECHNOLOGY	
RS-485 2-Wire	Data A(-), Data B(+), Ground
RS-485 4-Wire	TDA(-), TDB(+), RDA(-), RDB(+), Ground
Connector	DB9 Female
Data Rate	Up to 921.6 Kbps
USB TECHNOLOGY	
Connector	USB Type B Female
Standard	2.0 (Backward Compatible)
Data Rate	12 Mbps
POWER	
Source	USB Port
Input Voltage	5 VDC
Consumption	~ 0.5 W (Low power device, draws less than 100 mA)
SOFTWARE	
Driver CD	Windows XP, 7 (32/64 bit), 8 (32/64 bit), 8.1 (32/64), 10 (32/64)
MECHANICAL	
Dimensions	5.8 x 3.2 x 1.6 cm (2.3 x 1.3 x .6 in)
Enclosure	In-line mounted, plastic
Weight	0.23 lbs (104.3 g) with USB Cable
ENVIRONMENTAL	
Operating Temp	32 to 158°F (0 to 70 °C)
Storage Temp	-40 to 185 °F (-40 to 85 °C)
Op Humidity	0 to 95 % (Non-condensing)
MTBF 2-Wire	2130833 hours
MTBF 4-Wire	1869313 hours
MTBF Method	Parts Count Reliability Prediction
REGULATORY	
Approvals	FCC, CE

APPROVALS / CERTIFICATIONS		
EU	2014/30/EU	Electromagnetic Compatibility Directive
	2011/65/EU	Reduction of Hazardous Substances Directive
EMC	EN 55022:2010 + AC	Information Technology Equipment - Radio Disturbance Characteristics - Limits and Methods of Measurement
	EN 61000-6-1	Generic Immunity Standard for Residential, Commercial and Light-Industrial Environments
	EN 61000-4-2	Electro-Static Discharge (ESD) Immunity
	EN 61000-4-3	Radiated Field Immunity (RFI)
	EN 61000-4-4	Electrical Fast Transients (EFT) Burst Immunity
	EN 61000-4-5	Surge Immunity
	EN 61000-4-6	RF Conducted Immunity

PINOUT: DB9 FEMALE CONNECTOR



PIN	485USB9F-2W	485USB9F-4W
1	Not Used	Not Used
2	Data A(-)	RDA(-)
3	Data B(+)	TDB(+)
4	Ground	Ground
5	Not Used	Not Used
6	Ground	Ground
7	Data B(+)	RDB(+)
8	Data A(-)	TDA(-)
9	Not Used	Not Used

MECHANICAL DIAGRAM

