



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Ethernet-based, Modular Media Converter Chassis

MediaConverter/1

B+B SMARTWORX

Powered by

ADVANTECH

www.advantech-bb.com



PRODUCT FEATURES

- Supports Fast Ethernet and Gigabit Ethernet
- Supports “Mc” modules
- Table-top
- 1-slot chassis
- Internal AC power
- Modular, hot-swappable architecture reduces operational costs associated with product installation, upgrades and maintenance

The unmanaged B+B SmartWorx' MediaConverter/1 enables you to install compact, horizontal modules that support speeds of 10/100Mbps, 100Mbps or Gigabit. The one-slot chassis is one of four chassis that can provide a low-cost solution for segments in a network that require a copper to fiber conversion.

The module series available from B+B SmartWorx for this chassis are the McLIM, McLIM-TP-TX/FX and McGigabit.

The one-slot chassis has a reliable internal AC power supply. A country-specific power cord is shipped with each chassis

ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION
MediaConverter/1	
851-10901	1 Slot, AC Chassis

ACCESSORIES

895-39949 - Rackmount Shelf

All product specifications are subject to change without notice.
MediaConverter-1_4117ds

Ethernet-based, Modular Media Converter Chassis

MediaConverter/1



SPECIFICATIONS

TECHNICAL	
1-slot AC chassis to house the following modules: McLIM, McLIM 10/100, McGigabit	
MECHANICAL	
Dimensions	4.16H x 12.06W x 13.97D cm (1.64H x 4.75W x 5.5D in.)
Shipping Weight	0.9 kg (2 lbs)
POWER	
115/230 or 120-240 VAC, 50/60Hz, 0.3A/0.15A	

ENVIRONMENTAL	
Operating Temperature – DC Terminal Block	0° to +50° C (+32° to +122° F)
Storage Temperature	-25° to +70° C (13° to +158° F)
Operating Humidity	5% to 95% (non-condensing), 0 – 10000 ft. altitude
REGULATORY APPROVALS	
FCC Class A, UL/CUL, CE, CSA	

MECHANICAL DIAGRAM

units = inches

