



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Ethernet-based, Modular Media Converter Chassis

MediaConverter/8

B+B SMARTWORX

Powered by

ADVANTECH

www.advantech-bb.com



PRODUCT FEATURES

- Supports Ethernet, Fast Ethernet and Gigabit Ethernet
- Supports “Mc” modules
- Table-top and rack-mountable
- 8-slot chassis
- Internal AC power
- Modular, hot-swappable architecture reduces operational costs associated with product installation, upgrades and maintenance

The unmanaged B+B SmartWorx' MediaConverter/8 to install compact, horizontal modules that support speeds of 10/100Mbps, 100Mbps or gigabit. The eight slot chassis is one of four chassis that can provide a low-cost solution for segments in a network that require a copper to fiber conversion.

The modules available from B+B SmartWorx for this chassis are the McLIM, McLIM-TP-TX/FX and McGigabit.

The eight slot chassis has a reliable internal AC power supply, and a country-specific power cord is shipped with each chassis.

ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION
MediaConverter/8	
851-10908	8 Slot, AC Chassis

All product specifications are subject to change without notice.
MediaConverter-8_4117ds

Ethernet-based, Modular Media Converter Chassis

MediaConverter/8



SPECIFICATIONS

TECHNICAL

8-slot chassis to house the following modules:
McLIM, McLIM 10/100, McGigabit
Fits into a 19" Rack

MECHANICAL

Dimensions 4.54H x 44.19W x 12.7D cm
1.79H x 17.4W x 5.0D in
Shipping Weight 2.8 kg (6.25 lbs)

POWER

120/240 VAC, 50/60Hz, 1A/0.5A

ENVIRONMENTAL

Operating Temperature – DC Terminal Block	0° to +50° C (+32° to +122° F)
Storage Temperature	-25° to +70° C (13° to +158° F)
Operating Humidity	5% to 95% (non-condensing), 0 – 10000 ft. altitude

REGULATORY APPROVALS

FCC Class A, UL/CUL, CE, CSA

MECHANICAL DIAGRAM

units - inches

