



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



RS-232 Mini Tester

Model 9PMTT

B+B SMARTWORX

Powered by

ADVANTECH

www.advantech-bb.com



PRODUCT FEATURES

- Test for RS-232 data line or equipment failures
- Convenient LEDs for line status
- Can be permanently installed in-line

Which RS-232 data lines are active? Find out with this RS-232 mini tester. It makes troubleshooting easy by helping to check interface connections, equipment, cable problems or failures.

Model 9PMTT RS-232 mini tester is designed to connect with any RS-232 interface. The tester may be left in the line permanently. It is transparent to data transfer. Bright red or green LED signals clearly show which lines are active. The LEDs' color indicates Negative or Positive voltage (red meaning Negative; green meaning Positive).

ORDERING INFORMATION

MODEL NUMBER	RS-232	RS-232
9PMTT	DB9 Male	DB9 Female

ACCESSORIES

9SGF - DB9 Gender Reverser – Changes Male Port to Female (F to F)

9SGM - DB9 Gender Reverser – Changes Female Port to Male (M to M)

SPECIFICATIONS

SERIAL TECHNOLOGY	
RS-232	
Connectors	DB9 male DB9 female
Signals	TD, RD, RTS, CTS, DSR, CD, DTR
Installation	In-line
LEDS	
Line Status	TD, RD, RTS, CTS, DSR, CD, DTR RED = negative voltage (mark) GREEN = positive voltage (space)
POWER	
Power	Port-powered from RS-232 handshake lines
Source	DTR & RTS
MECHANICAL	
Dimensions	5.0 x 5.4 x 1.6 cm (2.0 x 2.14 x .63 in)
Enclosure	Plastic
Weight	63.5 grams (0.14 lbs)
APPROVALS/CERTIFICATIONS	
2011/65/EU	Reduction of Hazardous Substances Directive (RoHS)
2012/19/EU	Waste Electrical and Electronic Equipment (WEEE)

All product specifications are subject to change without notice.
9PMTT_2817ds