



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# Secure, Rugged Dual Band Module – Access Point / Client / Router

Model APMN-Q551

B+B SMARTWORX

Powered by

ADVANTECH

[www.advantech-bb.com](http://www.advantech-bb.com)



## PRODUCT FEATURES

- Quick time to market and reduced integration costs
- 802.11a/b/g/n Wi-Fi radio (2.4 GHz, 5 GHz)
- AirborneM2M Power Save firmware reduces power consumption and extends battery life in mobile devices
- Extended operating temperature range (-40 to +85°C) and environmental specifications
- AirborneM2M Speed Link roaming provides enhanced connection reliability
- AirborneM2M PortFlex capability enables any combination of communication ports (UART, SPI, GPIO, Ethernet and 802.11 interfaces)
- FCC Part 15 Class B Sub C Modular Approval minimizes regulatory requirements
- Backwards compatible with previous generations of AirborneM2M embedded modules

## AirborneM2M Embedded 802.11a/b/g/n Dual Band (2.4 GHz, 5 GHz) Access Point Module or Client

The AirborneM2M line of highly-integrated 802.11 wireless access point modules allow OEMs to Wi-Fi enable devices used in an array of machine-to-machine (M2M) applications. B+B SmartWorx delivers all the necessary RF technology networking stacks and advanced security features in a compact, single-board package, reducing integration costs for OEMs and providing for a quick time to market.

### Big Performance in Small and Ruggedized Package

The AirborneM2M series delivers the industry's most rugged, highly integrated, embedded wireless access point Wi-Fi module solution. AirborneM2M modules meet extended operating temperature and shock vibration specifications of the most demanding M2M applications.

Utilizing a 32-bit ARM9 processor and the high-performance Atheros AR6203 802.11 radio, the module delivers increased transmit power and receive sensitivity, contributing to superior range performance.

### SpeedLink™ Roaming

The AirborneM2M Speed Link roaming feature provides enhanced connection reliability, enabling OEM devices to roam freely within a wireless network without loss of data or connection.

### Flexible and Easy to Integrate

AirborneM2M incorporates support for both wireless access point and serial to Wi-Fi communications. Utilizing AirborneM2M Port Flex capability, OEMs may configure via software any combination of UART, SPI, Ethernet, GPIO and 802.11 interfaces. Each individual port can be independently configured. A development kit is also available to aid developers (sold separately).

### Future-proof

These AirborneM2M modules are footprint and pin-compatible with their predecessors. B+B SmartWorx' commitment to maintaining hardware and software compatibility assures OEMs of a simple, future-proof migration path even as wireless technology evolves.

## Enterprise Class Security

Security protocols are important to mission critical wireless M2M applications. AirborneM2M™ Access Point multi-layer security addresses the requirements of Enterprise-class networks and corporate IT departments. These advanced security features include wireless security (802.11i/WAP2 enterprise), authentication security using WPA2 (AES-CCMP) and device security (multi-layered encryption). The AirborneM2M™ Access Point includes a fully functional DHCP server to provide unique addresses for each authenticated client. Up to 10 clients can be supported on the local Wi-Fi network.

## ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION
APMN-Q551	802.11a/b/g/n, 10/100 Industrial Wireless Access Point/Router/Client Module: UART, SPI and RS-232/422/485 wired interfaces
WLNN-EK-DP551	Design and Development Kit

## ACCESSORIES

**ACH2-DBAT-DP002** - 2dBi portable (rubber duck), 2.4/5GHz antenna

**ACH2-DBAT-DP003** - 3.8/5.5dBi portable (rubber duck), 2.4/5GHz antenna

All product specifications are subject to change without notice.  
APMN-Q551\_DualBandAccessPointModule\_4417ds

# Secure, Rugged Dual Band Module – Access Point / Client / Router

Model APMN-Q551



## SPECIFICATIONS

TECHNOLOGY	
Technology	IEEE 802.11a/b/g/n, Wi-Fi compliant
Frequency	2.4 ~ 2.4835 GHz (US/Canada/Europe) 5.150 ~ 5.350 GHz 5.725 ~ 5.825 GHz
Modulation Technology	DSSS, CCK, OFDM
Modulation Type	DBPSK, DQPSK, CCK, BPSK, QPSK, 16QAM, 64QAM
Network Access Modes	Access Point, Infrastructure (Client), Ad Hoc
Channels	
	US/Canada: 11 Channels 802.11b/g 13 Channels 802.11a
	Europe: 13 Channels 802.11b/g 19 Channels 802.11a
	France: 4 Channels 802.11b/g
	Japan: 14 Channels 802.11b 13 Channels 802.11g 23 Channels 802.11a
Wireless Data Rate	802.11b: 11, 5.5, 2, 1 Mbps 802.11a/g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps 802.11n: 65, 58.5, 42, 39, 26, 19.5, 13, 6.5 Mbps
MAC	CSMA/CA with ACK, RTS, CTS
Network Protocols	TCP/IP, ARP, ICMP, DHCP, DNS, UDAP, TFTP, UDP, PING
Receive Sensitivity 802.11 b/g	54 Mb/s = -72 dBm 36 Mb/s = -78 dBm 18 Mb/s = -84 dBm 6 Mb/s = -89 dBm 11 Mb/s = -86 dBm 1 Mb/s = -92 dBm
Receive Sensitivity 802.11 a	54 Mb/s = -74 dBm 36 Mb/s = -80 dBm 18 Mb/s = -86 dBm 6 Mb/s = -90 dBm

Transmit Power	802.11b = 15 dBm (31.6 mW) 802.11g = 12.6 dBm (18.12 mW) 802.11a = 17 dBm (50.1 mW)
Security Protocols (AP and AdHoc modes)	Disabled, WEP 64 & 128-bit, WPA-PSK(TKIP), WPA2-PSK(AES)
Security Protocols (Client mode)	Disabled, WEP 64 & 128-bit, WPA-PSK(TKIP), WPA2-PSK(AES), WPA & WPA2 Enterprise (EAP-TLS, EAP-TTLS, EAP-PEAP, EAP-FAST, LEAP) and a suite of migration modes (WPA-LEAP64, WPA-LEAP128, WPA-PSK64, WPA-PSK128, WPA-PSK128-TKIP, WPA2-PSK-TKIP) Supports Certificates and Private Key Upload and Storage (multiple)
Antenna	Two (2) U.FL Coaxial Connectors, 50 Ohms Maximum Gain @ 5 GHz = 5.5 dBi Maximum Gain @ 2.4 GHz = 4.1 dBi
Supply	3.3VDC +/-5%, 650 mA (maximum)
Supply In-rush Current	1500 mA (maximum) for 400us
DC Characteristics	Operating Current (Tx, 802.11g) = 370 mA (typical) Operating Current (Rx, 802.11g) = 200 mA (typical)
Environmental	Operating Temperature: -40 to +85 °C Storage Temperature: -40 to +85 °C Relative Humidity: 5 to 95% (non-condensing)
Interfaces	Dual UART (960Kbaud, RS232/ 422/ 485, SPI (1-bit/8 MHz), 10/100 Ethernet, PortFlex
Digital I/O	8 GPIO
LED Indicators	4 Indicator LED Signals (RF_ACT, POST, CONNECT, RF_LINK), Signal Strength
Connector	36-pin High Density SMT Connector from Hirose (DF12-36DS-0.5V), 4mm Height
<b>MEANTIME BEFORE FAILURE (MTBF)</b>	
MTBF	522001 hours (# APMN-Q551) 524380 hours (# WLNN-EK-DP551)
<b>APPROVALS, DIRECTIVES &amp; STANDARDS</b>	
North America	FCC Title 47 Part 15 Class B Sub C Intentional Radiator, IOCRSS210
CE - Directives (Europe)	2014/35/EU - Low Voltage Directive 2014/53/EU - Radio Equipment Directive (RED) Hereby, Advantech B+B SmartWorx declares that the radio equipment type Wi-Fi access point (module) is in compliance with Directive 2014/53/EU. The full text of the EU declaration of conformity is available at the following internet address: <a href="http://www.advantech-bb.com">www.advantech-bb.com</a> 2011/65/EU - Reduction of Hazardous Substances (RoHS) Directive 2012/19/EU - Waste Electrical & Electronic Equipment (WEEE) Directive
CE - Standards (Europe)	<b>EMC:</b> ETSI EN 300 328 v2.1.1 - EMC & Radio Spectrum Matters (ERM) Wideband Transmission Systems - 2.4 GHz ISM Band ETSI EN 301 893 v1.8.5 - EMC & Radio Spectrum Matters (ERM) Wideband Transmission Systems - 5 GHz ISM Band ETSI EN 301 489-1 v2.1.1 - Applied in accordance with the specific requirements of: ETSI EN 301 489-17 v3.1.1 - EMC & Radio Spectrum Matters (ERM) Broadband Data Systems EN 55032+AC, Class A - Information Technology Equipment (ITE) - RF Emissions EN 55024 - Information Technology Equipment (ITE) - Immunity Characteristics - Limits and Methods of Measurement <b>Safety:</b> <b>EN 60950-1 + A1 + A11 + A12 + A2</b> - Information Technology Equipment (ITE) - Safety - Part 1 - General Requirements <b>RF Exposure:</b> EN 62311 - Assessment of electronic and electrical equipment related to human exposure restrictions for EM fields (0 Hz to 300 GHz)