



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Model: EIR608-2SFP and EIR608-4SFP
Gigabit Eight Port Managed Industrial Ethernet Switches



Features

- ✓ **X-Ring Automatic Recovery**
- ✓ **Up to 8 10/100/1000TX RJ45 Ports with MDI/MDI-X**
- ✓ **(2 or 4) 100/1000 SFP Ports**
- ✓ **Dual 12 to 48 VDC Power Inputs**
- ✓ **Relay Alarm Output**
- ✓ **IP30 DIN Rail or Panel Mount**
- ✓ **Automatic E-mail Notification for system events**
- ✓ **SNMP, CLI, or Web Management**
- ✓ **Port Mirror and Port Trunk with LACP**

Functional Description

The Elinx EIR608-xSFP series Industrial Gigabit Managed Ethernet Switches provide powerful functionality in a small package. Designed for industrial applications, these switches contain all the standard features of other switches, such as IGMP Snooping, Port Based VLAN, 802.1Q Tag VLAN, RJ-45 automatic MDI/MDI-X, auto negotiation, store and forward switching, STP, RSTP, Web Based Management, Ingress Packet Filtering, and Egress Rate Control. These managed switches also come with important industrial features to ensure reliability in an industrial application. X-Ring technology with coupling ring and dual homing allows automatic recovery in less than 300 MS. Dual power inputs ensure reliability. A relay alarm output for port failure notification. DIN Rail and Panel Mounting options on the same IP30 case. Another important feature is automatic e-mail notification for system events such as a cold start, change in network topology, power status or SNMP authentication failure. The EIR608-xSFP is also Gigabit capable and comes with 2 or 4 SFP ports which allow the addition of fiber optic ports.

Ordering Information

Model Number	Description
EIR608-2SFP	8 Port Gigabit Industrial Managed Switch w/ 6 copper & (2) copper or SFP Combo ports
EIR608-4SFP	8 Port Gigabit Industrial Managed Switch w/ 4 copper ports and 4 SFP ports



International Headquarters: 707 Dayton Road PO Box 1040 Ottawa, IL 61350 USA
815-433-5100 Fax 433-5104 www.bb-elec.com orders@bb-elec.com support@bb-elec.com

European Headquarters: Westlink Commercial Park Oranmore Co. Galway Ireland
+353 91 792444 Fax +353 91 792445 www.bb-europe.com orders@bb-europe.com support@bb-europe.com

Specifications

Technology

IEEE Standards	802.3 10Base-T Ethernet, 802.3u 100Base-TX and 100Base-FX Fast Ethernet, 802.3ab 1000Base-TX 802.3x Flow Control and Back Pressure, 802.1d Spanning Tree, 802.1w Rapid Spanning Tree 802.1p Class of Service, 802.1Q VLAN Tag, 802.3z Gigabit fiber, 802.3ad Port Trunk with LACP , 802.1x User Authentication
Processing Type	Store and Forward
Flow Control	Flow control on full duplex, Back Pressure on half duplex
MAC Address Table Size	8 KB
Packet Buffer	1M bit
Flash ROM	4M byte
DRAM	32M byte
Protocol	CSMA/CD
Management	SNMP (v2, v2C, V3), Web GUI, TELNET, CLI.
Management Security	Up to 10 IP addresses can have permission to manage the switch. 802.1x (RADIUS) Authentication
Transfer Rate	14,880 pps 10BaseT, 148,800 100BaseTX/FX, 1,488,000 Gigabit
Packet throughput ability	23.8 Mbps @ 64 bytes
X-Ring	2 ports for X-Ring provide redundant backup with a recovery time below 300 MS.
Packet Filter	4 Selection Rules to filter combinations of Broadcast , Multicast, Unicast, and Unknown packets.
VLAN	Port based / Tag (256 entries) / VLAN ID (up to 4K) / GRVP (256 groups) / Double Tag VLAN (Q in Q) Private VLAN
Port Trunk	LACP Port Trunk. 4 Trunk Groups. Maximum 4 Trunk Members
Class of Service	4 priority queues per port
Quality of Service	Port based, Tag and IPv4 Type of Service, IPv4 / IPv6 Different Service
IGMP	IGMP snooping v1, v2. 256 multicast groups and IGMP query
Clock Synchronization	SNTP
Port Mirror	TX packet only or TX and RX packet
Firmware Update	TFTP
DHCP	DHCP Client Function to obtain addresses from DHCP server
Bandwidth Control	Ingress Packet Filter rules and Egress Rate Control

Interface

LAN/WAN Ports	EIR608-2SFP: (6) RJ45 10/100/1000, (2) RJ-45 10/100/1000 or SPF Mini-GBIC Combo (RJ45 disabled when SFP installed), (SFP ports are 100/1000) EIR608-4SFP: (4) RJ45 10/100/1000, (4) SPF Mini-GBIC (SFP ports are 100/1000)
Console Port	RS-232 RJ-45 (Adapter Cable Included)
Port Indicators (each port)	Green LED for Link / Activity, Green LED for speed 1000M, Green LED for SFP Link Activity
System Indicators	Green LEDs for Power, Power 1, Power 2, and Master. Yellow LED for Fault.

Power

Input Voltage	12 to 48 VDC, dual source
Current Consumption	1.4 A max
Input Connection	Terminal Block
Relay Alarm	1A @ 24V

Mechanical

Enclosure	IP30 Aluminum Case
Mount	35 mm DIN or Panel
Dimensions	2.9 x 4.2 x 6.4 in (7.4 x 10.7 x 16.3 cm)

SNMP MIB

RFC 1213 MIBII
RFC 1493 Bridge MIB
RMON RFC 1757
RFC 2674 VLAN MIB
RFC 1643 Ethernet like MIB
RFC 1215 Trap MIB
RFC 1157 SNMP MIB
RSTP MIB
Private MIB for switch info

SNMP Trap

Up to 3 Trap Stations
Cold Start
Port link up
Port link down
Authentication Failure
Power status
Port Alarm
Fault Alarm
X-Ring


Environmental

Operating Temperature	14 to 140 F (-10 to 60 C)
Storage Temperature	-40 to 185 F (-40 to 85 C)
Operating Humidity	0 to 95% NC
MTBF EIR608-2SFP	220593
MTBF EIR608-4SFP	286945

Regulatory Approvals

EMI	FCC Class A EN6100-4-2, -4-3, -4-4, EN6100-4-5, -4-6
Safety	EN60950
Free Fall	IEC60068-2-32
Shock	IEC60068-2-27
Vibration	IEC60068-2-6

CE Declaration of Conformity

Manufacturer's Name	B&B Electronics Mfg CO
Manufacturer's Address	707 Dayton Road PO Box 1040 Ottawa, IL 61350 USA
Model Numbers	EIR608-2SFP, EIR608-4SFP
Description	Industrial Managed Switch
Type	Light Industrial ITE Equipment
Application of Council Directive	89/336/EEC
Standards	EN55022 EN61000-4-2, -4-3, -4-4, -4-5 EN61000-4-6, -4-8, -4-11, -4-12 EN61000-6-2, -6-4
 Michael J. Fahrion, Director of Engineering	



International Headquarters: 707 Dayton Road PO Box 1040 Ottawa, IL 61350 USA
 815-433-5100 Fax 433-5104 www.bb-elec.com orders@bb-elec.com support@bb-elec.com

European Headquarters: Westlink Commercial Park Oranmore Co. Galway Ireland
 +353 91 792444 Fax +353 91 792445 www.bb-europe.com orders@bb-europe.com support@bb-europe.com