



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



10 Port Managed Industrial Ethernet Switches, 3 SFP Combo Ports

EIR610-3SFP-T



PRODUCT FEATURES

- X-Ring automatic recovery
- 7 10/100TX RJ45 ports with MDI/MDI-X
- 3 combo ports (10/100/1000 RJ45 or 100/1000 SFP Mini-GBIC Ports)
- Dual 12 to 48 VDC power inputs
- Wide operating temperature
- Relay alarm output
- IP30 DIN rail or panel mount
- Automatic e-mail notification for system events
- SNMP, CLI, or web management
- port mirror and port trunk with LACP

The Elinx™ EIR610-3SFP-T Industrial Managed Ethernet Switch provides powerful functionality in a small package. Designed for industrial applications, this switch contains all the standard features of other switches, such as IGMP Snooping, Port Based VLAN, 802.1Q Tag VLAN, RJ-45 automatic MDI/MDI-X, auto negotiation, store and forward switching, STP, RSTP, Web Based Management, Ingress Packet Filtering, and Egress Rate Control.

These managed switches also come with important industrial features to ensure reliability in an industrial application. X-Ring technology with coupling ring and dual homing allows automatic recovery in less than 300 MS. Dual power inputs ensure reliability. A relay alarm output for port failure notification. DIN Rail and Panel Mounting options on the same IP30 case. Another important feature is automatic e-mail notification for system events such as a cold start, change in network topology, power status or SNMP authentication failure.

ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION
EIR610-3SFP-T	Industrial Managed Ethernet Switch, 7 RJ45 Ports, (3) 10/100/1000 RJ45 or SFP Ports

ACCESSORIES

MDR-60-24 - DIN Rail Power supply 24VDC, 2.5A, 60W

C5UMB3FBL - 3 ft. (1 M) - Blue - Category 5e UTP Patch Cord

DFMM-LCLC-1M - Multi-Mode Duplex Fiber Cable, LC To LC, 1 Meter

DFSM-LCLC-1M - Single-Mode Duplex Fiber Cable, LC To LC, 1 Meter

SFP-1000SX-M-550M-T - SFP Module, 1000Base-SX, Multi-mode 550m, LC Connector (-40 to 85°C)

SFP-100FX-M-2KM-T - SFP Module, 100Base-FX, Multi-mode 2km, LC Connector (-40 to 85°C)

SFP-1000LX-S-10KM-T - SFP Module, 1000Base-LX, Single-mode 10km, LC Connector (-40 to 85°C)

SFP-1000LX-S-20KM-T - SFP Module, 1000Base-LX, Single-mode 20km, LC Connector (-40 to 85°C)

SFP-100FX-S-30KM-T - SFP Module, 100Base-FX, Single-mode 30km, LC Connector (-40 to 85°C)

10 Port Managed Industrial Ethernet Switches, 3 Combo Ports

EIR610-3SFP-T



SPECIFICATIONS

TECHNOLOGY	
IEEE Standards	802.3 10Base-T Ethernet, 802.3u 100Base-TX and 100Base-FX Fast Ethernet; 802.3x Flow Control and Back Pressure, 802.1d Spanning Tree, 802.1w Rapid Spanning Tree; 802.1p Class of Service, 802.1Q VLAN Tag, 802.3ad Port Trunk with LACP, 802.1x RADIUS
Processing Type	Store and Forward
Flow Control	Flow control on full duplex, Back Pressure on half duplex
MAC Address Table Size	8 KB
Memory	4MB Flash ROM, 32MB DRAM
Protocol	CSMA/CD
Management	SNMP v1, v2c, v3, Web GUI, TELNET, CLI, Menu Driven Interface
Management Security	Up to 10 IP addresses can have permission to manage the switch. 802.1x (RADIUS) Authentication
Transfer Rate	14,880 bps for 10Base-T Ethernet ports, 148,800 for 100Base-TX/FX Fast Ethernet ports
Packet throughput ability	8.3 Mbps @ 64 bytes
X-Ring	2 ports for X-Ring provide redundant backup with a recovery time below 300 MS.
Packet Filter	4 Selection Rules to filter combinations of Broadcast, Multicast, Unicast, and Unknown packets.
VLAN	Port based and Tag. Up to 256 VLAN groups
Port Trunk	LACP Port Trunk. 4 trunk groups / maximum of 4 trunk members.
Class of Service	4 priority queues per port
Quality of Service	Port based, Tag based, or IPv4 Type of Service, IPv6 Different Service
IGMP	IGMP Snooping v1, v2, and v3. 256 multicast groups and IGMP query
Clock Synchronization	SNTP
Management Security	IP Address
Port Mirror	TX packet only, RX packet only, or TX and RX packet
Firmware Update	TFTP, TFTP backup and restore
DHCP	DHCP Client / DHCP Server
Bandwidth Control	Ingress packet filter and Egress packet limit
INTERFACE	
LAN/WAN Ports	7 RJ45 10/100TX, 3 Combo RJ45 10/100/1000 or 100/1000 SFP Mini-GBIC Combo (On Combo ports the RJ45 is disabled when an SFP module is installed)
Console Port	RS-232 RJ-45 (DB9 to RJ-45 adapter cable included)
Port Indicators (each port)	10/100: Link/Activity (Green), Full-duplex/Collision (Yellow); Giga Copper: Link/Activity (Green), Speed (1000Mbps Green); SFP: Link/Activity (Green)
System Indicators	Green LEDs for Power, Power 1, Power 2, and Master. Orange LED for Fault.

POWER	
Input Voltage	12 to 48 VDC, dual source
Current Consumption	0.84 A max.
Input Connection	Terminal Block
Relay Alarm	1A @ 24VDC
ENVIRONMENTAL	
Operating Temperature	-40 to 167°F (-40 to 75°C)
Storage Temperature	-40 to 185°F (-40 to 85°C)
Operating Humidity	10 to 95% Non-condensing
MTBF	260818 hours
MECHANICAL	
Enclosure	IP30 DIN mount metal case
Mount	35 mm DIN or Panel
Dimensions	7.4 x 10.7 x 16.3 cm (2.7 x 4.2 x 6.4 in)
REGULATORY APPROVALS	
EMI	FCC Class A EN6100-4-2, -4-3, -4-4, EN6100-4-5, -4-6
Safety	EN60950
Free Fall	IEC60068-2-32
Shock	IEC60068-2-27
Vibration	IEC60068-2-6
RFC STANDARDS	
RFC1215 Trap	Up to 3 Trap Stations
RFC1213 MIBII	Cold Start
RFC1157 SNMP MIB	Port link up
RFC1493 Bridge	Port link down
RFC2674 VLAN MIB	Authentication Failure
RFC1643	Power status
RFC 757	Port Alarm
RSTP MIB	Fault Alarm
Private MIB	X-Ring Change
SNMP TRAP	