



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



High Speed USB 2.0 Serial Adapters

4 or 8 independent serial ports

Models ESU2-100, ESU2-400, QSU2-100, QSU2-400

B+B SMARTWORX

Powered by

ADVANTECH

www.advantech-bb.com



PRODUCT FEATURES

- Standard serial power via USB 2.0 without replacing peripherals or application software
- RS-232 or software selectable RS-232/422/485
- USB 2.0 (compatible with USB 1.1)
- Plug-and-play compatibility
- Devices enumerate themselves as standard COM ports
- Speeds up to 921.6 kbps
- High-speed UARTS with 1KB FIFOs boost data rates
- Full modem, hardware and software flow control
- Bus powering – no external power required

Connect and broaden the range of external peripherals on your computer with these USB 2.0 high speed serial adapters. The USB 2.0 standard has more bandwidth allowing higher data rates on serial ports for greater efficiency. USB 2.0 is fully compatible with USB 1.1 devices. Older devices work with the new bus, and vice versa.


These USB serial adapters give your laptop or workstation the ability to communicate between a USB port and up to eight RS-232, RS-422, or RS-485 serial peripherals. The USB serial adapters enumerate themselves as standard COM ports via the USB connection and are compatible with new and legacy RS-232 or RS-232/422/485 devices and the software created for them. The adapters support data rates up to 921.6 kbps, 1024-byte FIFO and hardware/software flow control.

400 Series Models feature software-selectable RS-232/422/485 MEI (“Multi-Electrical Interface”). MEI capability is available on all ports at the click of a mouse. LEDs visually tell you which ports are using which protocol – so go ahead, mix and match.

These USB serial adapters are the ideal solution for a variety of industries and applications including banking, retail and industrial automation where PCs have a significantly shorter lifecycle than the peripherals that use them.

ORDERING INFORMATION

MODEL NUMBER	PORTS	INTERFACE	SOFTWARE SELECTABLE?
QSU2-100	4	RS-232 with cable	-
QSU2-400	4	RS-232/422/485 with cable	Yes
ESU2-100	8	RS-232 with cable	-
ESU2-400	8	RS-232/422/485 with cable	Yes



All product specifications are subject to change without notice.

ESU2-QSU2_100-400_4-8port_2917ds

High-Speed USB 2.0 Serial Adapters

4 or 8 independent serial ports

Models ESU2-100, ESU2-400, QSU2-100, QSU2-400



SPECIFICATIONS

SERIAL TECHNOLOGY	
Serial Connectors	QSU2-100/400 = 4 ports (DB9 male) ESU2-100/400 = 8 ports (DB9 male)
Serial Port Configuration <i>Models QSU2-400 & ESU2-400 only</i>	Each port is independently configurable as RS-232, RS-422 or RS-485 for full-duplex or half-duplex communication)
Data Rate	Up to 921.6 kbps (maximum)
UARTS	1024-byte FIFOs for Transmit and Receive
Transceiver (RS-232/422/485)	MAX491 or compatible
USB TECHNOLOGY	
USB Connector	QSU2-100/400 = 1 port (USB Type A Male) ESU2-100/400 = 1 port (USB Type A Male)
Bus Interface	2.0 and 1.1 Compatible
INPUT/OUTPUT	
Differential Driver Output	50Ω Load: +2V (minimum), +3.3V (maximum) 27Ω Load: +1.5V (minimum), +3.3V (maximum)
High Input	+2.0V (minimum)
Low Input	+0.8V (maximum)
Driver Rise/Fall Time	5ns (minimum), 20ns (typical), 25ns (maximum)
Driver Input-to-Output Delay	20ns (minimum), 40ns (typical), 60ns (maximum)
Receiver Input-to-Output Delay	40ns (minimum), 70ns (typical), 100ns (maximum)
RS-232 Output	Voltage Range: +/-5V (minimum), +/-5.4V (typical)
RS-232 Input	Voltage Range: -15V (minimum), +15V (typical) Threshold Low: 0.6V (minimum), 1.0V (typical) Threshold High: 2.4V (minimum), 1.5V (typical)

SPECIFICATIONS - continued

POWER	
Source	Bus-powered; no external power supply required
Suspend Power	<500 mA
Unconfigured Power	<100 mA
Configured Power	<500 mA
SOFTWARE	
OS Support	Windows 2000, XP, Linux
MECHANICAL	
Dimensions	QSU2-100/400 = 9.18L x 5.25W x 1.675H (inches) ESU2-100/400 = 9.18L x 5.25W x 2.363H (inches)
ENVIRONMENTAL	
Operating Temperature	0 to 70 °C
Storage Temperature	-50 to 80 °C
Humidity	10 to 90%
REGULATORY	
Certifications	FCC Class B, CE, RoHS, WEEE Compliant

MECHANICAL DIAGRAM - QSU2-100 & QSU2-400

