



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Model USB2ARC5M
USB 2.0 Active Repeater Cable

Overview

The USB 2.0 Active Repeater Cable acts as a single port hub, which means that multiple cables can be cascaded (up to 5) to increase the distance between your computer and USB devices. It can extend the distance of a USB device up to 25 meters.

Features

- Cascades to extend distances up to 25 meters between the USB device and the computer
- Regenerates the USB signal for maximum reliability and performance over extended distances
- Connects to USB device or second active repeater cable
- Maximum transfer rate up to 480 Mbps
- Supports USB 2.0, 1.1 and 1.0

Specifications

Cable Length:	5 meters
Connectors:	Downstream connector (Type A female) Upstream connector (Type A male)
Data Rate:	Up to 480 Mbps (USB 2.0) Also supports High Speed 12 Mbps and Low Speed 1.5 Mbps
Power:	Bus powered
Operating Temperature:	0~70°C
Storage Temperature:	-10~80°C