



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Four-port USB Hub – OEM Module


Models USBHUB4OEM, USBHUB4OEM-12PK

B+B SMARTWORX

Powered by

ADVANTECH

www.advantech-bb.com



PRODUCT FEATURES

- High-retention USB Port Connectors
- Ultra-compact, Open Bare-board Design
- ESD Protection - 8 kV Contact, 15 kV Air
- -40 to 80 °C Operating Temperature
- Powered from USB Host
- USB 2.0
- Installs as an unbranded USB hub

Model USBHUB4OEM is a four-port, high-speed, USB hub intended for OEM applications where space is at a premium and external packaging is not required.

High ESD protection makes it suitable for use in electrically harsh environments. Full speed (480 Mbps) USB 2.0 support allows connectivity with modern computer technology. High retention USB ports on the upstream and downstream sides allow you to use standard off the shelf USB cables while being confident that they will not come loose during operation. When installed in your system, the USBHUB4OEM appears as an unbranded USB hub.

The hub is powered entirely by the USB host port, leaving your installation uncluttered by power cabling. As a bus powered device, it provides 100 mA of power to downstream peripherals which is adequate for most applications. *Important: check your device to be sure this power is adequate. If it needs more power, B+B SmartWorx has a variety of externally powered hubs to select from.*

The hub is available as a single unit for prototype work (Model USBHUB4OEM) or in a convenient 12-piece package for production orders (Model USBHUB4OEM-12PK).

ORDERING INFORMATION

MODEL NUMBER	USB SPEED
USBHUB4OEM	4 Port USB Hub, OEM Module
USBHUB4OEM-12PK	4 Port USB Hub, OEM Module, 12 Unit Pack


SPECIFICATIONS

USB TECHNOLOGY	
USB Compatibility	1.1 and 2.0
Speed	1.5, 12, and 480 Mbps
Connectors	Type A & B High Retention (15 N / 3.4 lbs-force withdrawal)
POWER	
Source	5 VDC from USB Host
Power Consumption	2.5 Watts Maximum
Downstream Power	Provides 100 mA per port to power downstream USB devices
MECHANICAL	
Dimensions	135.6 x 51 x 18 mm (.4 x 2.4 x 0.7 in)
Weight	0.8 oz (22.7 g)
MTBF	552747 hours
MTBF Calc. Method	MIL 217F Parts Count Reliability
APPROVALS, DIRECTIVES, STANDARDS	
FCC, CE	
Directives (EU)	2014/30/EU - Electromagnetic Compatibility Directive 2011/65/EU - Reduction of Hazardous Substances Directive (RoHS) 2012/19/EU - Waste Electrical and Electronic Equipment (WEEE)
Standards (EMC)	EN 55032: Class B - Information Technology Equipment - RF Emissions EN 55024 - Information Technology Equipment - Immunity Characteristics - Limits and Methods of Measurements EN 61000-6-1 - Generic Immunity Standard for Residential, Commercial and Light-Industrial Environments

All product specifications are subject to change without notice.
USBHUB4OEM_4817ds

Four-port USB Hub – OEM Module

Models USBHUB4OEM, USBHUB4OEM-12PK



MECHANICAL DIAGRAM

