



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Wzzard™ HVAC Monitoring Starter Kit

Wzzard Mesh Wireless Sensor for Industrial Applications

Model BB-WSK-HAC-2

B+B SMARTWORX

Powered by

ADVANTECH

www.advantech-bb.com



FEATURES

- + Monitor current and temperature to reduce energy costs
- + Snap & go set up - no downtime, disruption or wiring/cable runs
- + Built-in Node-RED™ software tool for easy deployment
- + Smartmesh IP wireless mesh for point-to-point, self-healing reliability; more resilient as more nodes are added
- + Easily scalable at any time to thousands of sensors
- + IP67 indoor/outdoor rated (Wzzard node)

Lower energy costs, schedule preventative maintenance and detect failures early through data-driven HVAC performance monitoring.

Monitor Performance of Your HVAC System

Today's leading manufacturing and facility managers have performance improvement programs in place to reduce input costs and improve their environmental footprint. But, often they're managing those programs with nothing more than an environmental temperature monitoring and periodic inspections, with no insight into the performance of individual HVAC units. Additionally, retrofitting a building automation system carries a high cost of installation and is disruptive to ongoing operations.

The Wzzard HVAC Monitoring Starter Kit provides a non-intrusive, easily installed solution for monitoring current and differential temperature on your HVAC equipment without disrupting your existing facility operations.

- Includes everything you need to monitor incoming and outgoing air or coolant temperatures along with current consumption of the compressor and fan.
- No equipment downtime. Simply snap on the current clamps and temperature probes connected to the wireless Wzzard mesh wireless sensor and provide an Ethernet connection to the gateway.
- Dashboard, data trendlines, email/SMS alerts and data logging capability.
- Easily expand the starter kit system by adding additional Wzzard mesh wireless sensor nodes and sensors to your existing gateway.
- Fast deployment of Proof of Concept and Pilots. Easy to scale to hundreds or thousands of inputs from one location or multiple locations.

Easy to Deploy

- The Wzzard mesh wireless sensor node is battery-powered and is easily deployed - no need to install expensive or intrusive wiring.
- Clamp-on current transducers are easy to install without disrupting equipment. Simply clamp them over the hot power lead.
- Tie temperature sensors directly into airflow or on high and low pressure lines
- Wzzard's 2.4 GHz wireless mesh technology continuously optimizes its channel selection to eliminate multipath interference, providing best-in-class reliability in difficult RF environments.
- Simple, cloud-based configuration of the gateway makes it easy to deploy and manage one device or many.

Scalable

- Grow from monitoring one unit to many simply by adding more sensor nodes and making simple dashboard edits.
- Or expand into a multi-site system integrated into your preferred software platform. The popular MQTT protocol and JSON data format make it easy to integrate into third-party software applications.
- Use the built-in Node-RED to create and customize your own applications without any advanced programming skills.

Rugged & Reliable

- Wzzard mesh wireless sensor node is IP67 rated, -40 to 80°C, for indoor and outdoor industrial use – no external enclosure required.
- Advanced Smartmesh IP wireless mesh protocol provides excellent point-to-point wireless reliability and becomes more resilient as more nodes are added to the system.

ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION
BB-WSK-HAC-2	Wzzard HVAC Monitoring Starter Kit

Included Hardware

- (1) Wzzard mesh wireless sensor node, Model# WSD2C21150 (2 analog inputs, 1 digital input, 1 digital output, 2 thermocouples, 2 thermistors, internal temperature)
- (2) JC10F50-V, 50A Clamp-On Current Sensors – for compressor and fan current.
- (2) BB-WTJ-10-36-TT, J-Type Thermocouple – #10 mounting hole, ungrounded.
- (1) SmartSwarm 342 Ethernet Network Gateway – with Wzzard board.
(Note: one gateway supports up to 100 wireless sensor nodes.)

Included Software

- Cloud license for SmartWorx Hub device management and configuration tool.
Node-RED flow with Web Server for:
- Real time data display.
 - Historian trending.
 - Visual and email/SMS alerts.
 - External data source integration (weather, Twitter feeds, and more).

All product specifications are subject to change without notice.
BB-WSK-HAC-2 Kit_0318ds

Wzzard™ HVAC Monitoring Starter Kit

Wzzard Mesh Wireless Sensor for Industrial Applications

Model BB-WSK-HAC-2



SPECIFICATIONS

GATEWAY/NODE	
Nodes per Gateway	32, maximum
Polling Range	10 seconds, maximum
Wireless Range	Up to 100 meters indoors; Up to 300 meters outdoors Line-of-sight, 2 meters above ground.
TEMPERATURE SENSORS	
Measurement Range	0 to 750 °C (-32 to 1382 °F)
Accuracy (0 to 40°C)	+/-2.2 °C (+/-3.96 °F)
CURRENT SENSORS	
Measurement Range	0.3 to 50 A
Minimum Reading (at 0 Amps Input)	0.3 A
Accuracy	+/-2.2%

Node-RED Dashboard

