imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

Features

- Halogen free available upon request by adding suffix "-HF"
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- **Epitaxial Die Construction**
- Complementary PNP Type Available (BC857AT,BT,CT)
- Ultra-Small Surface Mount Package Epoxy meets UL 94 V-0 flammability rating
- Moisure Sensitivity Level 1

Maximum Data

- Case: SOT-523
- Terminals: Solderable per MIL-STD-202, Method 208
- Polarity: See Diagram
- Marking:BC847AT--1E,BC847BT--1F,BC847CT-1G.


Maximum Ratings @ 25 $^{\circ}$ C Unless Otherwise Specified


| Symbol | Parameter | Value | Units | | | |
|-----------------------------------|--|-------------------------------------|-------|--|--|--|
| OFF CHARA | OFF CHARACTERISTICS | | | | | |
| V _{(BR)CEO} | Collector-Emitter Breakdown Voltage | lector-Emitter Breakdown Voltage 45 | | | | |
| V _{(BR)CBO} | Collector-Base Breakdown Voltage | 50 | Vdc | | | |
| V _{(BR)EBO} | Collector-Emitter Breakdown Voltage | 6.0 | Vdc | | | |
| Ι _c | Collector Current | 100 | mAdc | | | |
| P _d | Power Dissipation (Note 1) | 150 | mW | | | |
| $R_{\theta JA}$ | Thermal Resistance, Junction to 833 Ambient(Note 1) | | °C/W | | | |
| T _J , T _{STG} | Operating & Storage Temperature | -55~+150 ℃ | | | | |

Note: 1. Device mounted on FR-4 PCB with recommended pad lavout

BC847AT, BT, CT

NPN **Surface Mount Small Signal Transistor** 150mW





| _ | INCHES | | MM | | |
|-----|--------------|------|-------------|------|------|
| DIM | MIN | MAX | MIN | MAX | NOTE |
| А | .059 | .067 | 1.50 | 1.70 | |
| В | .030 | .033 | 0.75 | 0.85 | |
| С | .057 | .069 | 1.45 | 1.75 | |
| D | .020 Nominal | | 0.50Nominal | | |
| Е | .035 | .043 | 0.90 | 1.10 | |
| G | .000 | .004 | .000 | .100 | |
| Н | .028 | .031 | .70 | 0.80 | |
| J | .004 | .008 | .100 | .200 | |
| К | .010 | .014 | .25 | .35 | |
| | | | | | |

— www.mccsemi.com

BC847AT, BT, CT



Electrical Characteristics @ 25° C Unless Otherwise Specified

| Symbol | Parameter | Min | Тур | Max | Units | Test Condition | | |
|--------------------------------------|--|-------------------|----------------|-------------------|----------|---|--|--|
| OFF CHARA | OFF CHARACTERISTICS | | | | | | | |
| h _{FE} | DC Current Gain (Note 2) Current Gain A B C | 110 200 420 | 290 520 | 222 450 800 | | V_{CE} =5.0V, I _C =2.0mA | | |
| $V_{\text{CE(SAT)}}$ | Collector-Emitter Saturation Voltage (Note 2) | | | 250 600 | mV | I _C =10mA, I _B =0.5mA I _C =100mA, I _B =5.0mA | | |
| $V_{\text{BE(SAT)}}$ | Base-Emitter Saturation Voltage (Note 2) | | 700 900 | | mV | I _c =10mA, I _B =0.5mA I _c =100mA, I _B =5.0mA | | |
| V _{BE(ON)} | Base-Emitter Voltage (Note 2) | 580 | 660 | 700 770 | mV | V _{CE} =5.0V, I _C =2.0mA V _{CE} =5.0V, I _C =10mA | | |
| I _{сво} I _{сво} | Collector-Cutoff Current (Note 2) | | | 15 5.0 | nA μA | V _{CB} =30V, I _E =0 V _{CB} =30V, T _j =125℃ | | |
| f _T | Gain Bandwidth Product | 100 | | | MHz | V _{CE} =5.0V, I _C =10mA, f=100MHz | | |
| C _{CBO} | Collector-Base Capacitance | | | 4.5 | pF | V _{CB} =10V, f=1.0MHz | | |
| NF | Noise Figure BC847BT BC847CT | | | 10 4.0 | dB | V _{CE} =5V,R _S =2.0Kohm, f=1.0MHz,BW=200HZ | | |

Note: 2. Short duration pulse test used to minimize self-heating effect.

— www.mccsemi.com



Ordering Information :

| Device | Packing |
|----------------|-----------------------|
| Part Number-TP | Tape&Reel 3 Kpcs/Reel |

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com