mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



1 22005 À ADDED FORMS COMPLANT, TABLES AND TA				DATE	SYM	REVISION REC	ORD	AUTH	DR. CK.	
512 Image: 10° Lings How ABOVE ORDERING CODE BH24AA Image: 10° Lings How ABOVE Solder Lings How ABOVE Solder Lings How ABOVE Image: 10° Lings How ABOVE Sector Lings How ABOVE Image: 10° Lings How ABOVE Sector Lings How ABOVE Image: 10° Lings How ABOVE Sector Lings How ABOVE Image: 10° Lings How ABOVE Sector Lings How ABOVE Image: 10° Lings How ABOVE Sector Lings How ABOVE Image: 10° Lings How ABOVE Sector Lings How ABOVE Image: 10° Lings How ABOVE Sector Lings How ABOVE Image: 10° Lings How ABOVE Sector Lings How ABOVE Image: 10° Lings How ABOVE Sector Lings How ABOVE Image: 10° Lings How ABOVE Sector Lings How ABOVE Image: 10° Lings How How ABOVE Sector Lings How ABOVE Image: 10° Lings How				11/26/05	Α	ADDED "ROHS COM	PLIANT"	T.B.	B.S.	
Provide the set of the s				3/04/06	В	UPDATED MATERIAL	SPEC.	T.B.	B.S.	
Image: Sector	57.2			4/29/06	С	ADDED CONTACT RE	si. Info	T.B.	B.S.	
Solder LUGS = L (6') WHE LEADS = W 9 VOLTTYPE SNAPS = 9F 9 VOLTTY										
Solder LUGS = L (6') WHE LEADS = W 9 VOLTTYPE SNAPS = 9F 9 VOLTTY										
SPECIFICATIONS : Plastic material - polypropylene Flammability rating-UL94 HB, UL file no. E216959 Temperature Range: -10°C to +100°C Springs - hickel plated gring steel Wire - 152.4 mm Ref.Long 26 AWG, UL1007, CSA - TR-64, 300V, 80 C. Rivets - Brass, nickel plated * 9 Volts Snaps - Brass, nickel plated * Contact Resistance: Under 50mQ for +/- contacts per EIA-540,000				ORDEI	ring	SOLDE (6'') WIRE		6 = L 6 = W		
Specifications : Note: Dimensions in mm. (inches) Plastic material - polypropylene Flammability rating-UL94 HB, UL file no. E216959 Temperature Range: -10°C to +100°C Springs - nickel plated spring steel Wire - 152.4 mm Ref.Long 26 AWG, UL1007, CSA - TR-64, 300V, 80 C. Rivets - Brass, nickel plated Rivets - Brass, nickel plated ° 9 Volts Snaps - Brass, nickel plated ° Contact Resistance: Under 50mΩ for +/- contacts per EIA-540J000 DATE			(1.24")							
SPECIFICATIONS : Plastic material - polypropylene Flammability rating-UL94 HB, UL file no. E216959 Temperature Range: -10°C to +100°C Springs - nickel plated spring steel Wire - 152.4 mm Ref.Long 26 AWG, UL1007, CSA - TR-64, 300V, 80 C. Rivets - Brass, nickel plated 9 Volts Snaps - Brass, nickel plated Contact Resistance: Under 50mΩ for +/- contacts per EIA-540J000 Poluta R DATE	SOLDER LUGS SHOWN ABOVE									
Flammability rating-UL94 HB, UL file no. E216959 Temperature Range: -10°C to +100°C Springs - nickel plated spring steel Wire - 152.4 mm Ref.Long 26 AWG, UL1007, CSA - TR-64, 300V, 80 C. Rivets - Brass, nickel plated 9 Volts Snaps - Brass, nickel plated 9 Volts Snaps - Brass, nickel plated Contact Resistance: Under 50mΩ for +/- contacts per EIA-540J000 ANGULAR DATE DRAWN BY Sc. ANGULAR		Note: Dimensions in mm. (inches) TOLEBANCES								
Flammability rating-UL94 HB, UL file no. E216959 Temperature Range: -10°C to +100°C Springs - nickel plated spring steel Wire - 152.4 mm Ref.Long 26 AWG, UL1007, CSA - TR-64, 300V, 80 C. Rivets - Brass, nickel plated 9 Volts Snaps - Brass, nickel plated 9 Volts Snaps - Brass, nickel plated Contact Resistance: Under 50mΩ for +/- contacts per EIA-540J000 ANGULAR DATE DRAWN BY Sc. ANGULAR		(EXCEPT AS NOTED)								
Temperature Range: -10°C to +100°C Springs - nickel plated spring steel Wire - 152.4 mm Ref.Long 26 AWG, UL1007, CSA - TR-64, 300V, 80 C. Rivets - Brass, nickel plated 9 Volts Snaps - Brass, nickel plated Contact Resistance: Under 50mΩ for +/- contacts per EIA-540J000 ANGULAR DATE DRAWING NUMBER										
Springs - nickel plated spring steel Wire - 152.4 mm Ref.Long 26 AWG, UL1007, CSA - TR-64, 300V, 80 C. Rivets - Brass, nickel plated 9 Volts Snaps - Brass, nickel plated Contact Resistance: Under 50mΩ for +/- contacts per EIA-540J000 ANGULAR DATE DRAWING NUMBER	Temperature Range: -10°C to +100°C							5.0.		
Rivets - Brass, nickel plated * .8 (.030") FOUR "AA" CELL HOLDER 9 Volts Snaps - Brass, nickel plated .8 (.030") ANGULAR DATE Contact Resistance: Under 50mΩ for +/- contacts per EIA-540J000 ANGULAR DATE DRAWING NUMBER			ΤΙΤΙ Ε			, , ,				
9 Voits Snaps - Brass, nickel plated Contact Resistance: Under 50mΩ for +/- contacts per EIA-540J000 ANGULAR DATE DRAWING NUMBER	Rivets - Brass, nickel plated °									