



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





# VRLA Rechargeable Battery

## BP10-4



### FEATURES

- Maintenance free(no water topping-up required).
- No free acid(Non-spillable battery).
- Low self-discharge rate, lower than 3% capacity loss per month.
- Can be used in any orientation(excluding used inverted).
- Absorbent Glass Mat technology for efficient gas recombination.

### APPLICATION

- UPS
- Lighting
- Medical
- Old Laptop



### SPECIFICATIONS

Nominal Voltage	4 V
Nominal Capacity	10.0Ah @ 20 hour rate F.V.(1.75V/cell)
Approx. Weight	1310g(2.89lbs.)
Terminals	T1 (Faston Tab 187) T2 is optional
Internal Resistance	≤8mΩ (Fully Charged )
Max. Discharge Current	150 A (5 sec.)
Max. Charge Current	3.0 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage. : -20°C~40°C(-4°F~104°F)
Container Material	Standard:BP10-4 ABS( UL 94-HB) Optional: BP10-4FR ABS(UL 94-V0)

**ISO9001** **UL** MH19884

**OHSMS** **CE** CAM20310-2474-E-16

**ISO14001**

- IEC 61056-1
- JIS C 8702-1
- GB/T 19639.1

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<p>■ <b>Length</b> 101±1.5 (3.98±0.06)</p> <p>■ <b>Width</b> 50±1.5 (1.97±0.06)</p> <p>■ <b>Container Height</b> 94±1.5 (3.70±0.06)</p> <p>■ <b>Total Height</b> 100±2.0 (3.94±0.08)</p>		<p>• Terminal T1</p> <p>• Terminal T2</p>

### Constant power discharge characteristics at 25 °C/77 °F Unit: W

Discharge Time F.V. (V/cell)	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	120.5	88.7	71.1	42.3	24.26	9.72	6.70	3.74	1.97
1.75V	139.5	96.1	74.4	43.9	24.99	9.91	6.80	3.80	2.00
1.70V	148.2	99.6	76.7	44.9	25.44	10.00	6.84	3.82	2.01
1.65V	154.9	102.0	78.4	45.5	25.74	10.07	6.86	3.83	2.02
1.60V	160.0	104.0	80.0	46.0	26.00	10.13	6.88	3.83	2.02

### Constant current discharge characteristics at 25 °C/77 °F Unit: A

Discharge Time F.V. (V/cell)	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	32.57	23.43	18.55	10.75	6.12	2.43	1.675	0.936	0.493
1.75V	38.39	25.38	19.40	11.16	6.30	2.48	1.700	0.950	0.500
1.70V	40.79	26.30	20.00	11.42	6.41	2.50	1.709	0.955	0.503
1.65V	42.62	26.93	20.46	11.58	6.49	2.52	1.715	0.958	0.504
1.60V	44.04	27.46	20.87	11.69	6.55	2.53	1.720	0.958	0.504

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.