



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



72V External Battery Pack for Select Tripp Lite UPS Systems, 2U Rack/Tower, TAA

MODEL NUMBER: **BP72V18-2USTAA**



TAA-compliant external battery pack provides extended runtime for compatible 72V Tripp Lite UPS systems.

Features

Gives Your Compatible Tripp Lite UPS System Extended Runtime

The BP72V18-2USTAA is compatible only with Tripp Lite's SU3000RTXLCDTAA and other UPS systems that specify the use of this battery pack. Not only does it provide extended runtime, but it can also be daisy-chained using its rear connector to additional external battery packs for even longer extended-run operation. Heavy-gauge cabling with high-current DC connectors is included for simple installation.

Mounts in 2U of Space in 19 in. 4-Post Racks

This battery pack's multi-use form factor supports mounting in 2U of space in EIA-standard 19-inch racks using the included 4-post rack-mounting brackets. The BP72V18-2USTAA is also compatible with Tripp Lite's 2-9USTAND for upright tower configuration, 2POSTRMKITWM for 2-post racks or wall installation and UPDHDEARKIT for 2-point front-rail rack installation without rear supports (all accessories sold separately).

TAA-Compliant for GSA Schedule Purchases

The BP72V18-2USTAA is compliant with the Federal Trade Agreements Act for GSA Schedule purchases.

2-Year Warranty and Environmentally Responsible Design

The BP72V18-2USTAA comes with a 2-year warranty. It's manufactured in compliance with strict RoHS specifications, reflecting Tripp Lite's commitment to environmental responsibility.

Highlights

- Connects to expandable 72V DC Tripp Lite UPS systems for extended runtime
- Daisy-chain connector supports additional battery packs for even longer runtime
- Mounts in 2U of space in 19 in. rack using included 4-post installation hardware
- Supports 2-post rack, wall or tower installation with optional accessories
- Complies with Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Applications

- Extends the runtime of your compatible Tripp Lite UPS system
- Daisy-chains to additional battery packs to provide even longer extended-run operation

Package Includes

- BP72V18-2USTAA 72V External Battery Pack, 2U Rack/Tower, TAA
- Rack-mounting hardware
- Owner's manual

Specifications

OVERVIEW	
UPC Code	37332223678
BATTERY	



DC System Voltage (VDC)	72
UPS Connection	Attached cable with black 3-point DC connector
Typical Battery Lifespan	4-6 years typical (North America)
PHYSICAL	
Installation Form Factors Supported with Included Accessories	4 post 19 inch rackmount
Installation Form Factors Supported with Optional Accessories	2 post rackmount (2POSTRMKITWM); Wallmount (2POSTRMKITWM); Tower (2-9USTAND); 2-4 post front rail rackmount (UPSHDEARKIT)
Minimum Required Rack Depth (inches)	32
Minimum Required Rack Depth (cm)	81.28
Shipping Dimensions (hwd / in.)	9.00 x 28.00 x 26.00
Shipping Dimensions (hwd / cm)	22.86 x 71.12 x 66.04
Shipping Weight (lbs.)	134.39
Shipping Weight (kg)	60.96
Unit Dimensions (hwd / in.)	3.4 x 17.3 x 20.8
Unit Dimensions (hwd / cm)	8.6 x 44 x 52.8
Unit Weight (lbs.)	88.20
Unit Weight (kg)	40.01
Material of Construction	Steel
External Battery Pack Form Factor	Rack/Tower
CERTIFICATIONS	
Certifications	Tested to CE; TAA Compliant
WARRANTY	
Product Warranty Period (U.S. & Canada)	2-year limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	1-year limited warranty
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>