



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## Silicon PIN Photodiode



16140-1

### DESCRIPTION

BPV10NF is a PIN photodiode with high speed and high radiant sensitivity in black, T-1 $\frac{3}{4}$  plastic package with daylight blocking filter. Filter bandwidth is matched with 870 nm to 950 nm IR emitters.

### FEATURES

- Package type: leaded
- Package form: T-1 $\frac{3}{4}$
- Dimensions (in mm):  $\varnothing$  5
- Radiant sensitive area (in mm<sup>2</sup>): 0.78
- Leads with stand-off
- High radiant sensitivity
- Daylight blocking filter matched with 870 nm to 950 nm emitters
- High bandwidth: > 100 MHz at  $V_R = 12$  V
- Fast response times
- Angle of half sensitivity:  $\varphi = \pm 20^\circ$
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

### APPLICATIONS

- High speed detector for infrared radiation
- Infrared remote control and free air data transmission systems, e.g. in combination with TSFFxxxx series IR emitters

### PRODUCT SUMMARY

| COMPONENT | $I_{ra}$ ( $\mu$ A) | $\varphi$ (deg) | $\lambda_{0.5}$ (nm) |
|-----------|---------------------|-----------------|----------------------|
| BPV10NF   | 60                  | $\pm 20$        | 790 to 1050          |

#### Note

- Test condition see table "Basic Characteristics"

### ORDERING INFORMATION

| ORDERING CODE | PACKAGING | REMARKS                      | PACKAGE FORM      |
|---------------|-----------|------------------------------|-------------------|
| BPV10NF       | Bulk      | MOQ: 4000 pcs, 4000 pcs/bulk | T-1 $\frac{3}{4}$ |
| BPV10NF-CS21  | Reel      | MOQ: 5000 pcs, 1000 pcs/reel | T-1 $\frac{3}{4}$ |

#### Note

- MOQ: minimum order quantity

### ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25$ °C, unless otherwise specified)

| PARAMETER                             | TEST CONDITION                               | SYMBOL     | VALUE       | UNIT |
|---------------------------------------|--|------------|-------------|------|
| Reverse voltage                       |  | $V_R$      | 60          | V    |
| Power dissipation                     | $T_{amb} \leq 25$ °C                         | $P_V$      | 215         | mW   |
| Junction temperature                  |  | $T_j$      | 100         | °C   |
| Operating temperature range           |  | $T_{amb}$  | -40 to +100 | °C   |
| Storage temperature range             |  | $T_{stg}$  | -40 to +100 | °C   |
| Soldering temperature                 | $t \leq 5$ s, 2 mm from body                 | $T_{sd}$   | 260         | °C   |
| Thermal resistance junction / ambient | Connected with Cu wire, 0.14 mm <sup>2</sup> | $R_{thJA}$ | 350         | K/W  |

| <b>BASIC CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |  |                 |      |                     |      |   |
|---|--|-----------------|------|---------------------|------|---|
| PARAMETER   | TEST CONDITION   | SYMBOL          | MIN. | TYP.                | MAX. | UNIT                                    |
| Forward voltage   | $I_F = 50\text{ mA}$   | $V_F$           |      | 1.0                 | 1.3  | V                                       |
| Breakdown voltage   | $I_R = 100\text{ }\mu\text{A}$ , $E = 0$                                   | $V_{(BR)}$      | 60   |                     |      | V                                       |
| Reverse dark current  | $V_R = 20\text{ V}$ , $E = 0$  | $I_{ro}$        |      | 1                   | 5    | nA                                      |
| Diode capacitance   | $V_R = 0\text{ V}$ , $f = 1\text{ MHz}$ , $E = 0$                          | $C_D$           |      | 11                  |      | pF                                      |
| Open circuit voltage  | $E_e = 1\text{ mW/cm}^2$ , $\lambda = 870\text{ nm}$                       | $V_O$           |      | 450                 |      | mV                                      |
| Short circuit current   | $E_e = 1\text{ mW/cm}^2$ , $\lambda = 870\text{ nm}$                       | $I_K$           |      | 50                  |      | $\mu\text{A}$                           |
| Reverse light current   | $E_e = 1\text{ mW/cm}^2$ , $\lambda = 870\text{ nm}$ , $V_R = 5\text{ V}$  | $I_{ra}$        |      | 55                  |      | $\mu\text{A}$                           |
|   | $E_e = 1\text{ mW/cm}^2$ , $\lambda = 950\text{ nm}$ , $V_R = 5\text{ V}$  | $I_{ra}$        | 30   | 60                  |      | $\mu\text{A}$                           |
| Temperature coefficient of $I_{ra}$   | $E_e = 1\text{ mW/cm}^2$ , $\lambda = 870\text{ nm}$ , $V_R = 5\text{ V}$  | $TK_{I_{ra}}$   |      | -0.1                |      | %/K                                     |
| Absolute spectral sensitivity   | $V_R = 5\text{ V}$ , $\lambda = 870\text{ nm}$                             | $s(\lambda)$    |      | 0.55                |      | A/W                                     |
| Angle of half sensitivity   |  | $\varphi$       |      | $\pm 20$            |      | deg                                     |
| Wavelength of peak sensitivity  |  | $\lambda_p$     |      | 940                 |      | nm                                      |
| Range of spectral bandwidth   |  | $\lambda_{0.5}$ |      | 790 to 1050         |      | nm                                      |
| Quantum efficiency  | $\lambda = 950\text{ nm}$  | $\eta$          |      | 70                  |      | %                                       |
| Noise equivalent power  | $V_R = 20\text{ V}$ , $\lambda = 950\text{ nm}$                            | NEP             |      | $3 \times 10^{-14}$ |      | $\text{W}/\sqrt{\text{Hz}}$             |
| Detectivity   | $V_R = 20\text{ V}$ , $\lambda = 950\text{ nm}$                            | $D^*$           |      | $3 \times 10^{12}$  |      | $\text{cm}^2/\sqrt{\text{Hz}}/\text{W}$ |
| Rise time   | $V_R = 50\text{ V}$ , $R_L = 50\text{ }\Omega$ , $\lambda = 820\text{ nm}$ | $t_r$           |      | 2.5                 |      | ns                                      |
| Fall time   | $V_R = 50\text{ V}$ , $R_L = 50\text{ }\Omega$ , $\lambda = 820\text{ nm}$ | $t_f$           |      | 2.5                 |      | ns                                      |


**BASIC CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)


Fig. 1 - Reverse Dark Current vs. Ambient Temperature




Fig. 2 - Relative Reverse Light Current vs. Ambient Temperature




Fig. 3 - Reverse Light Current vs. Irradiance




Fig. 6 - Relative Spectral Sensitivity vs. Wavelength




Fig. 4 - Reverse Light Current vs. Reverse Voltage




Fig. 7 - Relative Radiant Sensitivity vs. Angular Displacement





Fig. 5 - Diode Capacitance vs. Reverse Voltage



PACKAGE DIMENSIONS in millimeters



Drawing-No.: 6.544-5185.01-4

96 12198



## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.